University of Rhode Island

DigitalCommons@URI

SURFO Technical Reports

Graduate School of Oceanography

2006

SURFO Technical Report No. 2006-02

SURFO

Follow this and additional works at: https://digitalcommons.uri.edu/surfo_tech_reports

Recommended Citation

SURFO, "SURFO Technical Report No. 2006-02" (2006). *SURFO Technical Reports*. Paper 6.
https://digitalcommons.uri.edu/surfo_tech_reports/6

This Periodical is brought to you for free and open access by the Graduate School of Oceanography at DigitalCommons@URI. It has been accepted for inclusion in SURFO Technical Reports by an authorized administrator of DigitalCommons@URI. For more information, please contact digitalcommons-group@uri.edu.

Papers from
the
**SUMMER UNDERGRADUATE RESEARCH FELLOWSHIP
PROGRAM IN OCEANOGRAPHY**

at

THE UNIVERSITY OF RHODE ISLAND
Graduate School of Oceanography
and
Department of Ocean Engineering

NARRAGANSETT, RHODE ISLAND

June - August 2006

This program was supported jointly by
The Department of Defense ASSURE Program and
The National Science Foundation REU Program (OCE-0552606).

GSO Technical Report No. 2006-02

**PARTICIPANTS IN THE 2006
SUMMER UNDERGRADUATE RESEARCH
FELLOWSHIP PROGRAM IN OCEANOGRAPHY**

FELLOWS

Katie J. Clegg	University of Maine, Orono, ME
Alicia Colabella	Hamilton College, Clinton, NY
Robert Dubuc III	University of Oregon, Eugene, OR
Xue Fan	McGill University, Montreal, QU
Amy L. Fearing	Rensselaer Polytechnic Institute, Troy, NY
Graham E. Lau	York College of Pennsylvania, York, PA
Stephanie Luberd	Minnesota State University, Mankato, MN
Elizabeth Petrik	Amherst College, Amherst, MA
Dana M. Reznik	Ohio Wesleyan University, Delaware, OH
Corin M. Schowalter	Louisiana State University, Baton Rouge, LA
Joseph W. Swearman	Penn. State University, University Park, PA

ADVISORS

Peter Cornillon
Kathy Donohue
Brian Heikes
Katie Kelley
Roger P. Kelly
John King
S. Bradley Moran
Rebecca S. Robinson
Tatiana A. Rynearson
Yang Shen
Vitalii Sheremet
David C. Smith
David S. Ullman
Randy Watts

PROGRAM ASSISTANTS

Cristin Ashmankas, Kim Carey & Rhonda Kenny

PREFACE

This report presents the papers written by the 11 participants in the 2006 Summer Undergraduate Research Fellowships in Oceanography (SURFO) program at the Graduate School of Oceanography (GSO), University of Rhode Island (URI). This past summer represented the 20th year in which the program has been coordinated and extended through the several disciplines in oceanography and ocean engineering at URI's Narragansett Bay Campus. The 2006 program continued excellence beyond the official duration of the program with at least two projects presented at the annual ASLO national meeting..

During the fall of 2005 advertisements were sent to physics, chemistry, biology and geology departments, including faculty advisors at a number of minority colleges. Flyers and overheads were provided to colleagues presenting invited talks at various undergraduate institutions. The SURFO web site has continued to be updated and more useful links describing possible research programs at GSO/URI have been added. We received 88 applications for the program, and about 97% of these applicants used the electronic application form. This represents a significant increase in electronic applications from ~two-thirds in previous years to the present 97%. Eleven students were selected for the program with a breakdown by oceanographic discipline as follows: 4 Geological, 3 Physical, 2 Chemical, 1 Biological, 1 Astrobiological. The gender break-down was a female majority (8 female, 3 male) and one participant was from an under-represented group in science.

The duration of the SURFO program for the summer of 2006 was decrease from 11 to 10 weeks as a means to avoid scheduling conflicts with students attending undergraduate institutions on the trimester plan. This change allowed us to delay the start of the program, so nearly all of the students could participate in the full 2-week orientation period. The orientation period began with a breakfast to welcome the new students and introduce them to the GSO campus community, and was followed by a tour of the campus and facilities. For the first 5 work days, daily background/introductory seminars were presented by faculty and graduate students from the various sub-disciplines of oceanography. The seminars included overviews of the history of oceanography, biological oceanography, marine and atmospheric chemistry, marine geology & geophysics, and physical oceanography. One of the SURFOs spent the first month of the program at sea, so many of the issues covered in the orientation were revisited by the PI after the cruise. During the remainder of the program on Tuesdays, GSO faculty members or marine scientists presented weekly seminars on “hot topics” in oceanography. We were fortunate this year to have 3 new female faculty members (part of the NSF ADVANCE initiative) present their research. On Thursdays of each week, a professional development workshop or discussion was held to round-out the students experience. Topics such as “learning/research styles”, “scientific writing and effective presentations”, “hands-on modeling methods”, and “science ethics” were provided.

We continued an informal round-table meeting with several faculty members, graduate students and SURFOs to discuss how to get into graduate school and what will be expected of them. We also conducted a similar round-table format to discuss possible careers in oceanography and other STEM fields. Our exit questionnaires revealed that students found these seminars interesting and very useful, and the exposure to a wide range of disciplines/research topics helped students identify additional areas of interest. Other undergraduates (NOT affiliated with the SURFO program) and even graduate students at GSO also attend many of these seminars. The SURFO students also participated in additional seminars provided by Dr. Padma Venkatram an of the Student Diversity Office at URI who invited researchers from under-represented groups to give formal science lectures and informal round-table discussions about careers in the sciences. Several of the students also attended a series of Metcalf Lectures given by notable environmental science journalists.

Included in the summer events was our annual day of kayaking on Ninigret Salt Pond, led by Bob Sand, to investigate the flora and fauna of a salt pond lagoon. We also had a rather invigorating experience with a fast-moving thunderstorm while on the salt pond to round-out our interdisciplinary field experience. A subset of SURFOs also participated in a series of field days funded by other projects where water sampling and fish trawls were made at several locations in Narragansett Bay and Rhode Island Sound. We also continued with our tradition of having informal noon-time barbecues every other Friday for the SURFOs on the Knauss Quad. This provided the SURFOs with a taste of graduate-student life in an informal setting where they were able to meet with GSO faculty, graduate students and staff. The annual SURFOs vs ADVISORS softball game was won by the advisors, which continued the advisors undefeated streak.

One measure of success of our program is if fellows continue on with graduate studies in science and, specifically, in oceanography or ocean engineering. The exit questionnaire and follow-up conversations indicate that 11 of 11 the students definitely plan to continue on with graduate studies in science/engineering. Of these, 8 said they are seriously considering oceanography.

The participants in the 2006 SURFO program are grateful to the Department of Defense ASSURE Program and the National Science Foundation REU program for their support of the program through grant OCE-0552606. The NASA Astrobiological Institute at GSO/URI (Steve D'Hondt, David Smith and Art Spivack) also provide supplemental funds for Dana Reznik. Yang Shen also provided additional support for Robert Dubuc III to participate in the SURFO program with funding from his NSF grant OCE-0241655.

The SURFO participants and I would like to thank all of those individuals at URI who contributed to the program's success including those who advised the students and who gave SURFO seminar presentations. In addition, our thanks to Rhonda Kenny and Kim Carey for their assistance in the preparation of this report as well as the administrative, financial and recruitment tasks. Finally, we would like to thank Cristin Ashmankas who served as a graduate coordinator for the program, Bob Sand for guiding the kayak trip, and Dr. Scott Rutherford and Brooke Longval for participating in the kayak trip.

Robert A. Pockalny
SURFO Site Director

A handwritten signature in black ink, appearing to read "Robert A. Pockalny", is written over a light gray rectangular background.

TABLE OF CONTENTS

	<u>Page Number</u>
Participants in the 2006 Fellowship Program	i
Site Director's Preface	ii
1. Coastal Deglacial Diatom-bound $\delta^{15}\text{N}$ Record from Palmer Deep, Antarctica <i>Katie J. Clegg and Rebecca S. Robinson</i>	1
2. The Effects of Slab Composition and Mantle Processes in Magma Generation at the Indonesian Subduction Zone <i>Alicia Colabella and Katie Kelley</i>	5
3. The Coupling of Tsunami and Seismic Energy <i>Robert Dubuc III and Yang Shen</i>	10
4. The Effect of Density Stratification and a Cape in a Baroclinic Western Boundary Current Separation Experiment <i>Xue Fan, Peter Cornillon, Andrew Eichmann and Vitalii Sheremet</i>	17
5. Sea Surface Height Variability in the Kuroshio Extension <i>Amy L. Fearing, Kathleen A. Donohue and D. Randolph Watts</i>	22
6. PCR Optimization and Comparative Sequence Analysis of Metabolic Genes between Isolates of the Diatom <i>Ditylum brightwellii</i> <i>Graham E. Lau and Tatiana A. Rynearson</i>	26
7. Behavior of Ice Formaldehyde Mixtures under Simulated Polar Conditions <i>Stephanie Luberdia and Brian Heikes</i>	32
8. Characterizing Flow Processes in Narragansett Bay Using Reciprocal Transmission Sonar <i>Elizabeth Petrik and David S. Ullman</i>	36
9. The Search for Hydrogenase Activity in <i>Psychromonas kaikoe</i> , a Piezophilic, Facultative Anaerobic, Marine Bacterium <i>Dana M. Reznik and David C. Smith</i>	43
10. Analysis of the Historical Nutrient Input to Greenwich Bay, RI: Geochemical Evidence for trends in Eutrophication from Sediment Cores <i>Corin M. Schowalter, Danielle Cares, Clifford Heil, Mark Cantwell, John King</i>	47
11. Variability in Coastal Groundwater Radium Activity: Implications for Radium-derived Residence Time and Groundwater Flux <i>Joseph W. Swearman, S. Bradley Moran, and Roger P. Kelly</i>	51

A coastal deglacial diatom-bound $\delta^{15}\text{N}$ record from Palmer Deep, Antarctica

Katie J. Clegg,¹ and Rebecca S. Robinson

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. Here we measured diatom-bound $\delta^{15}\text{N}$ as a measure of nutrient consumption in the surface Antarctic in a sediment core from Palmer Deep. Palmer Deep is a small basin near the Antarctic Peninsula. This high-resolution core contains a record of environmental changes within the seasonal ice zone during the deglaciation and through the Holocene. We compare the diatom-bound $\delta^{15}\text{N}$ to magnetic susceptibility, opal, diatom assemblage changes, and bulk sedimentary $\delta^{15}\text{N}$ downcore in ODP Site 1098 from Palmer Deep. The early Holocene is marked by high inputs of lithogenics, high levels of productivity, stratification, and surface nutrient depletion. The mid Holocene experienced longer open-ocean periods, decrease in stratification, and an increase in upwelling of nutrient-rich water. During the late Holocene, nutrient consumption rose slightly with an increase in the deposition of lithogenics and a decrease in productivity, suggesting that nutrient supply was diminished.

1. Introduction

In the Southern Ocean sea-ice is one of the main ecosystem drivers (Tynan, 1998; Smith and Nelson, 1986). The Seasonal Ice Zone is defined as the region where the surface ocean is covered by ice during the winter and has open water for some period during the summer months (Fig. 1). When the ice edge melts back, a thin layer of fresher melt water serves to stabilize the surface ocean, light limitation is relieved, and iron that has accumulated with dust on the ice surface is potentially added. These highly favorable growth conditions result in ice-edge diatom blooms during the summer months (Smith and Nelson, 1986; Sedwick and DiTullio, 1997). High degrees of nutrient consumption have been observed in the stratified surface layer in conjunction with the diatom blooms.

One of the primary goals of this project was to evaluate the relative changes in nutrient consumption under varying amounts of seasonal ice cover. To do so, we measured the N isotopic composition of diatom-bound organic matter as a measure of nutrient consumption, in ODP Site 1098, from Palmer Deep. Palmer Deep is a small basin 10km offshore of the western edge of the Antarctic Peninsula (Fig. 2). It has a sill depth of about 200m, has high sediment accumulation rates on the order of 260 cm/ky (Shipboard Scientific Party, 1999), and contains a continuous record through the Holocene (Domack et al., 2001). Palmer Deep is within the seasonal ice zone and is only ice-free for about 4 months a year (Shipboard Scientific Party, 1999).

There are several water masses that influence the Palmer Deep region off the Antarctic Peninsula. Antarctic Surface Water resides in the upper 100-150m of the water column and is characterized by high oxygen concentrations and lower nutrient concentrations (Smith et al., 1999). Below this at about 200m is the Upper Circumpolar Deep Water (UCDW) characterized by low levels of oxygen and high nutrient concentrations. This located at about the sill depth of Palmer Deep so it is possible that at times it may be influenced by this low oxygen-high nutrient water mass (Smith et al., 1999).

Sedimentary N isotope records may allow for the reconstruction of nitrate consumption at the sea surface through time. Isotope fractionation occurs when organisms

Figure 1: Map of the seasonal ice zone around Antarctica (yellow) as well as the Antarctic Polar Front (blue) and Sub Antarctic Front (Red).

Figure 2. Bathymetric map of Ocean Drilling Project Leg 178. Study site for this project is 1098, Palmer Deep, a small basin off the Antarctic Peninsula. (www.odp.tamu.edu).

¹Now at the University of Maine

take up nitrate (NO_3^-). Diatoms preferentially take up $^{14}\text{NO}_3^-$ so that as the nitrate pool is drawn down, it is becoming enriched in $^{15}\text{NO}_3^-$. A parallel increase occurs in the organic N that is produced and spatial variations in nitrate consumption have been shown to be mirrored by the surface sedimentary $\delta^{15}\text{N}$. $\delta^{15}\text{N}$ is calculated by,

$$\delta^{15}\text{N} = (^{15}\text{N}/^{14}\text{N}_{\text{sample}})/(^{15}\text{N}/^{14}\text{N}_{\text{standard}})*1000$$

where the standard used is atmospheric N_2 . In this study, diatom-bound $\delta^{15}\text{N}$ is measured instead of the more standard bulk sedimentary $\delta^{15}\text{N}$. Bulk measurements record the $\delta^{15}\text{N}$ of the entire food web and have the potential to be altered over time by chemical or biological processes (Robinson et al., 2004; Sigman et al., 1999). The $\delta^{15}\text{N}$ values can be changed, either being increased or decreased falsely, and it is impossible to know that if there is diagenetic effect if it was constant over space and time, so it is not possible to correct for it. Diatom-bound is measured to eliminate the risk of diagenesis while at the same time measuring the $\delta^{15}\text{N}$ of the surface ocean where diatoms live. The draw back to diatom-bound measurements is that it is not yet known if diatom assemblage changes alter the $\delta^{15}\text{N}$ measurements. In the second part of this paper, we will compare the bulk and diatom-bound $\delta^{15}\text{N}$ records from Palmer Deep. Since sedimentation rates at Palmer Deep are extremely high and its core contains relatively high concentrations of organic material the diatom-bound and bulk $\delta^{15}\text{N}$ records were expected to be quite similar. This is true for the lower portion of the record but not for the upper third.

2. Materials and Methods

The diatom-bound $\delta^{15}\text{N}$ was measured from a sediment core retrieved from Palmer Deep, Antarctica (65°S , 66°W). This core represents a high-resolution record of the Holocene from the Last Glacial Maximum (LGM). It is observed to have primary laminations indicating that it is relatively undisturbed by benthic organisms giving us a continuous, undisturbed record of the Holocene.

The diatoms were physically separated via a protocol adapted from Robinson et al., 2004. The $<63\mu\text{m}$ opal fractions were treated with a series of chemical cleanings to remove both metals and exterior organic N that may be on the outside of the diatom opal (Robinson et al., 2005). A reductive cleaning using sodium dithionite is followed by an oxidation with 30% hydrogen peroxide in a boiling water bath and then with perchloric acid at 100°C .

2.1. Measurements

Once clean and dry, the diatoms are oxidized with an alkaline potassium persulfate reagent that converts organic nitrogen (ON) to nitrate (NO_3^-). NO_3^- concentrations are measured to determine the N content of the opal. Finally, the NO_3^- sample is utilized for the isotopic measurement where denitrifying bacteria convert the NO_3^- to N_2O (Robinson et al., 2004). Isotope analyses were standardized to the potassium nitrate reference IAEA-N3 (4.7‰). Corrections were also made to each sample to account for the persulfate blank.

The age model we used is based on data from Domack et al., 2001. We used Domack's 39 ^{14}C age dates from Site 1098. A polynomial was fit to the age versus depth (in mcd) curve and the age of our samples was calculated from the polynomial.

3. Results

The $\delta^{15}\text{N}$ profile from Palmer Deep is shown in Figure 3, and it has been fit to an age model adapted from Domack et al., 2001. The profile shows higher $\delta^{15}\text{N}$ values at the beginning of the Holocene after deglaciation, followed by a low, and then a slight increase towards the present. The bulk $\delta^{15}\text{N}$ and opal data are also shown (Dunbar, personal communication) (Fig. 4). The bulk $\delta^{15}\text{N}$ shows a similar trend to the diatom-bound $\delta^{15}\text{N}$ data, with the exception of the late Holocene interval. The opal data, an indicator of primary productivity, shows extremely high levels of

Figure 3. Diatom-bound $\delta^{15}\text{N}$ from Palmer Deep.

Figure 4. Diatom-bound $\delta^{15}\text{N}$, Magnetic Susceptibility, Opal Content, and bulk $\delta^{15}\text{N}$ from Palmer Deep, separated into Early, Mid, and Late Holocene.

productivity in the early Holocene, continued high levels during the mid Holocene, and decreased levels of productivity in the late Holocene towards present. The magnetic susceptibility (MS) data in Figure 4 was adapted from Acton et al., 2001. It shows high inputs of lithogenics in the early Holocene, lower lithogenic deposition in the mid Holocene, and an increase in lithogenics in the late Holocene towards present.

4. Discussion

4.1 Early Holocene

For discussion purposes we have defined three episodes in the Holocene history of Palmer Deep: the early, mid, and late Holocene (Fig. 4) based upon the variation observed in the diatom-bound $\delta^{15}\text{N}$ and MS records, primarily. In the early Holocene, the $\delta^{15}\text{N}$ show higher ^{15}N during this period, indicating higher nutrient consumption. MS and opal fluxes are also higher during this period. Thus it seems that the early Holocene was a time of relatively high surface productivity with high inputs of lithogenic material from land. The elevated lithogenic content has been interpreted previously as an indication of high rates of erosion due to significant amounts of ice along the Peninsula (Acton et al., 2001). In addition, this period of the Holocene is also marked by higher numbers of *Chaetoceros* spores. *Chaetoceros* spores are indicative of high productivity, nutrient depletion, sea-ice, melt water, and thus stratification (Leventer et al., 2002). There are also high levels of the ice-loving diatom species *F. curta* and low levels of the open-ocean diatom species *F. kerguelensis* (ODP Leg 178 Shipboard Scientific Party, 1999). The evidence for the presence of ice, high productivity, and relatively high degrees of nutrient utilization indicate that the surface waters overlying Palmer Deep were likely near the retreating ice edge for a significant portion of the summer months such that strong stratification occurs, establishing prime conditions for large-scale diatom blooms.

4.2. Mid Holocene

Following the early Holocene, the mid Holocene exhibits lows in $\delta^{15}\text{N}$ indicating less nutrient consumption. The MS also exhibits very low values, indicating a much lower input of lithogenics. Productivity remained relatively high during this period as shown in the opal data. There is also an increase in the presence of the open-ocean diatom *F. kerguelensis* and a decrease in both *Chaetoceros* spores and the ice-loving diatom *F. curta*. This leads to the inference of prolonged periods of open-ocean and a decrease in ice-cover during this period. Since there is far less nutrient depletion in the mid-Holocene relative to the early Holocene but still relatively high levels of productivity, there must have been an increase in the supply of nutrients. We attribute this to weaker or less prolonged stratification of the surface ocean and an increase in the upwelling of nutrient-rich water, possibly from the UCDW, because UCDW occurs at a depth at about 200m (Smith et al., 1999) and Palmer Deep has a sill depth of the same depth it is possible that these waters made it into the basin

and carried with them low oxygen levels and high nutrient concentrations.

4.3. Late Holocene

The late Holocene shows a slight increase towards the present in $\delta^{15}\text{N}$, indicative of either nutrient depletion or a decrease in nutrient quality. There was an increase in lithogenics to the area as indicated in the increase in MS that may indicate a return of the influence of ice. However, unlike the high MS episode during the early Holocene, the latest Holocene was a time of very low productivity, as indicated by the opal accumulation data. In addition, there are still more open-ocean diatoms, *F. kerguelensis* relative to the *Chaetoceros* spores and ice-loving species. The evidence for enhanced consumption of nutrients despite lower overall demand (lower production) suggests that nutrient supplies were weaker. This, taken with the evidence for more ice, suggests that perhaps supply of nutrients was cut off due to surface stratification but that somehow bloom conditions were not met. On the other hand, the presence of open ocean diatoms indicates that stratification can not have been the dominant surface condition. At present, we are not sure what was happening during the late Holocene.

4.4. Bulk Vs Diatom-Bound $\delta^{15}\text{N}$ Measurements

The diatom-bound and bulk measurements seem to correlate well for the early and mid Holocene. Figure 5 shows the bulk and diatom-bound profiles; they both show an elevated $\delta^{15}\text{N}$ at the early Holocene followed by a decrease in the mid Holocene. The bulk profile shows a continuing decrease into the late Holocene, while the diatom-bound shows an increase in $\delta^{15}\text{N}$. This difference may be due to diagenetic alteration of the bulk isotopic signal. Since the interval that shows some difference in the general trend is also the interval of lowest opal and overall accumulation rates, one could infer that under lower flux conditions the bulk is more likely to be altered (Robinson et al., 2005). Since the bulk measurements may undergo diagenesis, diatom-bound measurements have a potential to be more accurate and indicative of surface biogeochemistry. More comparisons of diatom-bound and bulk measurements need to be made to prove the accuracy.

Figure 5. Comparison of diatom-bound and bulk $\delta^{15}\text{N}$ profiles at Palmer Deep. (Bulk from Dunbar, pers. comm.).

5. Conclusions

The diatom-bound $\delta^{15}\text{N}$ along with MS and opal data gives insights in to nutrient status changes at Palmer Deep throughout the Holocene. The profile shows the greatest nutrient utilization during the early Holocene, and is accompanied by the highest opal fluxes and lithogenic input, likely related to the presence of sea ice. Surface stratification due to the seasonal ice retreat is thought to have primed conditions for large diatom blooms and the extensive draw down of NO_3^- . During the mid Holocene, nutrient consumption was lower but production was still relatively high suggesting that the supply of nutrients to the region must have been greater. Conditions during the late Holocene are not yet fully understood, more data from coastal locations are needed to understand the full picture as well as comparisons of bulk and diatom-bound data. Diatom-bound measurements have the potential to increase the accuracy of $\delta^{15}\text{N}$ profiles, however more work needs to be done to be certain of its accuracy. This preliminary work in Palmer Deep sets the stage for more diatom-bound work within the coastal region adjacent to Antarctica.

Acknowledgments. We thank the Department of Defense ASSURE Program and the National Science Foundation REU Program for funding the SURFO program at the University of Rhode Island, Dr. Rebecca Robinson for continued guidance throughout the project, Dr. Robert Dunbar, Stanford University, for providing additional data, Dr. Daniel Sigman, Princeton University, for providing assistance, facilities, and equipment for $\delta^{15}\text{N}$ measurements, Julie Fliegler for assistance in lab, and Cristin Ashmankas and Dr. Robert Pockalny for their dedication to the University of Rhode Island's SURFO Program.

References

- Acton, G. et al. (2001). Palmer Deep composite depth scales for leg 178 sites 1098 and 1099. www-odp.tamu.edu.
- Altabet, M and Francois, R. (1994). Sedimentary nitrogen isotopic ratio as a recorder for surface ocean nitrate utilization. *Global Biogeochemical Cycles* 8, 103-116.
- Domack, E. et al. (2001). Chronology of the Palmer Deep site, Antarctic Peninsula: a Holocene paleoenvironmental reference for the circum-Antarctic. *The Holocene* 11, 1-9.
- Leventer, A. et al. (2002). Laminations from the Palmer Deep: A diatom-based interpretation. *Paleoceanography* 17.
- ODP Leg 178, Shipboard Scientific Party, Palmer Deep (Sites 1098 and 1999).
- Robinson, R. et al. (2004). Revisiting nutrient utilization in the glacial Antarctic: Evidence from a new method for diatom-bound N isotopic analysis. *Paleoceanography* 19.
- Sedwick, P. and DiTullio, G. (1997). Regulation of algal blooms in Antarctic shelf waters by the release of iron from melting sea ice. *Geophysical Research Letters* 24, 2515-2518.
- Sigman, D. et al. (1999). The isotopic composition of diatom-bound nitrogen in Southern Ocean sediments. *Paleoceanography* 14, 118-134.
- Smith, D. et al. (1999). Hydrography and circulation of the West Antarctic Peninsula Continental Shelf. *Deep-Sea Research I* 46, 925-949.
- Smith, W and Nelson, D (1986). Importance of Ice Edge Phytoplankton Production in the Southern Ocean. *Bioscience* 36, 251-257.
- Tynan, C. (1998). Ecological importance of the Southern Boundary of the Antarctic Circumpolar Current. *Nature* 392, 708-710.

Katie J. Clegg, and Rebecca S. Robinson, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (katie.clegg@umit.maine.edu, rebecca@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

The effects of slab composition and mantle processes in magma generation at the Indonesian Subduction Zone

Alicia Colabella¹ and Katie Kelley

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. At subduction zones, H₂O driven from the subducting plate plays a major role in magma production and is thought to be the main cause of arc volcanism in these regions. Recent studies, however, increasingly favor pressure-release from upward mantle flow as a secondary driver of mantle melting. Direct studies of H₂O in subduction zone magmas are made possible through igneous phenocrysts, which often trap a small portion of the early magma (i.e., melt inclusions) during crystallization prior to the eruptive degassing that removes H₂O from the melt. Examining melt inclusions from island arcs worldwide reveals original magmatic H₂O contents up to 6-8 wt.%, coincident with enrichments in fluid-mobile trace elements derived from the subducting slab. Island arc basalts in Indonesia are unique because their melt inclusions reveal that this region has unusually low primary H₂O contents of ~0.5-2 wt.%. These low H₂O contents are similar to mid-ocean ridge basalts and may indicate pressure-release as an independent cause of mantle melting. This study used the Laser Ablation Inductively-Coupled Plasma Mass Spectrometer (LA-ICPMS) to analyze the trace element chemical composition of olivine-hosted melt inclusions found in scoria and tephra from two volcanoes in Indonesia (Galunggung and Tambora). Here we show that rare earth element patterns and Nb/Y ratios in these melt inclusions, paired with existing H₂O data, constrain several important features of the melting process beneath Indonesia. These new data illustrate the main differences between the two volcanoes, namely variability of slab additions along the arc and evidence of different mantle sources present beneath these volcanoes. Our data also clearly display the extent to which slab-derived H₂O has contributed to mantle melting beneath Indonesia. Ultimately we were able to establish a resolvable distinction between water flux and decompression melting in Galunggung and Tambora.

1. Introduction

The processes that lead to mantle melting at subduction zones are complex. Magma generation in these regions is largely thought to be caused by water influx from the dehydrating, subducting slab into the overlying wedge of mantle (Figure 1). The added water lowers the mantle melting temperature, in a fashion similar to the way salt lowers the melting temperature of ice (i.e., solidus depression). Water therefore acts as a flux in the mantle wedge, allowing the mantle to melt when it otherwise would not (Figure 2, top). Recent melt inclusion data from subduction zone volcanoes show high water contents (~6-8 wt.%) coincident with enrichments of fluid mobile elements, further supporting the flux melting hypothesis (e.g., Roggensack et. al. 1997; Wallace, 2005). Previous studies of melt inclusions from Indonesia, however, reveal much lower water contents of <0.5-2 wt.%, similar to the water contents found in mid-ocean ridge basalts and back arc basins (Sisson and Bronto, 1998; Stolper and Newman, 1994; Michael, 1988). These low water contents are significant because they indicate that the magma generation occurring in this “dry” arc can not be solely attributed to H₂O-flux melting and there is likely a second type of melting occurring in these regions (Sisson and Bronto, 1998). This alternate melting is similar to the process that creates magma beneath mid-ocean ridges, whereby upwelling mantle crosses the anhydrous mantle solidus through adiabatic decompression and causes melting in the absence of elevated H₂O (Figure 2 also, bottom).

This study focuses on the composition of olivine-hosted melt inclusions from two volcanoes, Galunggung volcano in western Java and Tambora volcano in Sumbawa. Melt inclusions often trap samples of the original magma before it degases upon eruption, preserving the concentrations of H₂O and CO₂ in the magma before these volatiles are lost (Lowenstern, 2003). Melt inclusions are the only means by which we may directly study the concentrations of dissolved volatiles in magma. These tiny inclusions may also preserve the composition of the magma before magma

Figure 1. Cross section of a subduction zone. Black arrows indicate relative plate motions. Shaded arrows indicate processes leading to mantle melting and magma formation.

¹ Now at Hamilton College, Clinton, NY

Figure 2. The top diagram shows the necessary conditions under which a mantle that has experienced water additions will melt. Water addition expands the conditions under which the mantle will melt. The bottom diagram shows the anhydrous mantle solidus and the upwelling path by which normal, “dry” mantle crosses the dry solidus through decompression in order to melt. The star and arrow represent an adiabatic path approaching the dry solidus.

chamber pooling or crystal fractionation (Lowenstern, 1995). Because of these characteristics, melt inclusions provide us with a means by which to examine and compare the original magmatic volatile and trace element composition in order to evaluate the specific relationship of volatiles to melting processes occurring at the Indonesian subduction zone.

This study used a set of pre-existing ion probe volatile data (H_2O , CO_2) to confirm previously recorded low water contents in Indonesia, and here we present new laser ablation inductively coupled plasma mass spectrometer (LA-ICPMS) trace element data for these same melt inclusions. This work uses these new data to assess compositional differences between these two Indonesian volcanoes and to evaluate the cause of mantle melting, independent of slab additions, in the unique, “dry” Indonesian subduction zone.

2. Samples and Methods

2.1. Samples

The samples used in this study were collected from Galunggung and Tambora volcanoes, located at opposite

Figure 3. Location map of Indonesia indicating the positions of Galunggung and Tambora volcanoes.

ends of the Indonesian arc (Figure 3). Basaltic scoria samples from Galunggung volcano (samples G2 and Gal20298) were collected in real-time by Sutikno Bronto during a volcanic eruption in 1983, and these samples also provided melt inclusions that were subject to prior study (Sisson and Bronto, 1998). Fine-grained basaltic tephra (samples TB-188, -185, -183) from Mt. Tambora were collected by Haraldur Sigurdsson from the Black Sands unit, a glass-rich phreatomagmatic deposit. Olivine crystals were hand-picked from crushed and sieved samples, and crystals containing melt inclusions were identified in a mineral oil immersion and removed for further analysis. We focus on olivine crystals for this study because they form early in basaltic magmas, trapping in their melt inclusions the most primitive magma.

2.2. Preparatory Methods

We sorted through volcanic tephra samples from Galunggung and Tambora using a binocular microscope to identify olivine phenocrysts containing melt inclusions. We then placed inclusion-bearing crystals on individual 1” circular glass slides with a thin coating of vacuum grease. The crystals were oriented to place the face of the crystal closest to the melt inclusion(s) towards the greased side of the slide. We piled one eyedropper full of orthodontic resin powder onto the crystal followed by approximately 5-6 drops of orthodontic resin liquid. This combination creates a solution that hardens in approximately ten minutes and can be easily slid off the slide with a razor. Each mounted crystal was then polished using 40, 30, 15, 9, 6, 3, and 1 μm Al_2O_3 polishing papers until the melt inclusion became exposed and polished at the surface. To determine when a melt inclusion is exposed it is helpful to utilize a petrographic microscope with reflected light capability, as the contrast between the crystal and inclusion glass exposed at the surface are highlighted using reflected light. Melt inclusions appear darker than their surrounding olivine host when exposed and polished, and the glass usually acquires a smoother polish than the olivine. Final polishing was performed using a grinding wheel and 0.3 μm loose alumina grit. We then removed crystals from the resin by using a fine point soldering iron set at 375° F, which melts the surrounding resin. Once a suite of melt inclusions was

prepared, we remounted all exposed inclusions together in one 1" round resin mount. This final mount was then polished to reveal a smooth surface ready for the laser ablation inductively coupled plasma mass spectrometer.

2.3. Analytical Methods

The UP-213 Laser Ablation System (New Wave Research) and the X-Series^{II} ICP-MS (Thermo Electron Corporation) were used to analyze melt inclusion compositions. We tuned the ICP-MS using a piece of NIST-612 glass to ensure optimum sensitivity and stability. After tuning, we analyzed three standard USGS glasses with known compositions (BIR-1G, BCR-2G, and BHVO-2G), which were used to calibrate the LA-ICPMS signal for the elements of interest.

For melt inclusion analysis, we set the laser to drill a 30 μm spot continuously for 60 seconds, and we set the ICP-MS to collect data for two minutes (30 seconds of background prior to laser on, 60 seconds of laser ablation on the sample, and 30 seconds of washout after laser off; see Figure 4). We acquired data before and after drilling in order to eliminate the effects of washout from the ablation of previous samples and also to factor out the instrumental background signal. We used these methods to acquire LA-ICPMS data for 40 major and trace elements in the melt inclusions (Li, Be, Mg, Si, Ca, Sc, Ti, V, Cr, Mn, Co, Ni, Cu, Zn, Rb, Sr, Y, Zr, Nb, Cs, Ba, La, Ce, Pr, Nd, Sm, Eu, Tb, Gd, Dy, Ho, Er, Yb, Lu, Hf, Ta, Pb, Th, and U).

2.4. Data Treatment

The raw laser data from the standard glasses and melt inclusions are transformed into concentrations using a multi-step method. First, we examine the readouts and determine where the background and melt inclusion signal begin and end. When identifying the background we are sure to avoid washout from the laser in our calculations and we pay special attention to Mg when determining the signal to avoid including signal from the host olivine if the laser has drilled through the melt inclusion and into the crystal (see Figure 4). Next we average together the background time slices and the signal time slices. We then subtract the average background from the average signal to remove additions to the signal from the ambient instrumental background. We then normalize the background-subtracted counts for each element to ^{47}Ti . For the USGS glasses, we then multiply these normalized counts by the known TiO_2 concentrations of the glasses, and plot these values for a given element against the known concentrations of the element in each glass, forming a three-point linear calibration curve for each element. For the unknowns, we multiplied by an assumed TiO_2 concentration, forcing MgO to yield an arbitrary value of ~ 8 wt.%. This assumption introduces significant error into our final concentration data, since the MgO content of the melt inclusions is unknown and may vary from one inclusion to another. We mostly discuss ratios in this study, however, which eliminates this source of error. After this step, we use the linear relationships from the standard calibrations to calculate the element concentrations in the melt inclusions. Standard calibration curves were linear ($r > .999$) and repeat

Figure 4. Time-resolved laser data acquisition for melt inclusion TB-188-11. Bold lines indicate the background signal, the time at which the laser turned on, the ablation signal in the melt inclusion, ablation signal in the host olivine, and the time at which the laser switched off. The Mg signal clearly illustrates the point at which the laser drilled through the back of the melt inclusion and into the host olivine crystal. These data were acquired using a 30 μm spot setting with a 10 Hz repeat rate, at 0.75 mJ/pulse beam energy (Kelley et al., 2003).

laser analysis on BHVO-2G show reproducibility of $<2.7\%$ rsd for La and $<3.6\%$ rsd for U.

3. Results and Discussion

3.1 Results

Here we present the new LA-ICPMS data in combination with the existing volatile data set. Our data show that, in general, Tambora has higher H_2O than Galunggung, although both have low H_2O contents compared to other arcs (Figure 5). Both samples contain many inclusions with relatively high CO_2 levels (>50 ppm), confirming that many of these melt inclusions were trapped before extensive degassing took place. CO_2 is less soluble than H_2O and thus degasses almost completely before H_2O degassing begins (Figure 5). Because of this characteristic, the presence of significant CO_2 in a melt inclusion indicates that H_2O has likely not significantly degassed. This indicates then that the low H_2O contents are primary and not a result of rapid degassing during eruption (Sisson and Bronto, 1998).

Figure 5. H₂O vs. CO₂ in olivine-hosted melt inclusions from Galunggung (diamonds and squares) and Tambora (triangles, crosses, and stars).

Figure 6. Chondrite-normalized rare earth element diagram, showing REE patterns from representative melt inclusions from both Galunggung (G2) and Tambora (TB-188). A normal mid-ocean ridge basalt (MORB; Niu and Batiza, 1997) and typical arc basalt (Agrigan, Marianas, Elliott et al., 1997) are shown for reference.

Figure 7. Nb/Y vs. H₂O/Y in Indonesian melt inclusions. The bold line is the nominally anhydrous mantle array, as defined by NMORB, EMORB, and OIB (Cervantes and Wallace, 2003). Mariana trough points are also as shown by Cervantes and Wallace (2003). Arc melt inclusions from the Mexican subduction zone are plotted as well (Cervantes and Wallace, 2003).

The rare earth element (REE) patterns of these melt inclusions illustrate the overall extent of trace element variability between these two volcanoes. Trace element differences between Galunggung and Tambora are clearly evident in their REE patterns (Figure 6). Both volcanoes are enriched in light REE relative to normal mid-ocean ridge basalt, and show smoothly sloping patterns that are more like typical arc basalts (See Figure 6). Tambora, which has higher water concentrations than Galunggung, also is more enriched in light REE and has more steeply sloping REE patterns than Galunggung. Based on these observations, there are two interpretations that may explain the trace element variations here. Either these differences are a feature of the mantle beneath these volcanoes or they result from variable slab additions. In the following section, we distinguish between these two possible sources using trace element ratios.

3.2. Discussion

There are two plausible reasons for the variation and enrichment in rare earth elements in the Indonesian melt inclusions. Either the mantle source in these regions is more enriched or slab recycling is contributing to the rare earth element abundance in this area (e.g., Figure 6). In order to distinguish between these two sources we examine the relationship of Nb/Y to H₂O/Y (Figure 7). Niobium is a highly incompatible element during mantle melting, and as such it favors being in the melt. Yttrium is a mildly incompatible element meaning that it also prefers melt over the solid mantle, but not as strongly as Nb. As a result of the variation in the incompatibilities of these elements, Y in the mantle is less affected than Nb by the continual removal of melt. This causes the ratio of Nb/Y to vary significantly based on subtle differences in the progressive depletion of the mantle over geologic history. Both of these elements are fluid immobile, and we therefore assume neither has been added to the mantle from the subducting slab. These characteristics make the Nb/Y ratio highly sensitive to the mantle composition and independent of slab additions to the mantle. Higher Nb/Y indicates that the mantle is either more primitive (i.e., less depleted) or enriched (Cervantes and Wallace, 2003). H₂O/Y, on the other hand, clearly increases as H₂O is added to the arc mantle by the slab (Cervantes and Wallace, 2003).

The first inference to be made from Figure 7 is the obvious difference in mantle sources beneath these two volcanoes. Galunggung has a mantle source that is more similar to MORB and Tambora appears to more enriched, closer to EMORB. Figure 7 further shows that Tambora and Galunggung receive different contributions from the slab. Surprisingly, despite the higher overall H₂O content of Tambora melts, it is Galunggung that has larger H₂O addition from the slab (see Figure 7). This suggests that Galunggung obtains most of its low H₂O from the slab while Tambora's composition indicates that its higher H₂O is an inherent property of the mantle. As previously mentioned, water additions have a huge impact on mantle melting processes. As such, this variation that we see in slab additions between Galunggung and Tambora implies unique mantle melting processes occurring beneath the volcanic front in this region. Samples that plot below or on

the anhydrous mantle line are a result of pure pressure-release melting, while points above this line show the increasing importance of H₂O-flux melting because points above the line contain excess water from the subducting slab. Points below the line contain no slab-derived water, requiring an alternate type of melting (i.e., pressure-release). Decompression and H₂O-flux are thus both present and important beneath both of these volcanoes. Both melting processes are present, and the relative importance of slab-derived H₂O compared to other arcs is less. Decompression melting here appears as important as it is beneath back-arc basins. Without the presence of decompression melting, it is possible that H₂O-flux melting in these regions would not be substantial enough to create these volcanoes.

4. Conclusions

Our data confirm that Indonesia is an unusual arc, distinguished from others by its low H₂O contents. Our new LA-ICPMS data for olivine-hosted melt inclusions show that two Indonesian volcanoes, Galunggung in the west and Tambora in the east, show relative enrichment in the rare earth elements compared to MORBs and other island arcs, despite low overall H₂O. Furthermore, our new data demonstrate that the mantle sources beneath Tambora and Galunggung are distinct from each other. Coupling the new trace element data with existing H₂O data, we show that Galunggung has more slab-derived H₂O than Tambora, despite its lower overall H₂O concentrations. Finally, these data show that both flux melting and pressure release melting contribute to the magmas formed beneath Indonesia, and that pressure release is a major mechanism driving melting independent of slab-derived H₂O.

Acknowledgments. We thank the Department of Defense ASSURE program and the National Science Foundation's REU program for funding A.C.'s research this summer. We also thank Tom Sisson for providing the Galunggung samples, Haraldur Sigurdsson for providing the Tambora tephra samples, Richard Kingsley for assistance in the lab and Rob Pockalny for his dedication to the SURFO program.

References

- Cervantes P, Wallace P.J. (2003) Role of H₂O in subduction zone magmas: new insights from melt inclusions in high-Mg basalts from central Mexico. *Geology* 31:235-238
- Elliott, T., T. Plank, A. Zindler, W.M. White, and B. Bourdon (1997), Element transport from slab to volcanic front at the Mariana arc, *Journal of Geophysical Research*, 102 (B7), 14991-15019
- Kelley KA, Plank T (2003) Composition of altered oceanic crust at ODP Sites 801 and 1149. *Geochemistry Geophysics Geosystems* vol.4 number 6 doi:10.1029/2002GC000435
- Lowenstern J.B. (1995) Applications of silicate melt inclusions to the study of magmatic volatiles, in *Magmas, Fluids, and Ore deposits*, Ed. J.F.H. Thomson, Min. Assoc. of Canada Short Course vol. 23: 71-99
- Lowenstern JB (2003) Melt inclusions come of age: volatiles, volcanoes, and Sorby's legacy, in *Melt inclusions in Volcanic Systems: Methods, Applications, and Problems*, Ed. B. DeVivo and R.J. Bodnar. *Developments in Volcanology* 5:1-22
- Michael, P. (1988), The concentration, behavior and storage of H₂O in the suboceanic upper mantle: Implications for mantle metasomatism, *Geochimica et Cosmochimica Acta*, 52, 555-566
- Niu, Y., and R. Batiza (1997), Trace element evidence from seamounts for recycled oceanic crust in the Eastern Pacific mantle, *Earth and Planetary Science Letters*, 148 (3-4), 471-483
- Patino LC, Carr MJ, Feigenson MD (2000) Local and regional variations in Central American arc lavas controlled by variations in subducted sediment input. *Contrib Mineral Petrol* 138:265-283
- Plank T, Langmuir CH (1993) Tracing trace element from sediment input to volcanic output at subduction zones. *Nature* 362:739-742
- Roggensack K, Hervig RL, McKnight SB, Williams SN (1997) Explosive basaltic volcanism from Cerro Negro Volcano: influence of volatiles on eruptive style. *Science* 277:1639-1642
- Sisson TW, Bronto S (1998) Evidence for pressure release melting beneath magmatic arcs from basalt at Galunggung, Indonesia. *Nature* 391:883-886
- Spandler CJ, Eggins SM, Arculus RJ, Mavrogenes JA (2000) Using melt inclusions to determine parent-magma compositions of layered intrusions: application to the Greenhills Complex (New Zealand), a platinum group minerals-bearing, island-arc intrusion. *Geology* 28:991-994
- Stolper, E., and S. Newman (1994), The role of water in the petrogenesis of Mariana trough magmas, *Earth and Planetary Science Letters*, 121, 293-325
- Syracuse EM, Abers GA (2006) Global compilation of variations in slab depth beneath arc volcanoes and implications. *Geochemistry Geophysics Geosystems* vol.7 number 5 doi:10.1029/2005GC001045
- Walker JA, Roggensack K, Patino LC, Cameron BI, Matias O (2003) The water and trace element contents of melt inclusions across an active subduction zone. *Contrib Mineral Petrol* 146:62-77
- Wallace PJ (2005) Volatiles in subduction zone magmas: concentrations and fluxes based on melt inclusion and volcanic gas data. *Journal of Volcanology and Geothermal Research* 140: 217-240

The Coupling of Tsunami and Seismic Energy

Robert Dubuc III¹, and Yang Shen

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. Uncharacteristic long-period ground motions were observed at the Diego Garcia and Cocos Islands seismic stations after the 2004 Sumatra-Andaman earthquake and preceded the arrival of the tsunami wave itself. As a tsunami wave propagates across the open ocean, it is relatively uninfluenced by the ocean bottom. Once it reaches a rise in sea floor, it interacts with the bottom and loses energy. A portion of this energy is assumed to be converted into the elastic deformation of the sea floor. Deformation of the sea floor in a long period fashion could produce the long-period seismic waves that were recorded. A 2 dimensional finite-difference code was used to study this possibility. The interaction between tsunami waves and induced seismic waves at the water/ocean crust boundary is simulated on a simple rectangular gridded model. Parts of the code were modified so that the changes in pressure on the sea floor from a propagating tsunami were portrayed by point sources. These point sources correspond to gravitational pressure from a propagating tsunami and were located on top of the grid. Gravitational pressure associated with the tsunami was translated into ground displacement and served as parameters for the point sources. Synthetic long period waveforms were recorded that resembled observed data. Local bathymetry and geology had to be left out due to the limitations of the program. With further investigation, real time tsunami warning could be improved immensely.

1. Introduction

The December 26th, 2004 the Sumatra-Andaman earthquake created one of the most destructive tsunamis known to human kind. After the earthquake uncharacteristic long-period waveforms were observed at the Diego Garcia and Cocos Island seismic stations (Shen et al., 2006). As tsunami waves interact with a sharp rise in sea floor, they lose energy to reflection, bottom friction, and turbulence. The assumption is made that a portion of this energy is translated into the elastic deformation of the sea floor. This, in turn, induces the long period seismic waves that were recorded. Travel time anomalies between the actual tsunami waves and seismic waves correlate to a sharp rise in sea floor at both seismic stations which validate this assumption. (Shen et al., 2006). The period and dispersive characteristics of the seismic records also correlate to the tsunami records at near co-located tidal gauges and suggest that the ground motions were induced by the tsunami waves (Shen et al., 2006) (Fig. 1).

Changes in pressure associated with the propagating tsunami could inhibit a loading and unloading effect on the ocean bottom which would produce seismic waves. In this project the deformation of sea floor associated with gravitational pressure from propagating tsunami waves was explored. Since tsunamis are infrequent and there is not an abundance of tools in the field which measure tsunami waves and their implications, computers are needed to model this interaction. Synthetic seismic surface waves induced from point sources on the top of a rectangular 2 dimensional model are the focus of study for this paper. The point sources, located on the synthetic sea floor, are to be representative of the changing gravitational pressure from over head tsunami waves. These point sources display the loading and unloading effect the ocean bottom would endure as tsunami waves propagate over head.

Figure 1. The real seismograms and tidal gauges recorded at Diego Garcia and Cocos Islands. Notice the difference in time between the tsunami arrival at the tidal gauges and the beginning of the long period waveforms on the seismograms. Compare the seismograms to figures 10-11.

2. Methods

ELA2D, a 2D finite difference code written in Fortran, was used to simulate seismic activity on the sea floor. ELA2D was designed by Joachim Falk to model elastic isotropic media and uses elastodynamic equations for wave propagation. The code creates a rectangular 2D model consisting of grids which can each be assigned p and s -wave velocities, and density values. The model was set up so that the z -axis was depth into the interior of the earth, and the x axis was distance in the direction of the propagating tsunami. Where $z = 1$ a free surface condition was put into effect so that surface waves would propagate along the top of the model. The model was 1000 X 800

¹Now at the University of Oregon

with spacings of 58300 m in order to satisfy stability conditions. Matlab was used to view snapshots of wave propagation and synthetic seismograms (Fig. 2). The model represented ridged sea floor without water present and every grid was given the same p-wave velocity, s-wave velocity and density values of 3100 m/s, 1800 m/s and 2925 kg/m³ respectively.

Parts of the code were modified so that multiple point sources on the top of the grid could be triggered in succession, each with different characteristics. The point sources simulate sea floor displacement resulting from propagating tsunamis which induce seismic waves. The time of triggering and the distance between each point source are characterized by the velocity of the tsunami at a certain point and the spacing of grids. The point sources trigger one after another so they reflect propagating tsunami wavelets passing over head. The velocity of the tsunami waves when wavelength is much greater than ocean depth is given by the equation,

$$c = (gh)^{0.5} \quad (1)$$

where g is gravity and h is the depth of the ocean (Lay and Wallace, 1995).

Synthetic seismic waves induced from the hypothetical tsunami waves have wavelengths ranging from 792,000 m to 2,790,000 m. The model was modified to withstand such large waveforms given certain stability conditions. These include that there must be at least 10 grid points per wavelength and that,

$$V_p * (dt / dx) < 1/(2)^{0.5} \quad (2)$$

where V_p (3100 m/s) is P-wave velocity, dt (13.3 s) is the time step and dx (58300 m) is distance between grids (Virieux, 1986). Four different tsunami waveforms were picked with periods of 900s, 710s, 600s, and 440s to be the point source's origin of energy. Each point source moves up and down sinusoidally four times in a row to reflect those different period tsunami wavelets. Each point source is slightly different and reflects how the four different tsunami wavelets change as the tsunami propagates.

Since the grid spacing was so large, bathymetric features could not be included into the model. Therefore, the top of the model was assumed to be a gently rising sea floor with a slope of .393 degrees. Point sources are placed 1-3 grid space away (the last 6 point sources are always 1 grid space apart) from one another and represent the loading effect the sea floor would endure as tsunami waves pass by (Fig. 3). Each of the nine point sources displays movement for 2640 s and since they are close to one another, multiple point sources will display movement at the same time. The hypothetical tsunami interacts with the sea floor over a distance of approximately 700000 m. This creates superposition of synthetic waveforms and can be seen in the synthetic seismograms. The synthetic seismograms are located 1 to 17 grid spaces away from the last point source.

The tsunami itself is not represented in the model, only point sources that would be induced by a tsunami are present on the very top of the model. A hypothetical tsunami must be formulated in order to explain the specifications of each point source. The tsunami waves are assumed to be linear long surface-gravity waves and non-linear effects are

Figure 2. Z component snap shot from Matlab. Model is 1000 X 800 with grid spacing of 58.3 km. The Z component is vertical into the earth, and the X component is horizontal distance in the direction of the propagating tsunami. Point sources trigger left to right on top of the model.

Figure 3. The slope hypothetical tsunami waves were climbing. In reality the point sources (red dots) were located horizontally on top of the model. The first and second grid points (4000 m, 3600 m) were located 2-3 grid points away, the second and third were located 1-2 grid points away, and the rest of the point sources were located next to one another.

not taken into consideration for this project. Tsunami wavelets in 4 km of water with periods of approximately 1000 s and less travel at different velocities (Lay and Wallace, 1995). Once these different wavelets propagate into shallower water, wavelengths become relatively much greater than water depth and the waves propagate at the same velocity which depends on (1) (Mark Wimbush, personal communication). Once the four hypothetical tsunami wavelets reach where the first point source occurs and start rising from 4 km, the assumption is made that they travel at the same speed. The periods of these 4 wavelets were chosen so that this assumption was a good approximation of linear-theory tsunami propagation.

An arbitrary wave train was constructed with these wavelets in order to very roughly resemble the actual tsunami that was formed after the Sumatra-Andaman earthquake (Fig. 4). The hypothetical tsunami wavelets were

Figure 4. The hypothetical tsunami wave. Y-axis is displacement in meters. These amplitudes reflect amplitudes the tsunami would have at the first point source. X-axis is in minutes. The wave would propagate left to right. The four different period tsunami wavelets are assumed to have aligned themselves in this fashion over the deep ocean at the first point source. The periods are retained throughout all of the point sources and all 4 waveforms are assumed to travel at the same speed as they travel up slope.

Figure 5. Differences in gravitational pressure on the sea floor resulting from the propagating tsunami induces ground displacement. Ground displacement has the same period as the tsunami and propagates at the same speed. The point sources display vertical displacement and imitate this ground displacement over time at a point on the sea floor.

formed at approximately the same distance from Diego Garcia to the source of the earthquake and some shift in time between the 4 wavelets was allowed since the earthquake had a 500 s long rupture period (Yang Shen, personal communication). The 900 s, 710 s, 600 s, and 440 s periods were given velocities in the open ocean of 198 m/s, 190 m/s, 181 m/s, and 171 m/s respectively (Lay and Wallace, 1995). The arbitrary wave train was put together so that at the first point source had a smooth, continuous, decaying sinusoidal shape. The point source displacements are exactly out of phase with the tsunami water displacements. They both have the same period but different amplitude (Fig. 5).

Each successive point source is located in the model at a location that corresponds to a point on the sea floor which is 400 m shallower than the previous point source (Fig. 3). As tsunami waves propagate upward they couple with the sea floor, slow down, and change in shape. Velocity, which controls when to activate successive point sources, is given by $c = (gh)^{0.5} = \lambda/T$ where T is period and λ is wavelength. T is conserved in propagating waves so λ changes with changing velocity (Mark Wimbush, personal communication). The amplitude of the tsunami wave, which in turn effects the amplitude of the point source displacement, is given by the relation $a \sim h^{-0.25}$ where a is amplitude and h is the depth of the ocean (Lighthill, 1978). At the location of the first point source, which corresponds to the initial rise in sea floor at 4km, the tsunami wavelets were given initial amplitudes of 0.5m, 0.4m, 0.3m, and 0.2m (Fig. 4). This is relative to the real Indian Ocean tsunami which had its biggest amplitude in the open ocean of approximately 0.5 m (McKee, 2005).

The tsunami's amplitude is the gravitational driving force which induces sea floor displacement. The amplitude above and below the mean sea level creates sinusoidal loading and unloading, which corresponds to mass excess and deficit at a specific point. The amplitude of each point source is assumed to correspond only to this gravitational loading and unloading. Excess pressure on the sea floor from the peak of the tsunami wave is given by $P = pga$ where p is density of water, g is gravity and a is the tsunami amplitude. Pressure is then integrated to obtain force for every tsunami wavelet at each location. Sea floor displacement is then calculated from force. If $1/2$ wavelength is less than the grid spacing (58300m), only positive values for pressure are integrated within the grid space interval. This is so the point source receives the correct amount of force from positive pressure and the negative pressure corresponding to the tail of the tsunami within the grid spacing doesn't effect the maximum displacement of the point source. Since the point source is really not a point, but rather a 58.3 km line, this approximation gives a realistic answer for the maximum amount of force given a pressure curve over distance. If $1/2$ wavelength is greater than 58300 m, the sine function is integrated from 0 to 58300 m, so that the point source doesn't experience more load than it should over the grid space interval (Fig. 6).

$$F = \int P \cdot \sin(2\pi x / \lambda) dx \quad c = (gh)^{0.5} \quad (3)$$

$$\begin{cases} 0, & 1/2 \lambda, \text{ if } 1/2 \lambda < 58300 \end{cases} \text{ or}$$

$$\begin{cases} 0, & 58300, \text{ if } 1/2 \lambda \geq 58300 \end{cases}$$

This value gives us force due to excess pressure from the tsunami's amplitude, over the width of a grid space. The equation,

$$w = FX^2(L-X/3)/2D, \quad (4)$$

is then used to find w , sea floor displacement, where F is force over a grid space, X is $1/4 \lambda$, L is $1/2 \lambda$ and D is a stiffness constant relating Lamé coefficients and the thickness of the lithosphere. This equation was derived to find the amount of displacement on a beam with fixed ends, length L , a thickness h , and force at a specific point X

Figure 6. Force is integrated from positive pressure only over the length of the grid. If the length of positive pressure from the tsunami ($1/2 \lambda$) is greater than the length of the grid, force is integrated only over the length of the grid. Ground displacement is then found from the force value. The value obtained for ground displacement becomes an amplitude for each point source. Each point source has 4 of these amplitudes, corresponding to each tsunami wavelet.

(Turcotte and Schubert, 2005). D , a stiffness coefficient is equal to

$$D = Eh^3 / 12 * (1 - \nu^2) \quad (5)$$

where h is the thickness and is given the value 100 km, and E and ν are Young's and Poisson's ratios. The values for Young's and Poisson's were derived from the Lamé coefficients which were derived from the equations

$$b = (M / \rho)^{0.5} \quad (6)$$

$$a = ((L + 2M) / \rho)^{0.5} \quad (7)$$

where b is s-wave velocity, M is the rigidity modulus, ρ is density, L is a Lamé parameter, and a is p-wave velocity.

L is set to be $1/2 \nu$ since the pressure from the tsunami is sinusoidal and has roots every $1/2$ wavelength. The load is said to be in the middle of a beam ($x = 1/4 \lambda$) which corresponds to the maximum sea floor displacement given a certain wavelet and location. The maximum sea floor displacement is then set to be an amplitude for the point source function. Each point source has 4 different maximum sea floor displacements which correspond to each of the 4 tsunami wavelets (Fig. 7). Since L is a function of wavelength, and w is proportional to L , the displacement due to load actually decreases as the tsunami further travels up slope and slows down. Force is also proportional to w but the decrease in L is more than the increase in F as the hypothetical tsunami travels upward (Fig. 8). Excess pressure on the sea floor from the tsunami wavelet produces a negative displacement on the sea floor with the same period as the propagating tsunami. The point sources trigger in accordance to the tsunami's velocity and change as a function of depth.

Figure 7. Point source, displacement vs. time. Y axis is in meters and X axis is in minutes. Each point source displays the same periods, but the amplitudes change relative to the values for ground displacement (Fig. 8).

3. Results and Discussion

The rough, long period, sinusoidally shaped observed seismic waveforms closely resemble the shape of synthetic seismic waveforms with certain fluctuation. The 9 point sources, once triggered, created an overlapping of seismic waves which superimposed with one another to create the rough sinusoidally shaped seismogram. The initial waves on the synthetic seismogram from the main run are the largest in amplitude, period, and are the smoothest waveforms in the seismogram. It seems that these first smooth waveforms correspond to the first few point sources which had the largest displacement in the synthetic seismogram (Fig. 8). Following the initial waves are low amplitude superimposed surface waves, which have much rougher characteristics than the initial surface waves. They do, however, also retain large periods and resemble observed seismic records.

The characteristics of the synthetic seismogram from the main run resembles the Diego Garcia records quite well with larger, smoother waveforms initially, and lower amplitude, rougher waveforms following (Fig. 9). This could be because the area of coupling for the tsunami as it approaches the Diego Garcia seismic station is spread out compared to Cocos, and has many bathymetric bumps (Fig. 10). Perhaps the complex sea floor bathymetry near Diego could have effected the induced surface waves and the smooth initial seismic waveforms were relatively unaffected by super-positioning.

The synthetic waveforms on the seismogram after the initial smooth waveforms looks more like the waveforms recorded at Cocos Island (Fig. 10). This last part of the synthetic seismogram seems to be an area of more complex super-positioning due to the overlapping of many induced seismic waves. The area of interaction of the tsunami and the sea floor as it approaches Cocos Island is a relatively smooth, steep rise in sea floor. The tsunami could have influenced the sea floor many times as it traveled up this

Figure 8. Ground displacement, wavelength, force, amplitude, and pressure at different point sources. The color lines represent 900 s wavelet (blue), 710 s wavelet (pink), the 600 s wavelet (yellow), and the 440 s wavelet (light blue). Ground displacement decreases as the hypothetical tsunami propagates into shallower water.

Figure 9. Water depth the tsunami traveled over vs longitude or latitude at Diego Garcia and Cocos Island respectively.

Figure 10. Synthetic seismograms from the main run which resemble the Diego Garcia seismic recordings. The first and second point source were located 3 spaces away from one another. The second and third point source were located 2 spaces away from one another. All other point sources were located next to one another.

Figure 11. Synthetic seismograms which resemble Cocos Island seismic records. The point sources displayed dispersive characteristics as the hypothetical tsunami went upslope. In order to physically explain this, non-linear wave theory would need to be considered.

sharp slope (Fig. 9). More super-positioning of seismic waves could create rougher waveforms with less variance in amplitude like the recorded Cocos Island waveforms (Fig. 1). In fact, during one run of the program the point sources were set up so that the tsunami would have displayed dispersive characteristics as it went up slope. The first point source was one large period waveform, the second point source had two smaller period waveforms and this went on until the sixth and final point source had six small period waveforms (Fig. 11). These point sources, however, were not backed up by physics and non linear theory would need to be taken into account to describe this behavior. In reality, tsunami waves do display non linear characteristics as they travel into shallower waters and can disperse (Rivera, 2006). Non-linear behavior of tsunami waves is not within of the scope of this project and linear approximations were used to simplify the justification of point source characteristics.

The amplitude of the real seismograms versus the synthetic seismograms is approximately an order of magnitude apart from one another. The synthetic seismograms show ground movement characteristic to the sea floor rather than ground motion on land. Since Diego Garcia and Cocos Island are islands protruding from the deep ocean, the amplification of seismic waves could have

taken place as they travel towards the top of the island structures. Also, in the real seismograms no vertical displacement was recorded and only tangential and radial displacements were observed. Since the model is only 2 dimensional, this type of situation could not be explored. This could also be a product of local geology and bathymetry inherent to the island structures.

The period of the synthetic waveforms also seem to reflect the period of the point sources. The first two major waveforms in the synthetic seismograms have periods of approximately 12 to 15 minutes. The first point source displacement had a period of 15 minutes (Figs. 7 and 10). In the real seismograms the first two waveforms have periods of 15 - 25 minutes. Perhaps the period of the seismic waveforms reflect the period of the tsunami itself, although it can't be inferred from this project. Within the model, though, the period of synthetic point source surely effects the period of the synthetic seismic waveform and in fact almost matches it.

The model was set up to be a simple 2D representation of how gravitational pressure from tsunami waves might induce seismic waves on the sea floor and many more details could be taken into effect. The synthetic results do, however, validate the assumption that a tsunami interacting with the sea floor can induce seismic waveforms with very long periods. The exact numbers used for pressure, force, and displacement could differ from reality since approximations discussed earlier were put in place to give displacement values for each point source. The shape of the seismic waveform, however, does not change drastically when you change these numbers. As long as tsunami waves induce long period displacements on the sea floor, long period seismic waves should result.

4. Conclusion

The theory of tsunami waves influencing seismic waves has many implications. The exploration of this idea could eventually result in better real time tsunami warnings and also help better the understanding tsunami waves themselves. In the future, this project would have to be considered as a three dimensional problem and bathymetric and geological factors would be entered into the model. Since ELA2D is only 2 dimensional and has various limitations, only the conclusion that long period seismic waveforms can result from tsunami waves loading and unloading in the form of point sources on the sea floor can be made. The point sources do, however, mimic the tsunami's loading and unloading due to pressure quite well given the limitations of the code. More grid points with much less grid spacing would be very helpful to further investigate these phenomena.

Acknowledgments. I would like to thank Yang Shen, Zhigang Zhang, and Mark Wimbush from the Graduate School of Oceanography at the University of Rhode Island for helping me with this project. I would also like to thank Rob Pockalny and Cristin Ashmankas also from the Graduate School of Oceanography at the University of Rhode Island for organizing the 2006 Surfo Program. We thank the Department of Defense ASSURE Program and the National Science Foundation REU Program for funding the SURFO program at the University of Rhode Island,

References

- Lay, T. and Wallace, T.G., *Modern Global Seismology* (Academic Press, San Diego, 1995).
- Lighthill, James, *Waves in Fluids* (Cambridge University Press, Cambridge, 1978).
- McKee, M., Radar satellites capture tsunami wave height, NewScientist.com, January 2005.
- Rivera, P.C., Modeling the Asian tsunami evolution and propagation with a new generation mechanism and a nonlinear dispersive wave model. *Science of Tsunami Hazards*, 25(1):18–33, 2006.
- Shen, Y., Yang, T., Dias, F., Grilli, S., Coupling between the tsunami and seismic energy of the 26 December 2004 Indian Ocean tsunami, submitted.
- Turcotte, D., Schubert, G., *Geodynamics: Applications of Continuum Physics to Geological Problems* (Cambridge University Press, New York, 2005).
-

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

The effect of density stratification and a cape in a baroclinic western boundary current separation experiment

Xue Fan¹, Peter Cornillon, Andrew Eichmann and Vitalii Sheremet

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. The physics of separation of western boundary currents from coastlines of mid latitude ocean basins has long been a mystery for physical oceanographers. In separation regions, complicated flow patterns and gyres are produced. They exchange and mix different water masses, drawing considerable interest from their impact on global climate regulation and nutrient cycles. For the Gulf Stream in particular, different factors such as the coastal shape (Cape Hatteras, North Carolina), inflow and outflow location, wind stresses, continental shelf slope, and shallow underwater plateaus (Grand Banks, Newfoundland) potentially play separate and important roles in separating the Gulf Stream from the coast. In order to study these factors, we set up a circular tank of water rotating on a spinning table. Sloping planes for the upper and lower boundaries of the enclosed tank create the β -effect. Water is pumped through gaps in the tank, producing a western boundary current. An artificial cape is introduced into the system, mimicking the geometry of Cape Hatteras at the Gulf Stream's point of separation. A baroclinic, 2-layer system is used to study the effects of stratification on the point of separation. The results of varying different parameters (flow rate, density difference between layers) are compared with observations of the Gulf Stream and output from a numerical model mimicking the experimental setup, developed by Vitalii Sheremet. Results show that position of the inflow and outflow gaps controls the separation point. Density differences alone do not significantly affect the separation point. High flow rates tend to create more modes of oscillation and a moving separation point. A cape at high density difference and low flow rate deflects the western boundary current flow more so than any other setup.

1. Introduction

Western boundary currents are intensified jets found on western edges of major ocean basins. A large portion of their length follows continental boundaries, transporting heat and nutrients. The separation point between the western boundary current and the coast has been a hot spot in oceanographic research, as it is important to ocean and current predictions.

The Gulf Stream, found in the Atlantic ocean basin, flows along the North American continent from the Gulf of Mexico to Cape Hatteras, North Carolina, where it is then deflected seaward, crossing over the Mid-Atlantic ridge and heading toward Europe. The mechanisms involved in Gulf Stream separation are not well understood.

A two-layer model of the ocean basin is used in our study of the Gulf Stream. This idealization of the ocean's density stratification allows us to experiment physics involving a free, parabolic interface. Inflow and outflow locations provide a way to control the separation point in our artificial western boundary current. Experiments with a cape are used to determine the impact of geological features. The results of various setups are compared to output of a numerical model made to mimic the parameters of our tank. The model essentially solves the stream function given the boundary conditions of the tank until steady state is reached. The creation of a two-layer system and the cape is described in section 2. The results of varying different parameters compared with the model are displayed in section 3, along with important features of certain experiments worth emphasizing. Section 4 summarizes the conclusions drawn from our experiments.

2. Methods

2.1. Tank Setup

A 1m diameter cylindrical tank is used to create the western boundary current needed for our experiment. The tank is centered on a rotating table and has three compartments: an active region, a northern outflow collection region, and a southern input area. An aerial view of the tank is shown in Figure 1a. The outer tank walls rise to 45 cm in height. For all experiments, the rotation rate of the tank was set at 1 rad/s. A north-south gradient in the thickness of the water column is created by sloping bottom

Figure 1. a) Vertical cross section through the tank from north to south. b) plan-view of the tank setup.

¹Now at McGill University, Montreal, Quebec, Canada.

and top lids in the tank's active area. These slopes create the β -effect, which simulates the effect of latitudinal dependence of the Coriolis force. The bottom lid begins at the southern point of the active region, sloping at $+0.05$. The top lid is added to prevent a parabolic surface from forming in a freely rotating non-lid experiment, and allows for the β -effect to act upon the top layer of a baroclinic experiment. The top lid also begins at the southern point, and slopes at -0.05 , so that the height of the water column in the active region ranges from 14 cm at minimum (north end) to 24 cm at maximum (south end). Lines of constant depth run east-west. The sloped bottom is marked with radial lines every 15 degrees arc and concentric lines from the midpoint at 5 cm increments.

Both the inflow and outflow gaps into and out of the active tank region are 8 cm wide and are cut out from the first 10 cm layer under the top lid. The inflow and outflow compartments are lined carefully with sponges, taking care to not disturb the flow in or around the gap regions. The sponges serve to diffuse the flow. A digital pump takes water from the northern outflow area, and puts it into the southern inflow compartment, thus creating a pressure difference, and causing water to be pushed into the active tank region.

Neutrally buoyant dye was used to trace time-averaged currents in the active region of the tank. A series of small holes was drilled into the top lid of the tank along radial lines at 180, 225, and 270 degrees, concentrated toward the outer rim of the tank. Needles were inserted about 5 cm down from the top lid, and were connected to micro-pumps to inject the dye at a slow rate (20 ml/h). A remote-controlled camera was mounted above the active region of the tank. Its output was sent by wireless transmitter to a television monitor as well as recorded within the camera.

2.2. Baroclinic System and cape

To create a stable baroclinic system for experimentation, we create a seawater solution to our desired density. This layer is allowed to equilibrate to a uniform distribution of temperature and density. The temperature of all water used is kept constant at room temperature to avoid any currents produced by a vertical temperature gradient. The densities tested ranged from 1025 kg/m³ (pure seawater from Narragansett Bay) to 1002.5 kg/m³ (diluted seawater). We define $\delta = \Delta\rho/\rho$, where $\Delta\rho$ is the difference in densities between the bottom and top layers, and ρ is the density of the top layer (fresh water having $\rho=1000$ kg/m³). A setup with a bottom layer density of $\rho=1025$ kg/m³ gives $\delta=0.025$. A "high density difference" setup refers to a two-layer system with high δ ($\delta=0.025$ for pure seawater), whereas a "low density difference" refers to a setup with low δ ($\delta=0.0025$ for seawater diluted such that for a given volume, there will be 1/10 the amount of seawater compared to pure seawater). Testing the extremes of the density range allows us to gauge to what extent the density difference has an effect on separation point. The denser solution is attached to an inflow tube that rotates with the table. Fresh water is put in the tank while the table is stationary – the quantity is measured such that when the tank is completely full with the two-layer system, the

denser liquid will rise to the bottom of the inflow and outflow gaps, shown in the vertical section in Figure 1b.

Once the fresh water is filled to the marked height, the tank is spun up until solid body rotation is achieved (usually 10 to 15 minutes). The denser seawater solution is then slowly pumped into the lowest part of the active tank region (the southern point). Neutrally buoyant dye matching the top layer density was injected into the bottom of the tank. This dye would rise through the denser fluid until it reached the interface between layers, allowing us to visually monitor the boundary height. In less dense solutions, dye was used to color the denser solution so that the interface between the bottom and top layer could be monitored more easily. Once the dense water layer is at the correct height, the water pump begins to push the flow.

An artificial cape was made to imitate the presence of Cape Hatteras. It was fit so that its protruding point would line up vertically with the due-west (270 degrees) line of the tank at all heights of the active region, and both sides of the cape were smooth and vertical. Figure 2 shows the shape and dimensions of the cape insert.

2.3. Numerical Model

The numerical model, developed by Vitalii Sheremet, was made to mimic the parameters of the tank setup, including a new addition of a baroclinic, two-layer fluid having a parabolic interface. The model finds a numerical solution to the Shallow Water Equations in the cylindrical coordinates of our rotating tank system. It tracks the progress of the stream function with trapezoidal time stepping until steady state is reached. In the case of the baroclinic system, the bottom layer is assumed to be at rest with respect to the rotating table. Contours of the stream function are plotted in the tank's coordinate system.

3. Results and Discussion

3.1. Gap Placement

The inflow gap was kept at the southern-most point. Outflow gaps varied from the northern edge to the middle of the tank. Geostrophic contours of constant depth run east-west, and waves and current tend to propagate along these lines in a rotating fluid. The outflow gap is used to simulate the underwater plateaus found at Grand Banks, Newfoundland. The global geostrophic contour at which these features are located is hypothesized to affect the Gulf

Figure 2. Cape insert.

Stream separation point. From our experimental results, we see that the point of separation is determined by the placement of the gaps. Figure 3 shows model output for two different gap placements compared to experimental results at given flow rates.

3.2. Density Stratification

By defining the flow rate, Q , to be the amount of water moved through the pump per unit time (in cm^3/s), we can compare the effects of density differences between layers at fixed flow rates. Figure 4 shows results from both high and low density difference runs at two different flow rates. The dye lines have been digitally enhanced to emphasize the path and separation point of each run. Dye experiments at varying densities exhibit little variation in separation point. This same observation can be made at different flow rates.

Figure 3. Black brackets designate gaps. Image **a** shows a barotropic model output for a gap at the north end of the active region. Image **b** shows the results of the experiment in this setup. Image **c** is the barotropic model output for a gap in the middle region of the active tank. Image **d** shows the experimental result of this setup.

Different values of Q allow us to examine the effect that varying flow rate has on a given density stratification. Dye runs for a given density difference are shown in Figure 4e and 4f. Again, paths of dye are manually highlighted. At low flow rates, the separation point is easily visible with dye experiments. When the flow rate is increased, dramatic shifts in the point of separation occur, as if the high flow rate is causing the separation point to drift. Many different modes of oscillation make the ink path difficult to map. This observation can be made for different densities. Therefore, flow rate has rather ambiguous effects on the separation point, and further study is needed by more accurate methods. A comparison between instantaneous velocity fields at a number of times may be more useful in the case of high-oscillation flow rates.

Discrepancies between the model output and the experimental setup are shown in Figure 5. The model predicts a separation point much lower than what is observed in the lab, even at different flow rates. The experimental setup more closely mimics model outputs of a barotropic system, where there is no velocity change with respect to height of the water column. This can be explained by the baroclinic model's assumption that the lower, denser layer rotates with the tank with a zero relative velocity.

Experimental tests with neutrally buoyant dye matching the lower level density show that at sufficient flow rates,

Figure 4. Image results for experiments at a) $Q=10\text{cm}^3/\text{s}$ and $\delta=0.0025$, b) $Q=10\text{cm}^3/\text{s}$ and $\delta=0.025$, c) $Q=20\text{cm}^3/\text{s}$ and $\delta=0.0025$, d) $Q=20\text{cm}^3/\text{s}$ and $\delta=0.025$, e) $Q=40\text{cm}^3/\text{s}$ and $\delta=0.0025$, f) $Q=40\text{cm}^3/\text{s}$ and $\delta=0.025$.

Figure 5. Image **a** shows the numerical model (colored lines) superimposed over data from an experimental run at $Q=10\text{cm}^3/\text{s}$ and $\delta=0.0025$. Image **b** shows the same for $Q=20\text{cm}^3/\text{s}$ and $\delta=0.025$.

there is a considerable amount of flow exhibited by the bottom layer, which was previously assumed stationary with respect to the tank. We hypothesize that the bottom layer flow generated enough energy to flow into the outflow gap. At this gap, water from the lower layer was being sucked up and into the outflow compartment. This generated a low-level flow that was less energetic than its upper-layer counterpart. However, the effect was enough to make the system substantially more barotropic, and thus pushing the separation point more northward to match flow patterns predicted and observed in a barotropic equivalent of the setup.

3.3. Cape

The cape was tested at multiple density differences and flow rates. Figure 6 shows the results of runs with the cape compared to those without the cape. At the low density difference extreme, the cape deflects very little water, and the western boundary current literally curls along the cape, back to the side of the tank, and separates at the same point it would have separated had there not been a cape. The cape's ability to deflect the western boundary current seems greatest at a high density difference, low flow rate situation. This effect can be contributed to the balance between the Rossby waves traveling west from the outflow gap along the geostrophic contour and the western boundary current's originally intended separation path. In a more baroclinic system, the upper layer Rossby waves tend to be weaker, thus pushing the current less westward. This allows the current to be deflected away from the tank side more easily.

3.4. “Virtual” Cape

In experimenting with different methods of dye pumping, we had drilled a radial row of 2mm-wide holes

Figure 6. Image **a** shows results from an experiment at $Q=10\text{cm}^3/\text{s}$ and $\delta=0.0025$ with the cape insert. Image **b** shows results at $Q=10\text{cm}^3/\text{s}$ and $\delta=0.025$ with the cape insert. Image **c** shows results of the same setup as in **a**, without the cape. Image **d** shows results of the same setup as in **b**, without the cape.

left unplugged, this allows for a free surface at those points, creating a potential vorticity barrier. The western boundary current essentially wrapped around this barrier, and reattached to the side of the tank after crossing the due-west line. A different sort of “cape” can be created, taking advantage of this pressure line effect. This sort of fake cape allows for an entirely different boundary condition at the cape face. It creates a free surface on which waves and other effects may form, and changes the no-slip condition of a rigid surface.

Because the shape of the current has a dependence on Rossby wave size, the velocity of the flow affects the path of the current around the virtual cape. When we vary the flow rate, differences in the current's path occur. According to Figure 7, at low flow rates, a larger, rounder “bump” appears around the virtual cape than at high flow rates. At higher flow rates, the current reconnects with the side of the tank earlier and more abruptly. At our highest flow rate, $Q=60\text{cm}^3/\text{s}$, there is little effect on the current by the potential vorticity barrier.

Figure 7. Results showing the deflected current due to the virtual cape at $\delta=0.0025$. The drilled holes forming the potential vorticity barrier are large white dots. Image **a** was run at $Q=30\text{cm}^3/\text{s}$, image **b** was run at $Q=40\text{cm}^3/\text{s}$, and image **c** was run at $Q=60\text{cm}^3/\text{s}$.

4. Conclusions

The Gulf Stream was modeled as a two-layer baroclinic system to examine the impact of different density stratifications on the artificial boundary current. In creating a baroclinic setup, different parameters were adjusted. These included density differences between layers, gap inflow and outflow restriction, flow rate, and presence of a cape. The separation point of the western boundary current from the tank edge was closely examined under each of the different tank setup circumstances.

As seen by the result shown in Figure 3, the separation point of an artificial western boundary current in a barotropic (one-layer) system is easily controlled by moving the location of the outflow gap in the active area of the tank. Disturbances propagating along geostrophic contours tend to affect the western boundary current's movement. This effect simulates the Gulf Stream flow around Grand Banks, Newfoundland.

The introduction of the two-layer system is a better approximation of the density stratification found in the ocean. It allows for examination of the effects of extreme density differences in the layer and of a parabolic free surface at the interface. At both extremes of very low density difference between layers and very high density differences, results (shown in Figure 4) suggest that the densities of a two-layer system do not affect the separation point in a meaningful way. At high flow rates, this effect is even less obvious, because the flow develops oscillations in the separation point. The baroclinic setup we have created here is not perfectly baroclinic, however – the bottom layer shows movement, which may explain the discrepancies between the model output and the experimental outcome. A more barotropic system tends to push the separation point further north than a baroclinic system.

A cape insertion is placed due west in the active region to mimic the presence of Cape Hatteras, North Carolina. As seen in Figure 6, the cape has little or no effect on the separation point at low density difference setups. However, at a high density difference, there seems to be a clear deflection of the western boundary current from its originally intended path. This suggests that under certain circumstances, interactions between the current and westward Rossby waves are balanced such that the cape does play a role in diverting the western boundary current from the continent.

Acknowledgments. We thank the Department of Defense ASSURE program and the National Science Foundation's REU program for funding. We also thank Joe Kuehl and Grant Stuart for their tireless assistance in the lab. We also thank Rob Pockalny, Cristin Ashmankas, and Kim Carey for making the SURFO program possible.

References

- Cushman-Roisin, B. 1994. Introduction to Geophysical Fluid Dynamics. Prentice Hall, N.J.
- Diehl, B. 2005. The Effect of a Cape on Separation of a Western Boundary Current. SURFO 2005, University of Rhode Island, Narragansett, RI.
- Munday, D. and Marshall, D. 2005. On the Separation of a Barotropic Western Boundary Current from a Cape. J. Phys. Oceanogr., In Press.
- Sheremet, V. and Kuehl, J. 2005. Gap Leaping Western Boundary Current in a Circular Tank. J. Phys. Oceanogr., Submitted.
- P. Cornillon and V. Sheremet, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (pcornillon@gso.uri.edu, vsheremet@gso.uri.edu)
- ¹X. Fan, McGill University, Montreal, QC.
(xue.fan@mcgill.ca)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program.

Sea Surface Height Variability in the Kuroshio Extension

Amy L. Fearing,¹ Kathleen A. Donohue, and D. Randolph Watts

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. As part of the Kuroshio Extension System Study, an array of current and pressure recording inverted echo sounders (CPIES) was moored in a 600 km X 600 km region centered near 35N 146E off the eastern coast of Japan. This array measured bottom pressure and currents as well as round trip acoustic echo time from the seafloor to the surface from May 2004 through June 2006. With this array, we can calculate sea surface height (SSH), and thereby track currents, its meanders, the eddies it forms, and how they interact. The acoustic echo time is used to calculate the steric, or heat-content, variations in SSH. Bottom pressure is used to calculate the mass-loading variations in SSH. Satellite altimeters also monitor SSH and here we compare these measurements with CPIES derived SSH. There is a mapped product with a resolution of 3.5 days which combines all satellite data and interpolates over space and time. We also used Jason-1 along track data, with a temporal resolution defined by the satellite repeat of 10 days. Standard deviations and correlations were computed for both parts of SSH, as well as the total SSH measured by the CPIES and the altimeter. It was found that the correlation between the altimeter SSH and CPIES SSH is best where the signal amplitude and variance is highest. The correlations improve when SSH is low-pass filtered with a 40 day cutoff. The Jason-1 along track data provides better correlations to CPIES sites directly on its tracks, with an average value of $r = 0.914$, than the mapped altimeter data which had an average value of $r = 0.886$.

1. Introduction

Off the east coast of Japan, the Kuroshio western boundary current forms a vigorously meandering free jet known as the Kuroshio Extension. The Kuroshio Extension separates the cold northern waters from the warm, southern, subtropical waters of the recirculation gyre. The difference in sea surface height across the width of the current can be greater than a meter. This region is very active.

As part of the Kuroshio Extension System Study (KESS), the first cruise in May 2004 deployed an array of 37 current and pressure recording inverted echo sounders (CPIES) and 9 pressure recording inverted echo sounders (PIES). They array was located in a 600 km X 600 km region centered near 35N 146E as seen in Figure 1. This array measured bottom pressure and currents as well as round trip acoustic echo time from the seafloor to the surface from May 2004 through June 2006. During June 2005, a mid-experiment cruise used pulse delay telemetry to retrieve the first year's data from the instruments. The recovery cruise in June 2006 retrieved the CPIES. Here we compare SSH derived from the CPIES array to two satellite SSH products.

2. Data

2.1. CPIES data

This study utilizes the first year of data from 35 CPIES and 9 PIES within the KESS array (Figure 1). The time series are about 400 days long. All of the instruments were bottom mounted at depths between 5000m and 6000m. The daily average round trip acoustic echo time (τ) and daily average bottom pressure (P) were recorded and telemetered during the second cruise.

2.2. Satellite altimeter data

Satellite altimeter products were produced by Ssalto/Duacs and distributed by Aviso, with support from Cnes. The gridded absolute dynamic topography maps with resolution of 3.5 days were correlated with the CPIES measured SSH. The gridded products during this time period combine data from ERS, Jason-1, and Topex/Poseidon. The gridded data is every third of a degree. The Jason-1 along-track data was also used to

Figure 1. KESS Observing Array. Diamonds indicate locations of CPIES. Gridded black lines indicate Jason-1 ground tracks. Contour lines are mean surface dynamic height in dyn-cm (Teague et al., 1990). The 2000 and 4000-m isobaths are shaded dark and light gray, respectively. The stars are moored profilers from Woods Hole Oceanographic Institution. The triangle is the Kuroshio Extension Observatory from the National Oceanic and Atmospheric Administration's Pacific Marine Environmental Laboratory.

¹Rensselaer Polytechnic Institute, Troy, NY

compare to sites located on those lines. These measurements were also absolute dynamic topography, with temporal resolution defined by the satellite repeat every 10 days. The Jason-1 satellite tracks are every 0.03 degrees longitude and 0.05 degrees latitude.

3. Methods

3.1. Computing sea surface height

3.1.1. Steric effects. Using measured τ values, GEM lookup tables provide temperature and salinity as a function of pressure that are used to calculate the geopotential height anomaly, Φ (Meinen and Watts, 2000). The steric part of SSH is then calculated as Φ/g , where g is gravity.

3.1.2. Mass-loading effects and the ‘common mode’. The mass-loading contribution to SSH is $P/(\rho g)$, where P is the leveled deep pressure at a reference pressure of 5000 dbars and ρ is the density. There was a ‘common mode’ with ~ 0.2 dbar range on 2 to 30 day timescales in the deep pressure values caused by atmospheric forcing. The

common mode was removed from the mass-loading part of SSH.

3.2. Comparing CPIES SSH to altimeter SSH

The values of steric and mass-loading sea surface heights are then interpolated to the same times as the AVISO SSH maps and along-track data. Total sea surface height (η) is then computed, and is given by:

$$\eta = \Phi/g + P/(\rho g) \quad (1)$$

Standard deviations are computed for each part of SSH, the CPIES total SSH, and the altimeter SSH measurements. Correlation coefficients between all of these are computed as well.

4. Results

The major part of SSH is steric. The mass-loading effects can have important contributions, but always have a much smaller amplitude than the steric effects.

Figures 2A and 2B show the standard deviations of the

Figure 2. A. Standard deviation of altimeter SSH in cm. B. Standard deviation of CPIES total SSH in cm. C. Correlation coefficient of altimeter and CPIES SSH. D. Correlation coefficient of 40 day low-pass filtered altimeter and CPIES SSH.

satellite SSH signals and CPIES SSH signals, respectively. The highest values are in the middle of the array, which is where the Kuroshio Extension is meandering for most of the year. The lower variances, and consequently lower standard deviations, are in the northern and southern sections of the array. The two maps agree well with the exception of the southwest corner. In this region, the altimeter has higher variance than the CPIES SSH. This stronger signal can be seen in the time series of site F1, shown in Figure 3A.

The correlation coefficient (r) between the altimeter measurements of SSH and the CPIES measurements of SSH is shown in Figure 2C. The higher correlations are in areas which also have a higher variance. In the middle of the array, there is one site (E5), which has a lower r value, but had a high standard deviation. When examining the time series (Figure 3B), during the first 100 days of the deployment there is a higher frequency signal that the CPIES is detecting that the altimeter is missing. The next step was to low-pass filter the SSH data with a second order Butterworth filter and try to separate out the higher frequency signal. A 40-day cutoff for the Butterworth filter was used. Correlation coefficients were again computed between the altimeter and CPIES data. The results of this filtering are shown in Figure 2D. The correlations improved at E5, as well as in the northern section of the

Figure 3. A. Time series of site F1, which is the site on the left which is circled on the schematic of the KESS array. B. Time series of site E5, which is the site on the right which is circled on the schematic of the KESS array.

array. However, it still didn't improve the southern tip of the array, where there were the lowest standard deviations.

Most of the CPIES in the array lay on Jason-1 ground tracks (Figure 1). These sites were also correlated directly to the Jason-1 along-track data. Figure 4 shows the correlated values with the along-track product and the gridded product. The average correlation for sites directly on these lines compared with the along-track product is 0.914. The average for the same sites array when compared with the gridded data product is 0.886. Points off of Jason-1 tracks have an average correlation of only 0.869. However, these correlation values are all much higher than those found in the Gulf of Mexico, which had an average correlation of 0.77 for the 5 sites which were coincident with the Jason-1 ground tracks (Donohue et al., 2006).

5. Conclusions

The altimeter measurements of SSH agree well with the CPIES measurements. This correlation is best when the variance in SSH is high. Low-pass filtering both the altimeter and CPIES data improves the agreement when the variance is high. Using sites along the Jason-1 ground tracks and comparing this data directly to the Jason-1 data has better correlations than comparing these sites with the

Figure 4. Correlations for sites that are coincident with Jason-1 ground tracks: A. with along-track altimetry data. B. with gridded altimetry data.

gridded altimeter product. In the future, studies may evaluate gridded products after Topex/Poseidon ceased to record data, and evaluate the seasonal influences on SSH signal amplitude. Knowing that the altimeter is measuring SSH well is important because this data extends back 20 years and covers all of the oceans, and is assimilated into current models and forecasts.

Acknowledgments. We thank the National Science Foundation for funding KESS, the National Science Foundation's Research Experience for Undergraduates program, the Department of Defense ASSURE program, the Ocean Data Facility at Scripps Institution of Oceanography, the captains and crews of the R/V Thompson, R/V Revelle, and R/V Melville, Karen Tracey, JaeHun Park, Andrew Greene, and Stuart Bishop.

References

- Aviso Altimetry, <http://www.aviso.oceanobs.com>
- Donohue, K., P. Hamilton, K. Leaman, R. Leben, M. Prater, D.R. Watts, E. Waddell, 2006: Technical Report, Exploratory Study of Deepwater Currents in the Gulf of Mexico. U.S. Department of the Interior, Minerals Management Service, Gulf of Mexico OCS Region, New Orleans, LA. OCS Study MMS 2006, 2-59 – 2-60.
- Meinen, C.S., and D.R. Watts, 2000: Vertical structure and transport on a transect across the North Atlantic Current near 42N: Time series and mean. *J. Geophys. Res.*, 105, 21869-21891.
- Teague W.J., M.J. Carron, and P.J. Hogan, 1990: A comparison between the Generalized Digital Environmental Model and Levitus climatologies. *J. Geophys. Res.*, 95, 7167-7183.
-
- Amy L. Fearing, Kathleen A. Donohue, and D. Randolph Watts, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (fearia@rpi.edu, kdonohue@gso.uri.edu, rwatts@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

PCR Optimization and Comparative Sequence Analysis of Metabolic Genes between Isolates of the Diatom *Ditylum brightwellii*

Graham E. Lau,¹ and Tatiana A. Ryneerson

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Diatoms are unicellular algae that contribute significantly to the photosynthesis conducted in the global ocean. It has been seen that variability occurs among diatom blooms, and this variability may partially be in response to genetic variations within an individual diatom species. This study sought to determine the genetic variability in five specific gene sequences in four isolates of the diatom *Ditylum brightwellii*. Four of the gene sequences chosen for this study are involved in metabolic pathways within the diatom cell; they include the gene for nitrate reductase (NR), the gene which codes for the D1 subunit of PSII (psbA), the gene coding for cytochrome oxidase 1 (CO1), and the genes coding for silicon transporters (SITs). The novel isolation and characterization of the four metabolic genes within this species, using the primers and methods described herein, required multiple rounds of PCR optimization to produce single sequence fragments of the expected length. The internal transcribed spacer 1 (ITS1) region of eukaryotic rDNA was also characterized in this study. PCR optimization and sequencing was successful for psbA and ITS1 gene sequences in three *D. brightwellii* isolates from Narragansett Bay, RI. PCR reactions for NR, CO1, and SIT genes have not yet been fully optimized. Here we report our method of PCR optimization and sequence analysis for the selected genes in isolates of *D. brightwellii*.

1. Introduction

Diatoms are unicellular phytoplankton that generate up to 40% of the primary production in the sea each year (Armbrust et al 2004). Diatoms are the primary silicifying organisms on this planet (Thamatrakoln and Hildebrand 2005), utilizing silica in their cell wall formation (Thamatrakoln et al 2005). Like most planktonic species, diatoms undergo rapid increases in cell abundance and population size when conditions are favorable (Ryneerson et al 2006). These increases are known as blooms. It has been difficult to explain the spatial and temporal variability that occurs among blooms based solely on environmental conditions. It appears that genetic variation within individual species may also contribute to the variation in bloom dynamics. For example, Ryneerson et al (2006) have shown that genetically different populations of the diatom *Ditylum brightwellii* form blooms under varying environmental conditions. One population in Puget Sound, WA bloomed early in the spring (February through April), referred to as population A, whereas another population bloomed later in the spring (May and June), referred to as population B. Ryneerson et al (2006) show that varying physical and chemical factors apply to the two populations. Population A bloomed during heightened levels of orthosilicic acid (Si(OH)_4) in the water and during lower levels of solar exposure than population B (Ryneerson et al 2006).

Considering that different populations of *D. brightwellii* bloom under varying physical and chemical conditions, metabolic variation may be a primary source of variability in bloom timing between populations. Differences at the genetic level of metabolic pathways may reveal why populations, some of which are separated by little or no geographical and chemical barriers, have such variable bloom dynamics. Genes involved in nitrogen metabolism, photosynthesis, electron transport, and silicon transport were determined to be good indicators, when taken

together, of how metabolic pathways may differ between populations. This study was conducted to determine if variations may exist between four selected genes involved in metabolism between representative isolates of the diatom *Ditylum brightwellii*.

Primary production in the global ocean is largely regulated by the rate and magnitude of nitrogen uptake by planktonic organisms (Allen et al 2005). Nitrate, the environmental source of nitrogen for diatom cells is reduced to nitrite by the assimilatory nitrate reductase enzyme. This enzyme is coded by the NR gene, which is a single-copy gene located in the nuclear genome (Allen et al 2005, Song and Ward 2004).

As photosynthetic organisms, diatoms require the ability to harness solar radiation as a form of energy. Photosynthesis occurs through two protein complexes, known as Photosystems I and II. Photosystem II is involved in the light-driven reduction of plastoquinone and the transport of electrons across the thylakoid membrane (Alfonso et al 2000, Tyystjärvi et al 2002). The gene psbA codes for the D1 subunit of the Photosystem II protein complex. The D1 subunit, along with the D2 subunit, forms the reaction center of the complex (Alfonso et al 2000), to which redox active components of photosynthesis bind (Tyystjärvi et al 2002). The psbA gene is located on the chloroplast genome (Morton 1994, Alfonso et al 2000, Tyystjärvi et al 2002, Stabile et al 1995). It has been reported by Stabile et al (Stabile et al 1995) that diatoms of the genera *Skeletonema*, *Cyclotella*, and *Coscinodiscus* have two copies of the psbA gene in their chloroplast genomes, possibly the result of gene inversion; however diatoms of the genus *Odontella* have only one copy of the gene. The chloroplast genome of *Ditylum brightwellii* has not yet been sequenced, so it is unknown if the psbA gene exists as a single-copy or a multi-copy gene in these diatoms.

The electron transport chain in the mitochondria of eukaryotic cells is the key to oxidative phosphorylation, driving the synthesis of adenosine triphosphate (ATP, the primary energy molecule of cells) through the production

¹Now at York College of Pennsylvania, York, Pennsylvania

of the proton motive force (Siedow and Umbach 1995). Cytochrome oxidase is the terminal protein complex in the electron transport chain. This protein complex oxidizes reduced cytochrome c and functions as a proton pump, aiding in the creation of the proton motive force. The CO1 gene codes for the cytochrome oxidase 1 enzyme and is located in the mitochondrial plasmid (Siedow and Umbach 1995, Hebert et al 2003). Sequence variation in CO1 has been used to identify closely related species and thus has been considered a successful barcoding gene (Hebert et al 2003, Morgan and Blair 1998, Smith et al 2005).

Diatoms construct their cell walls from silica, which is biologically precipitated from orthosilicic acid ($\text{Si}(\text{OH})_4$, the primary form of silicon in the global ocean (Thamatrakoln and Hildebrand 2005)). Silicic acid transport and silica deposition are tightly bound to the cell cycle and may serve as important growth regulators (Thamatrakoln et al 2005, Martin-Jézéquel et al 2000). Silicon transporters (known as SITs) are enzymes which act as mediators for the transport of silicic acid across the cell wall and membrane of diatoms. It has been shown that different species of diatoms may possess a different number and different types of silicon transporters (Thamatrakoln et al 2005, Thamatrakoln and Hildebrand 2005, Martin-Jézéquel et al 2000). Silicon transporters are multi-copy, nuclear genes (Thamatrakoln et al 2005).

Along with comparative sequence analysis of the NR, psbA, CO1, and SIT genes, it was determined in this research that internal transcribed spacer 1 (ITS1) sequences should also be utilized for comparative analysis between representative isolates of *Ditylum brightwellii*. ITS1 is a region of the eukaryotic, nuclear rDNA (Coleman 2003, Armbruster and Korte 2006). This non-coding region has become one of the primary regions of interest in modern phylogenetic analyses (Coleman 2003, Armbruster and Korte 2006).

ITS1 sequence data has been reported for *Ditylum brightwellii* isolates from Puget Sound in Washington, USA (Rynearson et al 2006). CO1 sequence data has been used for species-level phylogenetic analyses between *D. brightwellii* and seven other model diatom species (Ehara et al 1999), but has never before been used for subspecies comparisons of *D. brightwellii* isolates. The PCR primers used for CO1 isolation and amplification in this study had not been used before to amplify CO1. The NR, psbA, and SIT genes have not been isolated, amplified, or sequenced before in this species. Due to the novelty of the characterization of these genes in *D. brightwellii*, this study consisted of PCR optimization and sequence analysis to determine the specificity of newly designed primers and to compare sequence variation among isolates.

2. Methods

2.1 Collection and Culture of Isolates:

Three isolates of *D. brightwellii* were collected from Narragansett Bay, Rhode Island (41°29'32"N, 71°25'08"W), on December 6th, 2005. One isolate was obtained from the Provasoli-Guillard Center for the Culture of Marine Phytoplankton (CCMP). This isolate, CCMP 2227, was collected from Avery Point, Connecticut

(41°31'96"N, 72°06'70"W) on November 16th, 2001. Representative isolates were cultured in f/2 media at 14°C and with a 16:8 light:dark cycle.

2.2 DNA Extraction:

Cultures of exponentially growing isolates were filtered in volumes of 7mL and 15mL, based upon visual inspection of culture growth. Total genomic DNA was extracted using the DNeasy Plant Mini Kit from Qiagen (Valencia, CA) and following the manufacturer's protocol. Extracted genomic DNA was then stored at -20°C.

2.3 PCR primers and Conditions:

Primers and initial thermal cycling conditions for PCR were determined for each gene of interest. NR was amplified with a nested PCR, with the primers NRpt907F and NRpt2325R (Allen et al 2004) used in the first round, and the primers NRpt1000F and NRpt1389R (Allen et al 2004) used in the second, nested round. Primers for the PCR of the psbA gene, entitled psbA F-1 and psbA R-1, were designed based upon alignments of the psbA gene in other diatoms and closely related organisms. The initial PCR annealing temperature was 56°C, 4°C lower than the calculated melting temperature of the primer pair. CO1 PCR primers, titled CO1 C-F and CO1 C-R, were also designed based upon alignments with closely related organisms. The initial annealing temperature for the CO1 PCR was 45°C, 4°C lower than the calculated melting temperature of the primer pair. SIT genes were initially amplified using degenerate primers and initial PCR conditions in Thamatrakoln et al (2006). The primers SITdegF1, SITdegR1, and SITdegR2 were used in this study. The ITS1 primers 1645F and Dit5.8SR and thermal cycling conditions designed by Rynearson et al (2006) were used for ITS1 PCR.

2.4 PCR Optimization and Sequencing Preparation:

PCR's were optimized using the 12-buffer SureBand PCR Optimization Kit with Bio-X-Act Short enzyme from Bionex (Randolph, MA) and corrections in thermal cycling conditions. PCR products were analyzed for expected-length fragments through gel electrophoresis with 1% agarose gels. HyperLadder II (50bp to 5kbp range)(Bionex) and Hi-Lo Ladder (50bp to 10kbp range)(Bionex, Inc., Oakland, CA) were used as molecular weight standards. Gels were stained with ethidium bromide or SYBR Green and were visualized using a UV imaging system. If optimized, 50µL PCR reactions were conducted on all isolates for each gene or sequence of interest. 50µL reactions consisted of 7.50µL of extracted DNA, 1× PCR buffer mix (containing dNTPs, variable concentrations of MgCl_2 , additives, PCR enhancers, and reaction buffers)(Bionex), 5 units of Bio-X-Act Short enzymes (Bionex), and 0.32nmol of each of the relative forward and reverse primers.

PCR products from 50µL reactions were cleaned using the MiniElute PCR Purification Kit from Qiagen (Valencia, CA) and measured using the Qubit Quantitation Platform with the Quant-it dsDNA Broad Range assay (Invitrogen; Carlsbad, CA).

2.5 Sequencing and Analysis:

Samples that had been successfully optimized were sent to the Genomics and Sequencing Center (GSC) at the University of Rhode Island and/or to the W.M. Keck facility at Yale University. Sequencing was conducted using the Beckman-Coulter CEQ 8000 platform and software at the GSC. Sequencing at the W.M. Keck facility was carried out on Applied Biosystems 3730 capillary instruments. Samples were sequenced in both forward and reverse directions. Sequence data analyses were conducted using the CLC Gene Workbench software, including phylogenetic analysis using neighbor joining methods with 100 bootstraps.

3. Results

3.1 PCR Optimization:

The first round of the nested NR PCR began with the full range of 12 buffers, following the thermal cycling conditions from Allen et al (2005). Initial results showed multiple-banding patterns with some of the buffers amplifying fragments at the expected length of ~1418bp (Figure 1). After three rounds of PCR optimization, Buffer I was determined to be the optimal PCR buffer and conditions were reached which produced favorable results, though multiple bands still appeared (Table 1). Buffer I was then used in the second round of the nested NR PCR, with the product from the first round used as the template for the second round. NR PCR optimization was successful for all four isolates; one fragment band was produced of the expected length at ~389bp (Table 1).

The initial psbA PCR showed multiple banding patterns (Figure 2A). Single bands of the expected length of

Figure 1. Photograph of NR PCR gel taken after 2nd round of PCR optimization using NRpt907F and NRpt2325R primers. Lanes 1 and 8 contain 6 μ L of Hi-Lo Ladder (Bionexus, Inc., Oakland, CA). Lanes 2-7 contain PCR products from reactions using Buffers A, C, F, G, I, and L (Bioline), respectively, with reaction annealing temperature of 56°C. Lanes 9-14 contain PCR products from reactions using Buffers A, C, F, G, I, and L (Bioline), respectively, with reaction annealing temperature of 59.9°C. Lanes 2-7 and 9-14 were loaded with 3.5 μ L of sample and 1 μ L of 5 $\times$ loading buffer. Samples run on a 1% agarose gel at 100 volts for 60 minutes.

~700bp were observed after two rounds of PCR (Figure 2B), by using Buffer J and 56°C as the annealing temperature (Table 1). Optimization, showing single banding at the expected fragment length (~700), was successful for the three isolates from Narragansett Bay, but not for the isolate from Avery Point, which showed a second band around ~1400bp (Figure 2B).

CO1 PCR optimization was not successful using the 12-buffer optimization system. At the writing of this paper, single banding patterns of the expected fragment length had only been observed in one of the isolates from Narragansett Bay, but not in the other two or in the isolate from Avery Point.

SIT PCR optimization was also not achieved. SIT PCR using primers SITdegF1 and SITdegR1 revealed multiple

Figure 2. Photographs of psbA PCR gels taken after initial PCR (A) and after optimization for four isolates of *Ditylum brightwellii* (B). Samples were loaded at 5 μ L volumes with 1 μ L of 5 $\times$ loading buffer. Both are 1% agarose gels run at 100 volts for ~60 minutes. (A) Well 1 contains a blank, well 2 contains 4 μ L of HyperLadder II (Bioline, Randolph, MA), wells 3 through 14 contain PCR products from reactions using buffers A through L, respectively, with DNA from Avery Point, CT isolate as the template (B) Wells 1 through 3 each contain one of three different reaction products from psbA PCR of DNA from isolates from Narragansett Bay, RI, well 4 contains PCR product from isolate sampled from Avery Point, well 5 contains a blank, and well 6 contains 6 μ L of Hi-Lo Ladder (Bionexus, Inc., Oakland, CA).

Table 1. PCR optimization conditions for ITS1, psbA, CO1, nested NR, and SIT sequences.

PCR Reaction	Forward Primer	Reverse Primer	Expected Length (bp)	PCR Buffer ^a	Thermal Cycling Conditions ^b
ITS1	1645F	DIT5.8SR	700	L	36 × (95°C, 30 s; 65°C, 30 s; 72°C, 1 min.)
psbA	psbA F-1	psbA R-1	700	J	37 × (94°C, 30 s; 56°C, 30 s; 72°C, 3 min.)
CO1*	CO1 C-F	CO1 C-R	580	L	41 × (95°C, 30 s; 57.5°C, 30 s; 72°C, 45 s)
NR Nested (1 st Round)	NRPt907F	NRPt2325R	1418	I	37 × (94°C, 30 s; 56°C, 30 s; 72°C, 3 min.)
NR Nested (2 nd Round)	NRPt1000F	NRPt1389R	389	I	35 × (94°C, 30 s; 53°C, 30 s; 72°C, 3 min.)
SIT1*	SIT deg F1	SIT deg R1	880	A	11 × (94°C, 30 s; 71°C ^z , 2 min.; 72°C, 2 min) 40 × (94°C, 30 s; 52-54°C, 2 min.; 72°C, 2 min.)
SIT2	SIT deg F1	SIT deg R2	1020	A	11 × (94°C, 30 s; 71°C ^z , 2 min.; 72°C, 2 min) 40 × (94°C, 30 s; 52-54°C, 2 min.; 72°C, 2 min.)

^a One of twelve buffers (A through L) from SureBand PCR Optimization Kit (Bioline, Randolph, Ma)

^b ITS1 and CO1 PCR began with 95°C, 2 min. hot starts, psbA and NR PCR began with 94°C, 3 min. hot starts, and SIT PCR began with a 94°C, 2 min. hot start. All PCR reactions included a final extension step at 72°C for 10 minutes.

^z Annealing temperature for SIT PCR “touchdown” decreased by 2°C after every cycle.

* PCR optimization was not achieved for CO1 and SIT targets. Buffer and conditions listed may not be optimal.

^z Annealing temperature for SIT PCR “touchdown” decreased by 2°C after every cycle.

* PCR optimization was not achieved for CO1 and SIT targets. Buffer and conditions listed may not be optimal.

banding after three rounds of PCR optimization and had not been optimized further. After seven rounds of PCR optimization for the SIT PCR using primers SITdegF1 and SITdegR2, the PCR reactions had begun to produce double or single banding patterns. Buffer A was determined to be the optimal buffer, however annealing temperature had not yet been completely optimized (Table 1). When two bands were produced, one at the expected length of ~1020bp and one at ~500bp were produced. When single bands were produced, a fragment of the expected length of ~1020bp had been seen, suggesting optimization. However, at the time of the writing of this paper, SIT PCR had not been conducted in 50µL reactions with the four isolates of *D. brightwellii* from the study.

ITS1 PCR optimization was successful for the three Narragansett Bay isolates, but not for the Avery Point isolate. After two rounds of PCR optimization, it was determined that Buffer L and an annealing temperature of 65°C were the most suitable for amplification of the ITS1 sequence in these isolates (Table 1). Single band fragments of the expected length of ~700bp were seen for all four isolates, however the Avery Point isolate PCR reaction sample had become contaminated during the procedure.

3.2 Sequencing analysis:

Initial sequence results for the NR PCR product showed overlapping trace files and thus were too poor for further analyses. The psbA gene is 1056bp in length (Morton and Levin 1997). The psbA sequencing yielded 532bp of the 700bp amplicon. The psbA fragments from the three isolates from Narragansett Bay had identical sequence. The full-length ITS1 region, 638bp, was sequenced for all three isolates from Narragansett Bay. The DNA sequence among the three isolates was identical. ITS1 sequence data from the three Narragansett Bay isolates were aligned with ITS1 sequence data from isolates of *Ditylum brightwellii* from Puget Sound, WA (Ryneearson et al 2006) (Figure 3).

Alignment revealed homology of the Narragansett Bay isolates with the isolates of Population A from Puget Sound.

4. Discussion

532bp of the 1056bp psbA gene were sequenced for the three Narragansett Bay isolates. 100% sequence homology for the psbA gene between the three Narragansett Bay isolates may show that these isolates are all from the same clonal lineage. It is likely that isolates that share complete sequence homology, with even the third codon for each

Figure 3. Phylogenetic tree developed from CLC Gene Workbench alignment of three isolates of *Ditylum brightwellii* from Narragansett Bay, RI and twelve isolates sampled from Puget Sound, WA. Numbers at nodes correspond to replicate bootstraps returning with reported divergence. Scale bar indicates the percent genetic divergence.

residue being completely identical, must be very closely related. Though the homology between the three isolates for this gene may show relatedness of the isolates to each other, it also relates to the conservation of this gene, which is essential for photosynthesis and energy production.

The ~1400bp band which showed up in the psbA PCR of the Avery Point isolate (Figure 2B) is interesting to note. The expected length of the psbA PCR fragment is ~700 for the primer set used. The second band in the Avery Point sample is around twice the length of the expected fragment. It may be possible that a sequence inversion or a second copy of the psbA gene exists in the isolate from Avery Point; the same as has been seen in diatoms of the genera *Skeletonema*, *Cyclotella*, and *Coscinodiscus* (Stabile et al 1995). Further analysis of the larger band must be conducted for continued speculation.

All 532bp of the ITS1 region were successfully amplified through PCR and sequenced for the three Narragansett Bay isolates. The ITS1 sequence is believed to have been successfully amplified for the Avery Point isolate, however, due to sample contamination, this sequence must be amplified again before sequencing and analysis can be completed. The genetic homology in ITS1 sequence between the three isolates from Narragansett Bay further shows their close relatedness to one another. The three isolates had been collected from the same sampling location, at the same time, and on the same day. With this in consideration, it is fairly certain that the three isolates are all representative of a single population in Narragansett Bay.

Isolates of *Ditylum brightwellii* from Puget Sound, WA had been aligned by Ryneerson et al (2006) to reveal two populations, A and B (Figure 3). When ITS1 sequences from the three Narragansett Bay isolates were aligned with the isolates from Puget Sound, sequence comparisons revealed that the three isolates from the Narragansett Bay are more related to the isolates in Population A than to those in Population B.

Global dispersal theories may conclude that isolates from Population A, due to geographical or chemical barriers, are more dispersed into the global ocean than Population B, and thus there is such strong sequence homology with isolates from the east coast of North America. Perhaps the sample size was too small; three isolates taken from the same location and at the same time may not be representative of the total *D. brightwellii* in Narragansett Bay. Other theories may include the possibility that representative isolates from Population A were transferred from east coast to west coast or vice versa due to human interference (i.e. shipping or aquaculture).

The nested PCR for the NR gene sequence appears to have been successfully optimized for all four isolates. The poor sequencing results for the nested NR PCR products may be due to multiple fragments in the sequencing sample, showing that optimization of PCR had not occurred or that some level of sample contamination had occurred. Further amplification and sequencing of this gene from the four isolates is required to further the study.

Unfortunately, the sequences for the CO1 and SIT genes were not successfully sequenced for this study. CO1 PCR had been optimized in one isolate from Narragansett Bay out of the four isolates. This may show that some variation

exists between even the isolates for the CO1 sequence. With the implications of CO1 as a barcoding sequence, it is hopeful that variations in the CO1 sequence will illuminate even interspecies differences.

SIT PCR optimization has appeared within reach. Further annealing temperature adjustments using the primers SITdegF1 and SITdegR2 and using the methods described here may allow for successful amplification and sequencing of SIT genes in *Ditylum brightwellii*. Sequencing data and work from Thamtrakoln et al (2006) suggests that internal gene duplication or dimerization of two identical monomers may have occurred in the evolution of silicon transporters. The double band patterns seen in many of the SIT PCRs of this study (using the SITdegF1 and SITdegR2 primers) show one band at the expected length of ~1020bp and one band at around 500bp. It is possible that the smaller fragment is the result of amplification of the single monomer-coding sequence rather than the complete SIT sequence.

Conclusions as to the nature of genetic variations in the metabolic genes chosen for this study between representative isolates of *Ditylum brightwellii* cannot be inferred at this time due to the lack of sequence information. Further optimization and purification of PCR products will be required for continued analysis.

To gain a better understanding of the genetic variations in metabolism between populations of *Ditylum brightwellii*, multiple representative isolates from multiple sampling locations across the globe should be studied with methods similar to those used in this study. The incorporation of further metabolic gene targets would allow for increased sequence comparison data. Other genes involved in metabolic pathways, such as phosphate metabolism, or other genes involved in the pathways chosen for this study, such as psbD, which codes for the D2 subunit of Photosystem II, may be of interest in further studies. With the continued expansion of genomic technology, future research will include whole genome approaches to characterizing variation at the species and subspecies level. This variation can then be examined in the context of bloom dynamics. Considering diatom contributions to global primary production and the biological cycling of silica, knowing the full extent of variation within a species provides better understanding of the ecological potential of these organisms.

Acknowledgments. We thank Robert A. Pockalny, Ph.D. for his Directorship of the SURFO program at the Graduate School of Oceanography; Kim Carey, Rhonda Kenny, and Cristin Ashmankis for their support of the SURFO program at the Graduate School of Oceanography; Helen Day and Melissa Mercier for laboratory assistance; and Malcolm McFarland for sample collection. This work was supported by joint funding from the Department of Defense ASSURE program and from the National Science Foundation's REU programs as well as by the National Science Foundations ADVANCE program, URI.

References

- Alfonso, M., Perewoska, I., and Kirilovsky, D., Redox control of psbA gene expression in the cyanobacterium *Synechocystis* PCC 6803: involvement of the cytochrome b_6/f complex, *Plant Physiol.*, 122, 505-516, 2000.

- Allen, A.E., Ward, B.B., and Song, B., Characterization of diatom (Bacillariophyceae) nitrate reductase genes and their detection in marine phytoplankton communities, *J. Phycol.*, 41, 95-104, 2005.
- Armbruster, G.F.J., and Korte, A., Genomic nucleotide variation in the ITS1 rDNA spacer of land snails, *J. of Molluscan Studies*, 72, 211-219, 2006.
- Armbrust, V. E., et al, The genome of the diatom *Thalassiosira pseudonana*: ecology, evolution, and metabolism, *Science*, 306, 79-86, 2004.
- Coleman, A.W., ITS2 is a double-edged tool for eukaryote evolutionary comparisons, *Trends in Genetics*, 19:7, 370-375, 2003.
- Ehara, M., et al, Phylogenetic analysis of diatom *cox1* genes and implications of a fluctuating GC content on mitochondrial genetic code evolution, *Curr. Genet.*, 37, 29-33, 2000.
- Hebert, P.D.N., Ratnasingham, S., and deWaard, J.R., Barcoding animal life: cytochrome c oxidase subunit 1 divergences among closely related species, *Proc. R. Soc. Lond.*, 270, S96-S99, 2003.
- Martin- Jézéquel, V., Hildebrand, M., and Brzezinski, M.A., Silicon metabolism in diatoms: implications for growth, *J. Phycol.*, 36, 821-840, 2000.
- Morgan, J.A.T., and Blair, D., Relative merits of nuclear ribosomal internal transcribed spacers and mitochondrial CO1 and ND1 genes for distinguishing among *Echinostoma* species (Trematoda), *Parasitology*, 116, 289-297, 1998.
- Morton, B.R., Codon usage and the rate of divergence of land plant chloroplast genes, *Mol. Biol. Evol.*, 11:2, 231-238, 1994.
- Morton, B.R., and Levin, J.A., The atypical codon usage of the plant *psbA* gene may be the remnant of an ancestral bias, *Proc. Natl. Acad. Sci.*, 94, 11434-11438, 1997.
- Rynearson, T.A., Newton, J.A., and Armbrust, E.V., Spring bloom development, genetic variation, and population succession in the planktonic diatom *Ditylum brightwellii*, *Limnol. Oceanogr.*, 51:3, 1249-1261, 2006.
- Siedow, J.N., and Umbach, A.L., Plant mitochondrial electron transfer and molecular biology, *The Plant Cell*, 7, 821-831, 1995.
- Smith, M.A., et al, DNA barcodes reveal cryptic host-specificity within the presumed polyphagous members of a genus of parasitoid flies (Diptera: Tachinidae), *Proc. Natl. Acad. Sci.*, 103:10, 3657-3662, 2006.
- Song, B., and Ward, B.B., Molecular Characterization of the assimilatory nitrate reductase gene and its expression in the marine green alga *Dunaliella tertiolecta* (Chlorophyceae), *J. Phycol.*, 40, 721, 2004.
- Stabile, J.E., Gallagher, J.C., and Wurtzel, E.T., Colinearity of chloroplast genomes in divergent ecotypes of the marine diatom *Skeletonema costatum* (Bacillariophyta), *J. Phycol.*, 31, 795-800, 1995.
- Thamtrakoln, K., Alverson, A.J., and Hildebrand, M., Comparative sequence analysis of diatom silicon transporters: towards a mechanistic model of silicon transport, *J. Phycol.*, 00, 1-13, 2006.
- Thamtrakoln, K., and Hildebrand, M., Approaches for functional characterization of diatom silicic acid transporters, *J. Nanosci. Nanotech.*, 5:1, 1-9, 2005.
- Tyystjärvi, T., et al, Action spectrum of *psbA* gene transcription is similar to that of photoinhibition in *Synechocystis* sp. PCC 6803, *FEBS Letters*, 516:1-3, 167-171, 2002.

G. E. Lau and T. A. Rynearson, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (glau@ycp.edu, rynearson@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

Behavior of Ice Formaldehyde Mixtures under Simulated Polar Conditions

Stephanie Luberda,¹ and Brian Heikes

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. The process by which formaldehyde is transferred from vapor to solid ice was studied in three separate experiments. These were conducted in order to understand sample preservation, mass transfer of formaldehyde from high to low concentration ice and the process by which formaldehyde is deposited into snow. A simple series of cool and cold chambers were used to grow the snow within a cold finger. The samples were melted and the formaldehyde was measured using a fluorometer. Our studies at -20°C showed that formaldehyde will decompose over time within an ice sample and formaldehyde was transferred from a high to low concentration ice through air. During snow growth, the quasi-liquid layer is inferred to play an important role in the deposition of formaldehyde into snow.

1. Introduction

Formaldehyde is a common trace component in Earth's atmosphere. It is readily soluble in water and is found in rain and snow. This implies that it is deposited into snow as it forms within the atmosphere and accumulates upon the ground. In Polar Regions, this snow continues to build up over tens of years and eventually turns to ice. By studying this ice, scientists are hoping to get a glimpse into past chemical climates and how the chemistry in the atmosphere works. There is one major set back that keeps scientists from achieving this; air-snow chemistry of formaldehyde in polar climates remains poorly understood (for example, Couch et al., 2000; Jacobi et al., 2006). The process of formaldehyde deposition to an ice crystal from a vapor is uncertain. Prior research cannot seem to match the formaldehyde levels found in nature. The artificial snow made in laboratories seems to have less formaldehyde than natural snow. Another phenomenon scientists are unable to solve is why new snow and older snow that has been sitting for years have very different amounts of formaldehyde. It is these small mysteries; we have attempted to gain insight into this summer.

We performed three separate experiments designed to dig deeper into the process in which formaldehyde is deposited into snow from a vapor. The first was to test the stability of formaldehyde in frozen samples and how well it is preserved within the ice over time. This would be important to storing ice samples over time and whether or not the formaldehyde would stay within the ice. The second experiment was to find out if there is a mass transfer of formaldehyde from a high concentration ice to a low concentration ice through vapor. This experiment was to try and explain why new snow and old snow have different levels of formaldehyde. The third and final experiment was to grow ice from moving air that is saturated with water and formaldehyde vapor. Knowing the process in which formaldehyde is deposited into ice is important to understanding how this relates to processes happening in nature.

There are several possible ways that formaldehyde is transferred from vapor to solid ice. Figure 1 demonstrates the ways we hypothesize formaldehyde will move to ice. It

can either deposit directly from the vapor into ice already formed, possibly involving a subsequent reaction to form a di-alcohol. However formaldehyde may enter the ice matrix through a quasi-liquid layer present on the ice surface. This liquid layer is a very thin layer of water that has not formed into the rigid ice lattice. This layer gets thicker as the temperature is closer to 0°C and helps explain why ice is slippery. We hypothesize that the quasi-liquid layer plays the more important role in how formaldehyde is deposited into ice. Formaldehyde enters liquid water very easily so it would be able to enter the quasi-liquid layer and then be brought into the ice matrix. This process would be much easier than formaldehyde trying to enter an ice matrix that is already formed. It also runs contrary to the view of Crouch et al. [2000].

2. Methods

All samples of formaldehyde solutions were measured using a fluorometer. This required the samples be mixed with reagents. The reagents consisted of Formaldehyde Dehydrogenase (FDH), Nicotinamide dinucleotide (NAD⁺), Disodium hydrogen phosphate (Na₂HPO₄) and MilliQ water. To prepare the reagents, 4.578g of Na₂HPO₄ were dissolved completely into 500mL of water. The pH was then adjusted to 8 with approximately 2mL Hydrochloric acid (HCl) using an Orion pH meter Model.

Figure 1. Possible Ways Formaldehyde Moves from Vapor to Ice

¹Now at Minnesota State University, Mankato, MN

290A. Finally, both 113mg of NAD⁺ and 50 units of FDH were added

The fluorometer pulls both the sample solution and reagents through a peristaltic pump to mix them together within a mixing T. Air is then added at measured intervals to help maintain segmented flow through the reaction delay coil. Before the solution is pumped to the fluorometer, the air is released and the solution continues into the fluorometer. A computer then measures the signal, in volts, given off by the fluorometer.

2.1 Sample Preservation Experiment

We used two solutions for this experiment: 13M and 0.013M formaldehyde concentration. Four separate trays, each containing ten 7mL Teflon containers, were assembled. Two trays were used for each concentration, one meant to be left open while the other was to be capped. After filling each container with 5mL of the appropriate solution, one tray of each concentration was closed with Teflon caps. All four trays were then placed into a freezer at -20°C. After one week, two containers were taken from each tray and left to melt. The formaldehyde concentration was then measured using a fluorometer. Four containers were measured after three weeks and four more after six weeks.

2.2 Formaldehyde Transfer Experiment

This experiment was conducted using a deviled egg container. This container allowed for two separate solutions to be exposed to each other while maintaining a closed environment. Eight divots, used for holding an egg, was filled with 5mL of MilliQ water for a blank and eight were filled with 5mL of 0.013M formaldehyde solution. The cover was put over the container and it was placed into a freezer. It was allowed to sit for 6 weeks, with the expectation that formaldehyde would transfer from the high concentration ice through the vapor into the blank ice. The formaldehyde concentration was again measured using a fluorometer.

2.3 Snow Growth Experiment

Three solutions were used during this experiment: 13 μ M, 26 μ M and 39 μ M Formaldehyde. Snow was also grown using MilliQ water as blanks. The snow was grown using a system of cold chambers and shown schematically in Figure 2. One chamber was used to saturate the air. Pure air was generated by an Aadco Pure Air generator and pumped into a concordant flow air/water mixing coil. The formaldehyde solution was also pumped to the coil by a peristaltic pump where the air and solution were allowed to mix. The coil was placed into a cool bath at 20°C to allow for saturation. The saturated air was then pumped to a cold finger, while the excess water was pumped to a waste container. The cold finger condenser was placed into a cold chamber at -10°C for three hours to allow for adequate snow growth. Three snow samples were grown from each concentration. The snow was then allowed to melt and the formaldehyde concentration was measured using the fluorometer.

The experiment was repeated using dry ice to form the ice at -78°C. Using a vacuum flask as the cold chamber,

Figure 2. Experimental Setup to Grow Snow

dry ice was packed into the flask around the cold finger. Every 30 minutes or so, we checked the dry ice and added more if it was needed. Time permitted that only two snow samples be grown from each concentration.

2.4 Signal Processing

The fluorometer generates a continuous signal. Each sample was run for 10 minutes and because of system response time, only the center 3 minutes were used to quantify each formaldehyde sample. Fluorescence blanks were run between each sample. The signal for each sample was a 3 minute average of 1 second data taken from the center of the signal line. From this average, a blank was subtracted. The sample blank was interpolated from the two blanks surrounding each sample. The resulting signal, in volts, represented the concentration of formaldehyde within the sample. Using a calibration equation determined from known standard concentrations, the concentration of each unknown sample was found.

3. Results

The results of the sample preservation experiment are presented in Figure 3. Week 1 of the 0.013M concentration ice is missing due to the fact that the fluorometer was saturated and unable to read over 10 volts. This led to the realization that high concentration solutions needed to be diluted 1:1000mL. The closed containers in both concentrations show a slight but significant decrease as time progressed. The open containers of the low concentration, 13 μ M, showed a significant increase in formaldehyde over six weeks. The open containers of the high concentration, 0.013M formaldehyde, showed a slight decrease. Using a t-test, with a 95% confidence level, the mean value from each week shows a significant change between the open and closed containers.

The formaldehyde transfer experiment showed that formaldehyde moved from the high concentration, 0.013M, solution to the blanks. As shown in Figure 4, the ice concentration mean value of the blanks was 81.28 μ M which is a significant increase starting from zero. The high concentration solution also shows a decrease in formaldehyde after six weeks.

Figure 3. Data showing sample preservation over time. Barbs at top of columns show one standard deviation of the three replicates.

The snow growth data were analyzed using the procedure outlined in Burkhart et al. [2002]. Figure 5 shows the value plus standard deviation for each source-snow concentration pair. The linear trend with source concentration demonstrates the data are behaving ideally. K_D is the Henry's Law constant, within our experiment, determined from the ratio of the final bulk ice concentration to the gas-phase concentration and has units of molar per atmosphere. The Henry's Law constant results are presented in Figure 6 as a $\log_{10}$ of K_D for each temperature by the star. Using Burkhart's method, the value we found for K_D at -10°C was $2.23 \text{ mol L}^{-1} \text{ atm}^{-1}$. The value for K_D at -78°C was $2.56 \text{ mol L}^{-1} \text{ atm}^{-1}$. Figure 6 is modified from Burkhart et al. [2002] and shows their laboratory values and those for firm snow from Hutterli et al. [1999].

4. Discussion

The sample preservation experiment illustrated several points. First, the trend of the closed containers in both concentrations may be due to the decomposition of formaldehyde within the ice. Since the containers were closed, it's most likely that the formaldehyde wasn't given off to the air by the ice but decomposed. Secondly, the low concentration ice seems to have collected formaldehyde from the surrounding air. This may have been an attempt to equilibrate the partial pressures within the ice to the air by Henry's Law. We think this is because the two ice

Figure 4. Data from transfer experiment showing the mass transfer from high to low concentration ice over a period of 6 weeks. Barbs at top of columns show one standard deviation of the three replicates.

Figure 5. Snow growth at both -10°C and -78°C show a linear trend in accordance with Henry's Law.

Figure 6. Graph taken from Burkhart et al. [2002] with expanded axes and our points added as the stars. Burkhart et al.'s data (diamonds) and Hutterli et al.'s data (black circles) are comparing laboratory and field K_D values.

solutions were trying to equilibrate through the vapor. Thirdly, the high concentration ice seems to have given off formaldehyde to the air. The concentrations are trending downward in an attempt to equilibrate to the air. It seems that the high concentration ice is giving off formaldehyde to the air and the low concentration ice is collecting it from the air.

The transfer experiment results confirmed the earlier statement of formaldehyde transferring from the higher concentration ice to the lower concentration ice. The increase in the blanks was significant. The higher concentration ice also seems to have a trend downward over time, signifying a loss of formaldehyde. There seems to be a definite transfer of formaldehyde through the air within the container.

These trends may very well be occurring within nature and could explain the difference between old and new snow in nature. As the snow sits over time, the formaldehyde is decomposing within the snow pack and formaldehyde levels would be decreasing. As new snow falls on top of the old snow it puts the system out of equilibrium. The newer, higher concentration snow may start releasing formaldehyde to the air while the old snow would collect it until they were in equilibrium with each other. All the while, the formaldehyde would be decomposing within all the snow, new and old.

These trends show the samples of snow may not be very stable in storage. If the formaldehyde is decomposing within the ice, storing the ice for long periods of time may lead to less formaldehyde levels. This would imply that the samples would be inaccurate if left in storage.

The snow growth experiment seemed to follow nature more so than Burkhart et al. While performing our experiment, we took into account the quasi-liquid layer during the formation of snow. The formaldehyde was able to enter the liquid layer before becoming trapped within the ice matrix. Our snow was formed straight from air containing water vapor and formaldehyde vapor, allowing co-condensation mediated by an evolving quasi-liquid layer. Whereas Burkhart et al. moved formaldehyde air through a tube filled with pre-existing snow. The formaldehyde was trying to break into an already existing ice matrix and this may restrict the formaldehyde from entering the snow. This may have been why Burkhart et al. data were lower in concentration than Hutterli et al.'s natural snow values. Our datum point at -10°C seems to fit right into the field data from Hutterli et al. This gives evidence that the quasi-liquid layer plays a role in the deposition of formaldehyde into snow. Our datum point at -78°C doesn't fit into the natural snow trend. This may be an artifact from the way we conducted this portion of the experiment. We packed the dry ice around the cold finger but after about 30 minutes, the dry ice had sublimated away from the finger leaving a gap of air between the finger and ice. This air may have been warmer than the dry ice and have skewed our results.

If we were to perform these experiments again, there are several things we would do differently. We would perform the sample preservation in different temperatures to see if the formaldehyde would still transfer from the high to low concentration ice. It would also be useful to know if the formaldehyde would decompose at lower temperatures. This would also lead to checking sample preservation in the refrigerator. If formaldehyde decomposes within ice in the freezer, it may very well decompose in samples stored in the refrigerator. Another change we would make would be to have the dry ice in an ethanol, acetone or methanol slurry so the temperature would be constant at -78°C . This would prevent the air pocket from forming beside the cold finger and possibly skewing the data. I would also try to grow the snow under different temperatures to add more data points to the graph. This would help to confirm the quasi-liquid layer as being an important part of formaldehyde deposition within ice. Should it not be a straight line this is an indication that other processes could be in play and a decreasing role of the quasi-liquid layer as temperature decreases.

Acknowledgements. Special thanks to Haiwei Shen, Amy Higbie and Florian Werner for all their help. Also, much thanks to Brian Heikes for all his guidance and help during the program. Thanks to Rob Pockalny, Kim Carey and Cristin Ashmankas for setting up the SURFO program and making the summer a great one. Funding jointly by the Department of Defense ASSURE and National Science Foundation REU Programs.

References

- Burkhart, J., Hutterli, M., Bales, R. Partitioning of formaldehyde between air and ice at -35°C to -5°C . *Atmospheric Environment* 36 2157-2163, 2002.
- Couch, T., Sumner, A., Dassau, T., Shepson, P., Honrath, R. An Investigation of the Interaction of Carbonyl Compounds with the Snowpack. *Geophysical Research Letters* 27 (15), 2241-2244, 2000.
- Hutterli, M., Rothlisberger, R., Bales, R. Atmosphere-to-snow-to-firn transfer studies of HCHO at Summit, Greenland. *Geophysical Research Letters* 26 (12), 1691-1694, 1999.
- Jacobi, H., Annor, T., Quansah, E. Investigation of the photochemical decomposition of nitrate, hydrogen peroxide, and formaldehyde in artificial snow. *Journal of Photochemistry and Photobiology A: Chemistry* 179, 330-338, 2005.
- Lazrus, A., Fong, K., Lind, J. Automated Fluorometric Determination of Formaldehyde in Air. *Analytical Chemistry* 60 (10) 1074-1078, 1988.

S. J. Luberdá and B. G. Heikes, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (stephanie.luberdá@mnsu.edu, bheikes@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

Characterizing Flow Processes in Narragansett Bay Using Reciprocal Transmission Sonar

Elizabeth Petrik,¹ and David S. Ullman

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. This June, a reciprocal transmission sonar system was deployed off the University of Rhode Island Graduate School of Oceanography (GSO) pier to study flow patterns in Narragansett Bay. In particular, the system was to be used to quantify the turbulent intensity and its relationship to forcing mechanisms present in the bay. Simultaneous coded pings were transmitted between two transmitter/receiver transducers, and the difference between the times of flight in each direction, along with an estimated sound speed, was used to calculate the path-averaged current velocity along the acoustic path. The phase of the code received by each transducer gave a very precise ($\sim 0.01 \mu\text{s}$) measurement of the time of flight, with an unknown but apparently constant offset. The system's high ping rate, high carrier frequency, and capacity to acquire long data series under a variety of conditions allowed for resolution of a wide array of processes. We examined low-frequency, tide-driven changes in the mean current and compared them to current measurements taken using an acoustic Doppler current profiler (ADCP). Apart from a constant offset, the two methods showed agreement within the measurement uncertainties. We also took 1000-second spectra and found a persistent peak at approximately 0.1 Hz consistent with swell. The height and frequency time series of this peak were found to correlate with swell data from a National Oceanographic and Atmospheric Administration (NOAA) buoy off Montauk Point. At slightly lower frequencies (~ 0.01 Hz), we saw spectral evidence of small-scale (< 10 m) velocity fluctuations or scintillations caused by turbulent eddies. These, however, defied a quantitative analysis using Kolmogorov's $k^{-5/3}$ law.

1. Introduction

Turbulence is a three-dimensional, vortical, dissipative, chaotic process that is an important mechanism for distributing heat, salt, oxygen, pollutants, nutrients, and biomass throughout the ocean. The anoxic conditions that caused the 2001 Greenwich Bay fish kill, for instance, were a consequence of density stratification due to inadequate turbulent mixing. The original aim of this project was to use acoustic scintillation techniques developed by *Farmer and Di Iorio* [1994, 1998] to increase our understanding of turbulent processes in Narragansett Bay by quantifying the turbulent intensity and correlating it with forcing mechanisms, such as tidal currents.

Since the apparatus was capable of taking relatively long series of measurements, we also sought to corroborate our calculation of the mean current by a comparison with acoustic Doppler current profiler (ADCP) tidal current data. Furthermore, spectral analysis of the velocity allowed measurements of oceanic swell at the GSO pier.

In an ideal study of acoustic scintillations using reciprocal transmission, two travel times are simultaneously measured for opposite paths. This permits the separation of fluctuations (or "scintillations") in the travel velocity caused by vector (fluid velocity) and scalar (sound speed) components, as demonstrated by *Di Iorio and Farmer* [1998]. In our experiment, however, an unknown offset in the measurement of the travel time forced us to focus solely on the velocity fluctuations. We made independent measurements of the sound speed and assumed that it remained relatively constant for the duration of a data series. Nonetheless, the precise measurement of the time difference between the two paths

permitted by the phase of the received signals allowed us to see relatively low-energy perturbations in the mean current.

2. Materials and Methods

2.1. Apparatus and Setup

Our apparatus consisted of a pair of sonar tripods deployed off the GSO pier in mid-June. They were stationed at about 100 m from the pier, separated by 57 ± 4 m², and oriented north to south. The water depth at this location is about 10 ± 1 m, depending on the tide, and the transducers used in this experiment were positioned 3.09 ± 3 m above the bay floor. A sea cable connected to a router on the pier provided real-time control of the sonar system.

A pair of transmitter/receiver sonar transducers, one on each tripod, was used in reciprocal transmission mode, as described by *Di Iorio and Gargett* [2005]. Both were fired by the same computerized signal to ensure simultaneity. In order to resolve relatively small, transient flow structures, the transducers transmitted at a carrier frequency of 120 kHz and were set to ping at 10 Hz. In receiving mode, the sonar system sampled at 4 times per cycle, or 480 kHz, after counting a specified number of "blank" samples in the time before the arrival of the signal. Due to an unresolved problem with the data acquisition software, however, an unspecified amount of time was allowed to pass between the end of the transmission and the beginning of the counting of blank samples, and we were consequently unable to determine the absolute travel time from these measurements.

In order to obtain estimates for the sound speed, we also took weekly salinity, temperature, and pressure profiles at the tripod location using a conductivity, temperature, and

¹Now at Amherst College, Amherst, Massachusetts

depth sensor (CTD), and computed the sound speed from an empirical formula.

An ADCP positioned a few meters northeast of the northern tripod was also used for independent verification of the reciprocal transmission system's current data, as well as to find the current normal to the acoustic path and to obtain time series of the water pressure.

2.2. Data Acquisition and Processing

In order to improve the signal-to-noise ratio and the accuracy of the travel time measurement, the sonar carrier frequency was phase-modulated with a 7-bit pseudorandom code of bit length 4 cycles. Binary m-sequences were used for the coding, where a phase of 0 corresponded to a bit value of 1, and a phase of π corresponded to a value of 0.

In the data processing program, the raw signal was demodulated into two components (Fig. 1). The origin of time was set at the beginning of the received signal, and the components of the signal in phase with 120 kHz cosine and sine waves were arbitrarily designated as the in-phase and quadrature components, respectively. The demodulated signal was then low-pass filtered to extract the in-phase and quadrature components of the original code. We next found the covariance between a template of the transmitted code and the demodulated, filtered signal at each sampling point in the received signal. The correlation amplitude at each point is defined by

$$A = \sqrt{\langle I_{rec} \rangle \cdot \langle I_{trans} \rangle + \langle Q_{rec} \rangle \cdot \langle I_{trans} \rangle} \quad (1)$$

where I_{rec} is the in-phase component of the received signal, I_{trans} is the in-phase component of the transmitted code template, and Q_{rec} is the quadrature component of the received signal. (The transmitted code has no quadrature component.) A has its maximum at the point τ_{rough} nearest the start of the received signal. A quadratic interpolation performed on the values of A at the points above and below τ_{rough} gives a better estimate (τ_{interp}) of the lag time. Ideally, τ_{interp} should be accurate to within 1 sampling period, or $1/480 \text{ kHz} \approx 2 \mu\text{s}$, but in reality, it is regularly off by about a carrier frequency cycle, and it occasionally jumps tens of cycles when the maximum of A does not correspond to the beginning of the received signal.

The phase of the transmitted signal, defined as

$$\phi = \arctan\left(\frac{\langle Q_{rec} \rangle \cdot \langle I_{trans} \rangle}{\langle I_{rec} \rangle \cdot \langle I_{trans} \rangle}\right) \quad (2)$$

where "arctan" is the four-quadrant inverse tangent function, is much more precise. The phase at τ_{interp} was interpolated from the values at the sampled points above and below τ_{interp} . The phase in units of fractional cycles is added onto the integer number of cycles in τ_{interp} . When this is done for consecutive pings, a smooth time series of τ with an uncertainty of $\sim 0.1 \mu\text{s}$ (estimated by eye) is obtained.

In practice, a few extra steps are required to get an accurate value for τ . A transmitted ping reaches the receiver not only by the straight-line path, but also by

Figure 1. Steps in processing a raw sonar signal. The transmitted signal is a 120 kHz carrier frequency phase-modulated by the m-sequence 0100111 at 4 cycles per bit. This code is transmitted twice in a row. a.) Unprocessed "ping." The signal amplitude is related to the transducer voltage, and the sampling rate is 480,000 samples per second. The x-axis represents the number of recorded samples. b.) The signal is demodulated into in-phase (dark) and quadrature (light) components by multiplying it by a 120 kHz cosine and sine wave, respectively. c.) The demodulated signal is low-pass filtered and is shown with a template of the transmitted code (dashed) superposed at τ_{rough} . d.) The un-normalized correlation amplitude has its highest peak at τ_{rough} , where the received code starts. The secondary peak occurs where the second transmission of the code is received.

reflections off the sea surface and floor. These signals reach the receiver at a time delay of order one code length after the direct path, and can interfere with the original signal, degrading the correlation amplitude. To combat this problem, we transmitted the original 7-bit code with one repetition, called a guard sequence. Since m-sequences have very high, narrow autocorrelation peaks, the guard sequence ensured that the covariance would remain low between the points at which the transmitted code matched up with the first received code and when it matched up with the guard sequence. Since the correlation with the guard sequence was occasionally higher than with the first code, we programmed the data processing script to find all the local maxima in the covariance and choose the correlation peak closest to the value of τ for the previous ping.

Even after this adjustment, the time series of τ still showed some spikes, so we applied a filter first to eliminate values of τ whose correlation amplitude A was more than 2 standard deviations below the mean value for the series, and then to eliminate remaining values of τ that were more than 2.5 standard deviations from the mean. In most cases, this eliminated large spikes, although some persistent jumps to different offset values remained.

3. Theoretical Background

3.1. Fluid Velocity

For the setup diagrammed in Fig. 2, the travel times of sonar signals transmitted in either direction are

$$t_{mr} = \frac{L}{c+v}, t_{rm} = \frac{L}{c-v} \quad (3)$$

where t_{mr} is the travel time from the main to the remote tripod, t_{rm} is the travel time from the remote to the main tripod, c is the path-averaged sound speed, L is the distance between the tripods, and v is the path-averaged northward current. Because of the data acquisition software ambiguity, we do not know t_{rm} and t_{mr} but only the difference between them, $t_{rm} - t_{mr} = \tau_{rm} - \tau_{mr} = \Delta\tau$. Therefore, to find the current, we solved Eq. (3) for v in terms of $\Delta\tau$, c , and L . The result is shown in Eq. (4).

$$v = \frac{L}{\Delta\tau} \left(1 - \sqrt{1 - \frac{(\Delta\tau)^2 c^2}{L^2}} \right) \quad (4)$$

In using this formula, we have assumed that the effect of the fluctuations in the sound speed on $\Delta\tau$ over the course of a data series were negligible compared to the effect of the velocity fluctuations. This assumption is justified by an analysis of the effects of short-term fluctuations in c and v on representative values of Δt .

3.2. Turbulence

The following is an overview of the equations used in our turbulent analysis. A detailed discussion of the derivation of the rate of viscous dissipation and of Kolmogorov's law can be found in *Kundu* [1990].

When a vortical eddy is advected across the acoustic path, as diagrammed in Figure 2, the mean current undergoes a periodic fluctuation. It reaches a maximum when the angular velocity of the vortex u' is parallel to v , decreases to its original value when the u' is orthogonal to v , and reaches a minimum when u' is antiparallel to v . Taylor's hypothesis states that for sufficiently high current velocities normal to the acoustic path, we can make the approximation that the advected eddies are frozen, which leads to a relationship between the current speed $|u|$ across the acoustic path, the frequency f of the fluctuation in v , and the wave number k associated with an eddy of size $l = 2\pi/k$.

$$k = \frac{2\pi f}{|u|} \quad (5)$$

Applying a fast Fourier transform to the time series of v and multiplying each term in the Fourier series by its complex conjugate gives a spectrum S in units of velocity variance/frequency or $\text{m}^2/\text{s}^2/\text{s}^{-1}$. The rate of viscous dissipation of turbulent kinetic energy is called ϵ and is a consequence of strain produced by velocity shear. The

Figure 2. Experimental setup. The northward direction is indicated. The northward current is represented by v , the westward current by u , the vortex speed by u' , and the distance between the tripods by L .

dimensions of S are m^2/s^3 . In 1941, Kolmogorov argued that the variance spectrum of eddies that are much smaller than the boundary layer are independent of the energy in the largest scales. He further postulated that the variance spectra of eddies that are much larger than the scale on which molecular interactions dissipate energy are independent of the fluid viscosity. In this band of eddy sizes, called the inertial subrange, Kolmogorov suggested that S could be written as a function of k and ϵ alone, where ϵ enters because energy must be transferred from the largest to the smallest scales across the inertial subrange. Dimensional analysis gives the relation known as Kolmogorov's law.

$$S = A \epsilon^{2/3} k^{-5/3} \quad (6)$$

The constant of proportionality for this relationship has been experimentally determined to be ≈ 1.5 for all turbulent flows.

In the inertial subrange, the logarithm of the spectrum as a function of the logarithm of the wave number is therefore a line of slope $-5/3$ for point measurements of the velocity. Our apparatus, however, path-averages the velocity, so the multiple small eddies crossing the acoustic path at any given moment tend to cancel each other out. This results in an attenuation of the spectrum by a factor of $1/k$, so that the final spectrum is proportional to $k^{-8/3}$. The full formula for the path-averaged velocity variance spectrum has been derived by *Di Iorio and Farmer* [1998].

In order to arrive at a quantitative characterization of the turbulent intensity, we first apply a Fourier transform to our path-averaged velocity data to obtain a variance spectrum as a function of f . We can then use the value of u estimated from ADCP measurements and Eq. (5) to transform the spectrum into wave number space. The spectrum obtained should be proportional to $k^{-8/3}$ in the inertial subrange, which is bounded on the upper end by the depth of the water, about 10 m. We can then use Eq. (6) to find a value for ϵ , which tells us how fast turbulent kinetic energy is being turned into heat.

3.3. Uncertainty Analysis

The quantities used in Eq. (4) to obtain the current are L , c , and $\Delta\tau$. To a first order approximation, the errors in each quantity can be propagated by multiplying the derivative of v with respect to each by the estimated error. Thus, the errors in v as a result of ΔL , Δc , and $\Delta(\Delta\tau)$ are

$$\Delta v_L = \frac{1}{\Delta \tau} \left(1 - \frac{L}{\sqrt{L^2 - (\Delta \tau)^2 c^2}} \right) (\Delta L) \quad (7)$$

$$\Delta v_c = \frac{-(\Delta \tau) c}{\sqrt{L^2 - (\Delta \tau)^2 c^2}} (\Delta c) \quad (8)$$

$$\Delta v_{\Delta \tau} = \frac{L \left(L - \sqrt{L^2 - (\Delta \tau)^2 c^2} \right)}{(\Delta \tau)^2 \sqrt{L^2 - (\Delta \tau)^2 c^2}} (\Delta(\Delta \tau)) \quad (9)$$

respectively.

The distance L between the tripods was determined using a global positioning system (GPS) at the site of the buoys secured to the tripods, and we estimate its uncertainty to be ~ 4 m. This error is consistent for all our measurements; therefore, it does not affect time-dependent characteristics like the spectral energy distribution. For the representative current value $v=0.2$ m/s, Δv_L from Eq. (7) is about 0.014 m/s, or 7%.

Based on the sound speed profiles from CTD casts (Fig. 3), it appears that c changes by about 4 m/s from week to week as water temperatures increase. Although we have no measurements of higher frequency fluctuations in c , it seems reasonable to assume that the sound speed does not vary by more than 4 m/s for a data series of only a few days. Using Eq. (8) with $\Delta c=4$ m/s, the estimated value of Δv_c for $v=0.2$ m/s is 0.001 m/s, or about 0.5%.

The highest frequency variations in v must be from statistical noise in the measurement of $\Delta \tau$. We therefore estimate the uncertainty in v caused by $\Delta \tau$ by examining the high frequency noise in the velocity variance spectrum (Fig. 4). The spectrum flattens into $\sim 10^{-7}$ m²/s²/Hz white noise at a frequency of about 0.5 Hz. The area under this part of the spectrum gives the velocity variance, whose square root is the standard deviation. We therefore calculate $\Delta v_{\Delta \tau}$ to be $2 \cdot \sqrt{[(5-0.5) \text{ Hz} \cdot 10^{-7} \text{ m}^2/\text{s}^2/\text{Hz}] \approx 0.0013}$ m/s, or about 0.7% for $v=0.2$ m/s.

4. Results

4.1. Reliability of Method

In order to confirm the accuracy of our measurement of the current, we compared the northward current data obtained using Eq. (4) and the reciprocal transmission measurement of $\Delta \tau$ to the ADCP's data for the northward current 3 m off the sea floor. The ADCP takes localized measurements of the current velocity and averages them in one-minute ensembles, whereas the reciprocal transmission system takes path-averaged measurements at 10 Hz. Some statistical differences between the results of the two methods were therefore expected.

As shown in Figure 5, the current obtained using the reciprocal transmission method tracked the overall shape of the ADCP current very well for the two-tidal cycle

Figure 3. Sound speed profiles from weekly CTD casts. The vertical axis is in decibars, where 1 db $\approx$ 1 m below the surface. The transducer height is 3 m above the maximum depth for each cast, except July 17, when the cast did not reach the bay floor. Significant stratification is seen on July 17 and 31, whereas almost no stratification is seen on July 10 and July 24.

Figure 4. Average velocity variance spectra for data collected at high low flood and ebb tides. The dotted lines show a $-8/3$ slope in the expected inertial subrange; however, the actual data show poor agreement with the projected slope. The plots are indistinguishable except that ebb tide carries significantly more energy in the low frequency (<0.05 Hz) part of the spectrum than any other part of the tidal cycle. All the plots show a swell peak at about 0.1 Hz and a harmonic of this peak at about 0.2 Hz, and all the plots trail off into white noise at about 0.5 Hz.

measuring period, but with an increase in overall magnitude of 3.7(5)% and an offset of -6.83(9) cm/s. From the analysis in the uncertainty section, the magnitude discrepancy can be explained by the uncertainty in L . The offset, however, points to an unexplained measurement bias in $\Delta \tau$. Although this bias prevents our determining the value of the current along the acoustic path, if it is constant, it will not affect the time-dependent characteristics of the current measurement. Thus, the spectra of the data are not compromised by these errors.

ADCP/Reciprocal Transmission Method Agreement, 1 Min. Ensembles

Figure 5. Scatter plot of one minute ensembles of northward current velocities measured by the reciprocal transmission as a function of the ADCP current ensembles for a period of two tidal cycles. The expected best fit, plotted as a black line, is $x=y$; however, we found both a constant offset and a slope discrepancy in the measured data. The actual best fit is plotted in gray, and its equation is shown on the chart.

4.2. Swell Signal

Fourier transforms were performed on 28 segments of reciprocal transmission current data from eleven different days to study the distribution of velocity fluctuations in frequency space. In each segment, ten 1000 s sections of data, each overlapping the previous section by 500 s, were transformed and averaged together. The resulting spectra consistently showed a peak around 0.1 Hz, or 7-12 s, which is approximately the frequency of swell waves recorded by a National Oceanographic and Atmospheric Association (NOAA) buoy off Long Island's Montauk Point (Fig. 6). After data with multiple peaks were removed, the swell peak period from the reciprocal transmission method showed a positive correlation with the NOAA buoy's measured swell period for the same time (Fig. 7). With an r^2 value of 0.52, however, the linear fit was not good enough to make any quantitative observations about the changes in swell frequencies from Montauk to the GSO. The fact that the slope is less than one, however, indicates that lower frequency components of the swell dominate our signal compared to the NOAA buoy's.

To confirm that the spectral peak was a surface wave signature, we set the ADCP to measure the water pressure at about 1.8 s intervals. Since the pressure is directly proportional to the height of the water column, we expected to see a peak in the pressure spectrum at the same frequency as the peak in the reciprocal transmission spectrum. As shown in Figure 8, multiple peaks appear in the pressure spectrum, one of which corresponds to the 12 s peak in the sonar spectrum measured over the same time period.

4.3. Turbulence

We next sought to apply Kolmogorov's law with the path-averaging correction described in the turbulent theory

Figure 6. Swell data from a NOAA buoy off Montauk Point, Long Island. NOAA measures wave spectra for one hour and reports the average height of the tallest 1/3 of swell waves and the peak period of the swell containing the most energy. The horizontal lines demarcate the times at which reciprocal transmission data were collected. It is notable that the period is of order 0.1 Hz for most of the measured times

Figure 7. Swell period measured by the NOAA buoy plotted as a function of the peak period of the reciprocal transmission spectrum. This plot shows a weak positive correlation between the swell periods.

section to characterize the turbulent intensity. The spectra from high, low, flood, and ebb tides were separately averaged together as shown in Figure 4, and the $-8/3$ slope predicted by the theory was superimposed on the plot. For each section of the tidal cycle, however, the actual slope was shallower than predicted.

One possible reason for this is that the current speed u normal to the acoustic path was too small and inconstant for Eq. (5) to apply. The average speed of this current is about 10 cm/s compared to the along-path current v , and it contains fluctuations of order .001 Hz (about the length of a data segment used to produce one spectrum) that are large compared to its amplitude over a tidal cycle. The westward current speed can therefore vary from 0 to 0.2 m/s during the course of a single spectrum. Thus, Eq. (5) may not represent an accurate conversion from frequency to wave number space either because Taylor's hypothesis does not apply for small values of u or because u is too variable for

Figure 8. Pressure and velocity spectra measured over the same time period. Peaks in the spectra are marked with a dotted line. The pressure spectrum shows two main peaks, the second of which corresponds to the .08 Hz swell peak in the velocity spectrum.

its mean value to serve as a good conversion factor. If f is not proportional to k for a given spectrum, then the slope of $\log(S)$ with respect to $\log(f)$ will not be the same as the slope of $\log(S)$ with respect to $\log(k)$, and Kolmogorov's $-5/3$ law cannot be applied.

An alternate explanation is that the water column may be too stratified to find an inertial subrange. Several of the sound speed profiles in Figure 3 show values of c that change significantly with depth, indicating that temperatures decrease by several degrees from the surface to the bottom. Kolmogorov's law requires that the turbulence be isotropic; therefore, it does not apply where vertical layering may give eddies a preferred axis.

A third possible explanation is that the swell peak dominates in the inertial subrange part of the spectrum. Eddies with the swell's frequency of about 0.1 Hz advected through the acoustic path at the average cross-path current speed of 0.1 m/s would be of order 1 m in diameter, which should be well within the inertial subrange at our measurement site.

5. Discussion and Future

The good agreement between the ADCP and reciprocal transmission values for the current along the acoustic path, except for the constant offset, shows that reciprocal transmission is useful for measuring the path-averaged along-path current (v) with very high resolution. The low noise level in the high frequency range confirms that the method of maximizing the correlation amplitude and adding the phase provides a precise measurement of very small (~ 1 mm/s) fluctuations in the path-averaged along-path current velocity.

Once the software problem causing the offset error is resolved, the travel times t_{mr} and t_{rm} will be very accurately measurable, and Eq. (3) will be able to be solved for c and v separately. It would be interesting to study the relative effects of current velocity and speed of sound fluctuations on the travel times.

The consistent ~ 0.1 Hz spectral peak indicates that swell from the Atlantic is a significant part of the fluid motion in Narragansett Bay. Further studies could improve our understanding of how the swell period and amplitude changes upon entering the bay, what features and conditions of the bay determine its behavior, and whether swell is an important source of the energy that is dissipated in turbulent mixing. In order to study turbulence without the interference of this swell peak, however, we suggest that in future deployments, the tripods be oriented west-to-east, across the mouth of the bay. Since the swell waves travel primarily from south to north, this should attenuate their effect on the spectrum. Since tidal currents also run primarily north and south, this west-east orientation would provide sustained time periods when the current across the acoustic path is strong and in one direction. The application of Taylor's hypothesis would then be justified, and Eq. (5) could be used to convert from frequency to wave number space during strong flood and ebb tides.

Although the spectra we saw did not fit the Kolmogorov $k^{-5/3}$ law, the ebb tide spectra contained more energy in the lower frequency ($f < 10^{-2}$ Hz) part of the spectrum than did other parts of the tidal cycle. This indicates that the strong ebb currents produce more mixing than is present at other times. If this mixing behaves according to Kolmogorov's law, we hope that a future deployment with an east-west tripod orientation will allow us to find a value for ϵ .

Acknowledgments. We are grateful to Jim Fontaine, Tom Puckett, Mark Gustatson, and the science diving team for their help with the preparation and deployment of the apparatus, to Svein Vagle for setting up the software, and to David Farmer, Tetsu Hara, and Tobias Kukulka for their many intellectual contributions to this project. We thank the Department of Defense ASSURE Program and the National Science Foundation REU Program for funding the SURFO program at the University of Rhode Island,

References

- Di Iorio, Daniela and Farmer, David M., Separation of current and sound speed in the effective refractive index for a turbulent environment using reciprocal acoustic transmission, *J. Acoust. Soc. Am.* 103, 321-329, 1998.
- Di Iorio, Daniela and Farmer, David M., Path-averaged turbulent dissipation measurements using high-frequency acoustical scintillation analysis, *J. Acoust. Soc. Am.* 96, 1056-1069, 1994.

Di Iorio, Daniela and Gargett, Ann E., Studies of turbulent processes using Doppler and acoustical scintillation techniques, in *Sounds in the Sea, From Ocean Acoustics to Acoustical Oceanography*, by Herman Medwin et al., pp. 500-517, Cambridge University Press, New York, 2005.

Kundu, Pijush K., Turbulence, in *Fluid Mechanics*, pp. 416-473, Academic Press Inc., San Diego, 1990.

E. S. Petrik and D. S. Ullman, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (epetrik08@amherst.edu, d.ullman@gso.uri.edu)

The search for hydrogenase activity in *Psychromonas kaikoe*, a piezophilic, facultative anaerobic, marine bacterium

Dana M. Reznik¹, and David C. Smith

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. It has been argued that, due to the anaerobic nature and low levels of metabolically available energy, deeply buried marine sediments can serve as an analog for modeling habitability on extraterrestrial planets. Therefore, microorganisms inhabiting this subsurface anaerobic environment are of particular interest to microbiologists and astrobiologists. H_2 is an important intermediate in anaerobic metabolism and its utilization by microorganisms is mediated by the enzyme hydrogenase. Hydrogenase may be a proxy for microbial activity in subsurface habitats with extremely low metabolic rates. Currently, a tritium-based assay is used to quantify hydrogenase activity in samples retrieved from the subsurface. Despite the fact that microorganisms inhabiting the deep subsurface have evolved to function at high pressure, the assays are performed at one atmosphere and the effect of pressure has yet to be taken into account. In an attempt to find a model organism to study hydrogenase activity as a function of pressure, the piezophilic bacterium *Psychromonas kaikoe* was grown anaerobically under pressure and tested for the presence of hydrogenase. Even though the results of this study were inconclusive, the methods outlined by this paper will allow for the investigation of additional piezophilic isolates to be investigated for hydrogenase activity in the same fashion. In the future, a piezophilic microorganism will aid in our ability to determine the effects of pressure on hydrogenase activity and therefore, a more accurate view of microbial activity in the marine subsurface.

1. Introduction

Aquatic sediments that contain microbial communities play an essential role in the carbon cycle. Microbial activity in these areas has been investigated using metabolic assays. These assays determine the rates of change of substrates and products. Metabolic rates are often determined with the use of radiolabeled substrates given the extreme sensitivity of quantifying radioisotopes. H_2 has been studied because it is an important metabolic intermediate in anaerobic microbial communities in the subsurface seafloor. This gas is produced by carbohydrate and fatty acid fermentation and is used by sulfate-reducers, homoacetogens, and methanogens (Schink, 1997).

Hydrogenases are expressed by all bacteria that consume or produce hydrogen. These enzymes are of a large, diverse family and have been extensively researched. Hydrogenase activity may be a proxy for microbial activity in subsurface habitats with very low metabolic rates. This enzyme has been measured *in vivo* using a radiometric assay under anoxic conditions. The enzymatic reaction:

(where E = enzyme and H = hydrogen) demonstrates how hydrogenase catalyzes isotopic exchange between dissolved hydrogen gas (containing 3H) and the hydrogen in water molecules. Quantification of hydrogenase activity from sediments from the deep-sea floor has been performed using a tritium-based assay (Soffientino *et al.*, 2005). However, the tritium-based assay is currently designed to be conducted at 0.1 MPa.

Samples retrieved during deep-sea coring of the subsurface are brought to atmospheric pressure (0.1 MPa). The sediments and microbial communities in these cores are removed from their normal high-pressure environment and assayed at atmospheric pressure and therefore the

hydrogenases are not assayed at *in situ* pressures. A model organism may facilitate the detection of changes in hydrogenase activity at pressures greater than atmospheric pressure.

Piezophilic bacteria have been isolated and studied in order to determine the association between the deep-sea environment and its microbial population. Piezophiles are differentiated from other bacteria on the basis of enhanced growth at pressures greater than 0.1 MPa (Yayanos, 1995). *Psychromonas kaikoe* may be an ideal bacterium to discover the effects of pressure on hydrogenase activity. *P. kaikoe* is a halophilic, psychophilic, and piezophilic Gram-negative rod-shaped facultative anaerobe with optimal growth conditions at 3% NaCl, 10°C, and 50 MPa (Nogi *et al.*, 2002). The purpose of this research was to bring *P. kaikoe* into culture anaerobically and test for the presence of hydrogenase activity at different pressures, (0.1 MPa, 25 MPa, and 50 MPa).

In addition to quantifying hydrogenase expression, primers directed towards NiFe hydrogenases (Wawer and Muyzer, 1995) and Fe-only hydrogenases (Ozkan *et al.*, 2001) are used in the polymerase chain reaction (PCR) with DNA extracted from *P. kaikoe*.

2. Materials and Methods

2.1. Culturing Conditions

Psychromonas kaikoe (ATCC #) was brought into culture using modified OF medium (Nogi *et al.*, 2002). The medium was comprised of 3.6% Instant Ocean, 0.5% peptone, 0.1% yeast extract, 1% glucose, 0.5% low-melting point agar, and 0.003% bromthymol blue in distilled water. The medium was sparged with nitrogen after autoclaving and inoculated with *P. kaikoe*. The inoculum was taken up into sterile 3 mL syringes. All bubbles were removed by slight tapping, capped, and sealed with Parafilm. The syringes were incubated at 50 MPa and 10°C for five days

¹Ohio Wesleyan University, Delaware, Ohio 43015

in a pressure reactor seen in Figure 1. *P. kaikoa* syringes colonies grew separately within the agar and can be seen in Figure 2.

2.2 Hydrogenase Assay

Hydrogenase activity from the syringes with *Psychromonas kaikoa* colonies and medium was quantified using a tritium-based hydrogenase assay (Soffientino *et al.*, 2005).

2.3 DNA Extractions

Genomic DNA was extracted from an agar culture of *P. kaikoa* using Lyse-N-Go™ PCR Reagent (Pierce). Genomic DNA was also extracted from *Clostridium pasteurianum*, *Desulfovibrio vulgaris*, and a formalin-fixed culture of *Psychromonas kaikoa* using the DNeasy Tissue Kit (Qiagen).

2.4 Polymerase Chain Reaction

Initial PCR amplifications were performed with a Mastercycler ep System (Eppendorf). 10 µL of purified DNA was added to a 40 µL master mix comprised of *Taq* PCR Master Mix (Qiagen), appropriate primers, and purified PCR water. Two sets of primers were used to amplify different gene sequences. Primers Hyd2F and Hyd2R were used to amplify a 2,067 bp fragment of a NiFe hydrogenase gene (Wawer and Muyzer, 1995). Another set of primers, named Ozkan148F and Ozkan148R, used was specific for an Fe-only hydrogenase gene fragment that is 148 bp long (Ozkan *et al.*, 2001). See Table 1 for sequences. PCR amplifications using the extracted DNA from the formalin-fixed *P. kaikoa* used 5 µL of DNA and 45 µL of the master mix mentioned above.

Amplified DNA from PCR was placed into wells of 1% and 2% agarose gels. A 1% gel was used for the Wawer and Muyzer primer set PCR, while the 2% agarose gel was used for the Ozkan *et al.* primers.

3. Results

3.1 Tritium-based Hydrogenase Assay

Hydrogenase activity is determined by the slope of the regression line as a function of time. There is no significant difference among the live, Hg-killed control and the blank as seen in Figure 3. Therefore it was concluded that there was no significant hydrogenase activity expressed by *P. kaikoa* under these culture conditions

Table 1. Forward and Reverse Primer Sequences

Primers	Direction	Primer Sequence
Wawer & Muyzer	Forward	5'-CCGG(C/T)TGCCCGCC(G/C)AACCC-3'
	Reverse	5'-CGCAGGCGATGCA(G/C)GGGTC-3'
Ozkan.	Forward	5-GGTTTTGAAATCCTACTATGC-3'
and others	Reverse	5-TAGAACAACATCCACATCAGG-3'

Figure 1. The pressure reactor sat on the floor of the cold room (10°C) while the high pressure generator was mounted to a table. The high pressure generator was a manually operated using a screw pump that causes a piston to be compress liquid within a small volume to develop pressure (HiP, High Pressure Equipment Company).

Figure 2. On the left is an image of a 3 mL syringe with suspended colonies of *Psychromonas kaikoa*. The right picture is a *P. kaikoa* colony up close.

Figure 3. Data of *P. kaikoe* grown under pressure in anaerobic conditions. Hydrogenase activity catalyzes isotopic exchange between dissolved hydrogen gas and the hydrogen in water molecules. The rate of isotopic exchange measures hydrogenase activity in a sample. This rate can be measured by adding tritium as a tracer in the dissolved gas, and measuring its rate of transfer into water over time. Disintegrations/min from the liquid scintillation counter (LSC) is plotted above against time. Linear regression lines are also imposed on the graph on the left with their corresponding equations. The graph on the right compares the slopes of the regression lines. The error bars represent the 95% confidence intervals. By comparing the three CI's, it is revealed that the slope of the live sample is not significant. This is true because all the CI's overlap, the live sample is not significant.

3.2 PCR

No bands other than the positive control in the gel on the left were apparent. The boxes in Figure 3 show the locations where bands could have been present if the organism's genomic DNA contained a hydrogenase gene recognized by the primers. This implies that there was no amplification during the PCR reaction. Also, the positive control for the Ozkan *et al.* primers was not seen.

4. Discussion

4.1 Tritium-based Hydrogenase Assay

The simplest explanation for these results is that *P. kaikoe* does not produce hydrogenase. Because the tritium-based assay is very sensitive, it is unlikely that the levels of hydrogenase produced in culture were below the detection limit of the assay. On the other hand, hydrogenase may have been expressed at 50 MPa but is not functional at 0.1 MPa and therefore would not have been detected by the assay. Another possible explanation for the lack of hydrogenase activity is that the culture conditions used in this experiment did not induce hydrogenase production.

In the future, hydrogenase assays conducted at pressures above 0.1 MPa need to be designed. This will require implementing containment precautions for the tritium gas while in the pressure vessel. Additional piezophile isolates may possibly be surveyed for hydrogenase using the materials and methods established by this study. Because this bacterium grew well under the conditions outlined in this paper, the search for a model to show the difference of hydrogenase activity at diverse pressures can continue. Also, by using the syringe/low-melting point agar method, further piezophiles from deep sediments can be isolated and investigated for biochemical properties.

4.2 PCR

As with the tritium-based assay, one can assume that this bacterium does not have any hydrogenase genes. However, this assumption may not be correct when dealing with PCR analysis. It is possible that the genome of *P. kaikoe* contains a hydrogenase gene that is not recognized by the primers used in this study (NiFe and Fe-only hydrogenases). *Psychromonas kaikoe* may have another type of hydrogenase that would not have a similar sequence to the aforementioned hydrogenases. PCR conditions were not optimized either. The initial colonies used for PCR were grown in agar which can inhibit PCR reactions. In addition, because the PCR conditions were not listed in Ozkan *et al.* (2001) the times and temperatures used were based on the primers' T_m 's and base pair length. It is also possible that the Lyse-N-Go Reagent did not extract enough or any DNA from the cells as well. This method does not purify the DNA as well which may cause PCR reagents to stop functioning.

The gel in Figure 4 was improved by removing agar. *P. kaikoe* cells that had been fixed with formalin were used for DNA extraction. Also, positive controls of *Desulfovibrio* and *Clostridium* were used to confirm that the primers and other PCR reagents were functioning properly. The *Desulfovibrio* positive control functioned very adequately. A band was seen in the 2 kbp range. Because no bands were seen from any other well, one can presume that *P. kaikoe* does not have the NiFe hydrogenase gene. However, the *Clostridium* positive control did not produce a 148 bp band. This implies that the ideal PCR conditions for those primers were not met.

Figure 4. PCR gels. The gel on the left consisted of 1% agarose and was used to visualize the amplification of the NiFe hydrogenase gene described by Wawer and Muyzer in 1995 with a 1k bp ladder (L). The gel on the right consisted of 2% agarose and was used to visualize the hydrogenase sequence described by Ozkan *et al.* in 2001 with a 50 bp ladder (L). H- *P. kaikoa*, HB- blank, L- ladder, DH- *Desulfovibrio*, CH- *Clostridium*, O1- *P. kaikoa* with annealing temp. of 48°C, O5- *P. kaikoa* with annealing temp. of 51.4°C, O7- *P. kaikoa* with annealing temp. of 55.4°C, DO- *Desulfovibrio*, CO- *Clostridium*.

Acknowledgements. Funding for this research was provided by the NASA URI Astrobiology Program, the Department of Defense ASSURE Program, and the National Science Foundation REU Programs. We would also like to thank Dr. David Rowley for allowing us to use his lab facilities for our molecular work, Dr. Bruno Soffientino, Dr. Jens Kallmeyer, Miranda Smith, and Stephanie Forschner for their guidance, Joseph Swearman for his help with the moving of the pressure reactor, and Lindsay Sullivan for help in imaging the cultures.

References

- Ozkan, M., Desai, S.G., Zhang, Z., Stevenson, D.M., Beane, J.M., White, E.A., Guerinot, M.L., and Lynd, L.R. (2001). Characterization of 13 newly isolated strains of anaerobic, cellulolytic, thermophilic bacteria. *Journal of Industrial Microbiology and Biotechnology* 27, 275–280.
- Schink, B., 1997. Energetics of syntrophic cooperation in methanogenic degradation. *Microbiol. Mol. Biol. Rev.* 61, 262–280.
- Soffientino, B., Spivack, A.J., Smith, D.C., Roggenstein, E.B., and D'Hondt, S. (2006). A versatile and sensitive tritium-based radioassay for measuring hydrogenase activity in aquatic sediments. *Journal of Microbiological Methods* 66:136-146.
- Wawer, C. and Muyzer, G. (1995). Genetic Diversity of *Desulfovibrio* spp. in environmental samples analyzed by denaturing gradient gel electrophoresis of [NiFe] hydrogenase gene fragments. *Applied and Environmental Microbiology* 61, 2203–2210.
- Yayanos, A.A. (1995). Microbiology to 10,500 meters in the deep sea. *Annu Rev Microbiol* 49, 777-805.

Dana M. Reznik and David C. Smith, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (dmreznik@owu.edu, dcsmith@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

Analysis of the historical nutrient input to Greenwich Bay, RI: Geochemical evidence for trends in eutrophication from sediment cores

Corin M. Schowalter¹, Danielle Cares, Clifford W. Heil, Mark Cantwell, John W. King

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. In August, 2003, the large fish-kill in Greenwich Bay, RI involving the death of approximately one million juvenile menhaden brought attention to patterns and repercussions of the eutrophication in the area (Mastrati 2003). In an effort to understand historical eutrophication, which threatens the local fishing industry and tourism, we conducted a sediment study of Greenwich Bay to determine the historical record of organic deposition. Sediment cores from Greenwich Bay and Greenwich Cove were analyzed to determine patterns in metal deposition (e.g. Pb, Cu, Cr), trends in nutrient loading (e.g., TN wt. %, TC wt. %, C/N), and fluxuation between nutrient sources (e.g., $\delta^{15}\text{N}$, $\delta^{13}\text{C}$). Trends all provide supporting evidence that anthropogenic activity is promoting algae production, leading to eutrophication. This data will assist in future management of the Greenwich Bay ecosystems.

1. Introduction

Tracking variation in anthropogenic nutrient input to Greenwich Bay is a key issue in the maintenance of Rhode Island's coastal fishing industry and tourism. Increasing nutrient availability may lead to eutrophication (Schramm, 1996). Eutrophication is a process of increased plant mass production in marine environments. Consequences include decreases in seagrass photosynthesis due to poor light penetration through blooms as well as decreases in dissolved oxygen concentrations due to the decomposition of high quantities of organic material for the system (Schramm 1996). Extreme cases may result in hypoxic or anoxic conditions leading to shellfish kills and even fish kills. Increased plant productivity increases the deposition of dead material on beaches, decreasing the aesthetic quality of the coastline. Assessing the past and present sources and input of nutrients to Greenwich Bay will enable future control over the occurrence of eutrophication as it will serve as a baseline prior to advancements in the proposed wastewater treatment facility upgrades and stormwater management that aim to restore dissolved oxygen concentrations to "fishable" standards by the year 2015 (Nutrient, 2004). Eutrophication in Greenwich Cove is a continual issue as hypoxic/anoxic events occur periodically (Deacutis).

2. Materials and Methods

Push cores were obtained from our sample locations on July 12, 2006 (Table 1). The Greenwich Bay coring site was located by GPS coordinates in close proximity to Jeffrey M. Corbin's sample location (Corbin 1989). Greenwich Cove coring site GB2006-3 was chosen for its proximity to the point source of effluent discharge by the East Greenwich Wastewater Treatment Facility (EGWTF) (Fig. 1). The EGWTF is responsible for the input of 29 of the 135-234 total metric tons of nitrogen entering Greenwich Bay annually (Granger, 2000). The Greenwich Bay coring site GB2006-1 provides data reflecting the background conditions for the whole

Figure 1. Map of Greenwich Bay.

Table 1. Description of core locations.

Core	Date	Lat. °N	Lon. °W	Depth (m)	Type	Length (cm)
GB2006-	7-12-06	41 40.550	71 25.402	4.57	Push	208.5
GB2006-	7-12-06	41 41.445	71 26.664	1.98	Push	175.0

Greenwich Bay region. Samples of 2 cm length were taken from the cores at 2 cm intervals for 1-19 cm below the interface, at 4 cm intervals for 25-81 cm below the interface, and at 8 cm intervals from 89 cm below the interface and downcore.

¹Louisiana State University, Baton Rouge, La

Cores were digitally imaged and logged with the GeoTek Multi Sensor Core Logger to obtain bulk density and magnetic susceptibility. The digital image was broken into three bands of color (red, green, and blue). The red component was then charted to display the location of a change in color upcore. Total Pb, Cu, and Cr concentrations were obtained using a PERKIN ELMER Zeeman AA Spectrometer 4100ZL. Nitrogen and Carbon isotope compositions are reported in per mil (‰) notation relative to Pee Dee Belemnite and urea standards respectively. Total $\delta^{15}\text{N}$, $\delta^{13}\text{C}$, percent total carbon and percent total nitrogen values were calculated from data provided by a VG Optima IRMS using VG Isotech software. The Greenwich Bay core was dated by comparing downcore metal profiles with radiometrically dated profiles (Figs. 2, 3) (Corbin 1989). A grain-size analysis was conducted with a Malvern Mastersizer 2000 to determine the percent composition of sand, silt, and clay components. Because there was no significant increase in the sand component above the depth of the background metal compositions for either core, it was unnecessary to normalize the metals data against the sand concentration.

3. Results

3.1. Metal Deposition

Metal deposition to Greenwich Bay reached a maximum during the 1930s before metal concentrations decrease upcore to the interface (Fig. 4a). Metal deposition to Greenwich Cove reached two maximums, one at approximately 65 cm depth and a more recent peak upcore at approximately 15 cm depth (Fig 4b). The concentrations of metal seen in Greenwich Cove samples compared to metal concentrations of Greenwich Bay samples indicate a greater metal input in Greenwich Cove.

3.2. Core Imaging and Logging

GeoTek core imaging and logging data reveal a recent change in the ecology of Greenwich Bay (Fig. 5a). Around 1906 at Greenwich Bay, red intensity exhibits a decrease and magnetic susceptibility exhibits an increase upcore. Concurrently, sample density decreases upcore. The Greenwich Cove core exhibits similar trends in decreased red intensity, increased magnetic susceptibility, and decreased density upcore from about 45 cm depth (Fig. 5b). The Greenwich Cove sediment color change is not so clearly defined as that from Greenwich Bay. This is likely due to the natural occurrence or higher nutrient deposits to Greenwich Cove, resulting in a less drastic transition upon the affects of anthropogenic disturbance. Bulk density and magnetic susceptibility decrease and increase respectively at the sediment color change for the Greenwich Cove core, providing supporting evidence of a new trend in nutrient input to the cove.

3.3. Carbon and Nitrogen Input

3.3.1. C/N. C/N values showed no major change in Greenwich Bay and values indicate that marine and terrestrial sources contribute similar quantities of organic matter (Fig. 6). C/N values indicate a transition to

Figure 2. Core samples from a previous M.S. research project by Jeffrey M. Corbin in 1989 have been dated by radiometric analysis. Radiometrically dated downcore chromium profile from Greenwich Bay (left) is correlated to metal downcore profiles from Greenwich Bay GB2006-1 (Corbin, 1989). Year to depth ratios determined by the five reference points indicated by grey lines were averaged to calculate an average correlation of 2.72 ± 1.13 yr/cm for the Greenwich Bay core.

Figure 3. Depth versus age model. The R^2 value near 1 indicates that the linear relationship is a good fit for the data. Data points represent the five reference points used to develop a dating scale for Greenwich Bay core GB2006-1 (Fig. 2).

increasing quantities of organic sediments from terrestrial sources in Greenwich Cove beginning at 15 cm depth (Fig. 7). The total nitrogen mass composition component increased upcore from approximately from 0.15% to 0.40% since the 1400s to present in Greenwich Bay and from approximately 0.3% to 0.7% in Greenwich Cove. The total carbon mass composition component increased approximately from approximately 1.5% to 3.5 % in Greenwich Bay and approximately from 3% to 8% in Greenwich Cove.

3.3.2. $\delta^{15}\text{N}$. Historical $\delta^{15}\text{N}$ values display an increase upcore by approximately 0.75 per mil in Greenwich Bay from about 7 to 7.75‰, indicating a trend of increasing algal component in bay sediments over terrestrial plant

Figure 4. a. Metal deposition in Greenwich Bay from GB2006-1. b. Metal Deposition in Greenwich Cove from GB2006-3.

material. A history of greater algal than terrestrial plant component in Greenwich Cove sediments in which $\delta^{15}\text{N}$ values average about 7.75‰ is shown in the Greenwich Cove historical $\delta^{15}\text{N}$ record. Nitrogen isotope ratios may differentiate between nitrogen sources to plant components of marine sediments. Algae obtain most of their nitrogen from dissolved NO_3^- , leading to ($+7\text{‰} < \delta^{15}\text{N} < +10\text{‰}$) (Meyers 2001). Terrestrial plants obtain their nitrogen from N_2 , resulting in ($\delta^{15}\text{N} = 0\text{‰}$) (Meyers, 2001).

3.3.3. $\delta^{13}\text{C}$ Increasing upcore nutrient input around 1938 at Greenwich Bay and 25 cm depth at Greenwich Cove indicates phytoplankton to be the main carbon source. The trend shared by both Greenwich Bay and Greenwich Cove cores indicates fluctuation between phytoplankton and terrestrial or lake bottom plants in contribution to the greatest percent of carbon to the sediment. Carbon isotope ratios reflect historical nutrient availability and therefore marine productivity (Meyers 2001). Increasing and decreasing $\delta^{13}\text{C}$ values indicate increased and decreased productivity respectively (Meyers 2001). The $\delta^{13}\text{C}$ values also vary with respect to the source. Organic sediments produced from phytoplankton lead to ($-33\text{‰} < \delta^{13}\text{C} < -22\text{‰}$) while those produced from terrestrial or lake bottom plants lead to ($-22\text{‰} < \delta^{13}\text{C} < -8\text{‰}$) (Meyers 2001). Increased nutrient input such as nitrates to marine environments increases plant productivity and biological

Figure 5. GeoTek Multi Sensor Core Logger data for bulk density, magnetic susceptibility, and red intensity display a trend of increasing organic material in recent years for a. Greenwich Bay and b. Greenwich Cove. A sediment color change, identified by the steep decrease in red intensity at approximately 0.4 m depth, is a result of the presence of increased levels of organic carbon (Berner, 1981). The sediment color change located at approximately 0.45 m depth is less defined by the red intensity plot for Greenwich Cove is due to a historical trend of greater organic input to Greenwich Cove.

processes can afford to favor ^{12}C , producing less negative $\delta^{13}\text{C}$ values in the plant material (Meyers 2001). Average Greenwich Bay $\delta^{13}\text{C}$ values display a trend of decreasing negativity upcore until 1843 to about -19‰, increase negativity upcore until 1938 to about -20.75‰, and then decrease negativity upcore again to reach a current value of about -19.5‰. Average Greenwich Cove $\delta^{13}\text{C}$ values display a similar pattern, growing less negative upcore until 65 cm depth to about -19.25‰, increasing negativity upcore until 25 cm depth to about -22‰, and then decreasing negativity to reach a current value of about -20.5‰.

4. Discussion of Eutrophication

4.1. Physical Proxies

Core imaging and logging data indicate a drastic increase in organic matter to Greenwich Bay around 1906. Bulk density decrease may be attributed to the low density of organic material. Magnetic susceptibility increases at this same time, reflecting an increase of magnetic deposits, characteristic of industrialization (Thompson 1986). The Greenwich Cove sediment color change occurs at approximately 45 cm downcore. At this depth, red intensity decreases, similarly reflecting a trend in increasing levels of reduced iron. Increased concentrations of reduced iron serves as a proxy for historical eutrophication. Sediments containing high concentrations of organic carbon provide anaerobic conditions due to decomposition by aerobic bacteria, which consume O_2 (Bennington 1999). In marine environments, reduced iron (Fe^{2+}), soluble under anoxic conditions, is exposed to sulfide to produce a disulfide, pyrite (FeS_2), which is insoluble in water (Berner 1981). Sediment coloration reflects the oxidation state of iron. Oxidized iron is red while reduced forms of iron such as pyrite are black (Lynn 2000). At approximately 1906, the Greenwich Bay core exhibits a sharp red intensity decreases, suggesting an increase in reduced iron content.

4.2. Chemical Proxies

The greater concentration of metal deposition to Greenwich Cove over Greenwich Bay may be attributed to the site's proximity to the EGWWTF, which is also responsible for large quantities of nutrients input compared to other nutrient sources for Greenwich Bay. Sewerline pipes may be the source of much of the metal. Higher concentrations of copper in Greenwich Cove, which are increasing, may also result from marine antifoulant paints, composed of 20-76% copper, that coat the hulls of boats docked at the adjacent marina (Schiff 2003). For a boat, about 95% of the copper mass is passively leached into the water as opposed to during hull cleaning (Schiff 2003). Copper is highly toxic to marine organisms. The Greenwich Cove metal concentration maximum at 65 cm depth is also visible at lower concentrations in Apponaug Cove cores around 1900 suggesting that the metal entered the bay at Greenwich Cove, then dispersed (Corbin 1989). This quantity of metal likely entered Greenwich Cove following the beginning of American industrialization (1865-1889), but prior to 1900 although the source is unknown (Smithsonian).

4.2. Anthropogenic Sources

Carbon and Nitrogen data show a trend toward an increase in terrestrial material entering Greenwich Bay and Greenwich Cove. Terrestrial sources likely stem from human disturbances including erosion and agricultural runoff and sewage inputs from wastewater treatment facilities.

5. Conclusion

Human activity threatens the Greenwich Bay ecological sustainability. Environmental laws regulating metal input have been effective in the Greenwich Bay region as concentrations continue to decrease upcore. Terrestrial nutrient input is not decreasing, however and the increase in primary production in the system fluctuates annually, threatening marine life most commonly during summer months (Schramm 1996).

Acknowledgments. This project has been funded in part by the Department of Defense ASSURE and National Science Foundation REU Programs.

References

- Bennington, J. B. "Geol 135 Sedimentation: Diagenesis." http://people.hofstra.edu/faculty/j_b_bennington/135notes/diagenesis.html. 1999.
- Corbin, J., Recent and historical accumulation of trace metal contaminants in Narragansett Bay sediments. M.S. Thesis, University of Rhode Island, Kingston, RI, 295 pp, 1989.
- Deacutis, C., Diehl, D., Valkirs, A.; "Nutrient Impacts and Signs of Problems in Narragansett Bay" Rhode Island Department of Environmental Management.
- Granger, S.; Brush, M.; Buckley, B.; Traber, M.; Richardson, M.; and Nixon, S. W.; An assessment of eutrophication in Greenwich Bay. in M. Schwartz, ed. *Restoring Water Quality in Greenwich Bay: A Whitepaper Series*. Rhode Island Sea Grant, Narragansett, RI. 2000.
- King, J. W. et al. Anthropogenic Eutrophication of Narragansett Bay: Evidence of Dated Sediment Cores, *Ecosystem-based Management: A Case Study of Narragansett Bay*. In Review.
- Lynn, W.C. and Pearson, M.J., May "The Color of Soil" The Science Teacher. 2000.
- Mastrati, G. and Powell, S.; "Rhode Island Department of Environmental Management Annual Report". 49pp, 2003.
- Meyers, P. A., and Teranes, J. L.; *Sediment organic matter*, IN W. M. Last and J. P. Smol (ed), *Tracking Environmental Change Using Lake Sediments* vol. 2: Physical and Geochemical Methods, Kluwer Academic Publishers, Dordrecht, The Netherlands, p. 239-269, 2001.
- Nutrient and Bacteria Pollution Panel, Governor's Narragansett Bay and Watershed Planning Commission; 2004. "Initial Report".
- Schiff, K. C.; et. al.; Southern California Coastal Water Research Project "Copper emissions from antifouling paint on recreational vessels". 2003.
- Schramm, W. and Nienhuis, P. H. eds.; *Marine Benthic Vegetation: Recent Changes and the Effects of Eutrophication*. New York: Springer. 470pp, 1996.
- Smithsonian Institution. "American History Timeline" <http://www.si.edu/RESOURCE/FAQ/nmah/timeline.htm>.
- Thompson, R. and Oldfield, F.; *Environmental Magnetism*. London: Allen & Unwin. 227pp, 1986.

C. M. Schowalter and J. W. King, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (cschow1@lsu.edu, jking@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program

Variability in coastal groundwater radium activity: Implications for radium-derived residence time and groundwater flux

Joseph W. Swearman,¹ S. Bradley Moran, and Roger P. Kelly

Graduate School of Oceanography, University of Rhode Island, Narragansett, Rhode Island

Abstract. Short-lived radium isotopes ^{223}Ra ($t_{1/2} = 11.4$ d) and ^{224}Ra ($t_{1/2} = 3.66$ d) as well as longer-lived ^{226}Ra ($t_{1/2} = 1600$ yr) and ^{228}Ra ($t_{1/2} = 5.75$ yr) have been increasingly used as geochemical tracers to constrain water residence time and submarine groundwater discharge (SGD) in coastal waters. An important question is: to what extent does variability in pore-water radium influence estimates of water mass residence time and SGD? To address this question, the distribution of groundwater radium was determined at a shoreline site and along a transect through subaqueous sediments in a temperate coastal embayment; Ninigret Pond, RI. Radium activities were found to vary significantly with depth (~ 1 –40 times) and distance from the shoreline (~ 1 –30 times). These data were combined with results from previous studies to calculate residence times that varied from <1 –11 d and SGD from ~ 4 –45 $\text{L}^{-1} \text{m}^{-2} \text{d}^{-1}$. The implication is that variability in groundwater radium is important when using these tracers to estimate water mass age and SGD in coastal ecosystems.

1. Introduction

Submarine groundwater discharge plays an important role in the transport of nutrients and chemicals into coastal waters (Johannes 1980; Valiela et al. 1990; Burnett et al. 2001). Anthropogenic sources are often major contributors of nutrients to coastal aquifers, with elevated nutrient flux potentially affecting a range of ecological processes (Valiela et al. 1990). The residence time of water within a coastal embayment has significant implications for water quality, including denitrification and nutrient transport (Nixon 1996; Dettmann 2001). Accurate quantification of water residence time and groundwater discharge in coastal embayments is necessary for developing an improved understanding of coastal ecological processes.

The estimation of submarine groundwater discharge into coastal waters is an inherently difficult process, due primarily to the diffuse and variable nature of groundwater flow. Short-lived radium isotopes, ^{223}Ra ($t_{1/2} = 11.4$ d) and ^{224}Ra ($t_{1/2} = 3.66$ d), as well as longer-lived ^{226}Ra ($t_{1/2} = 1600$ yr) and ^{228}Ra ($t_{1/2} = 5.75$ yr) are naturally occurring geochemical tracers suitable for calculating water residence time and spatially and temporally variable submarine groundwater discharge (Scott 1998; Charette et al. 2001; Kelly and Moran 2002; Abraham et al. 2003; Charette et al. 2003; Hougham 2006). Radium-tracer techniques used to study groundwater discharge largely remain independent of problems related to aquifer heterogeneity when using methods such as seep meters and hydrologic models (Burnett et al. 2002). Submarine groundwater discharge can be estimated by balancing the input of elevated ^{226}Ra activity from a coastal aquifer with the subsequent tidal removal of ^{226}Ra from the embayment. The 3.66 d to 1600 yr range in isotopic half-lives also enables examination of water circulation on a wide range of time-scales, with ^{223}Ra and ^{224}Ra providing insight on water residence on the scale of a few days to several weeks (Hougham 2006).

Determination of representative groundwater Ra activities has been recognized as a source of uncertainty in calculating submarine groundwater discharge, though many

Ra-based studies of SGD provide only limited information on the variability in groundwater radium distributions. This study focuses on the variability in the distribution of ^{223}Ra , ^{224}Ra , ^{226}Ra , ^{228}Ra within subaqueous sediment pore-water of a coastal embayment. The implications of these data are discussed with regard to estimation of coastal submarine groundwater flux and water residence time.

2. Methods

2.1. Study Area

Ninigret Pond is a shallow lagoon located along the coast of southern Rhode Island (Fig 1). This embayment has an average depth of 1.2 m, a surface area of 6.45 km^2 , and a watershed area of 28.48 km^2 (RIGIS 2001). A permanent breachway allows an average tidal range of 0.14 m with Block Island Sound, and otherwise remains enclosed by a barrier beach (Lee 1980; Lee and Olsen 1985).

Two groundwater sample sets were collected in this study. One set included two shoreline sites, A and B, separated by 5 m and located along the northern shoreline of Ninigret Pond. The second sample set comprised five sites extending along a North-South transect perpendicular

Figure 1. Map of Ninigret Pond, RI.

¹Now at The Pennsylvania State University

from the landward shoreline of Ninigret Pond. Each site (*C*, *D*, *E*, *F*, *G*) is separated by ~200 m.

2.2. Sample collection and analysis

In July 2006, sediment pore-water for Ra isotopic analysis was collected using a drivepoint sampler. This stainless steel tube with slotted inlet was connected to a Cole-Parmer Masterflex E/S peristaltic pump. Samples were recovered at 10 cm increments to a maximum sediment depth of 50 cm. An adjustable stopper on the shaft of the drivepoint sampler was utilized to ensure proper sample depth. Pore-water (0.2–5.6 L) was filtered through a 47 mm Whatman GF/B filter (1 μ m nominal pore size) to remove suspended solids. During sampling, filters were replaced as necessary to maintain flow rates (≤ 1 L/min). The pore-water was then passed through MnO₂-coated acrylic fiber cartridges (≤ 1 L/min), which quantitatively removed radium from pore-water (Moore 1973). Radium-extracted pore-water samples were recovered for subsequent volume measurement. Pore-water samples independent of radium extraction were collected in glass bottles for salinity analysis.

MnO₂-coated acrylic fiber was partially dried with compressed air and analyzed three times for ²²³Ra and ²²⁴Ra activity using a Ra delayed-coincidence counter (Moore and Arnold 1996). Fiber was ashed at 500°C for 16 hours, packed into counting vials, and capped with epoxy to prevent ²²²Ra loss (Scott 1998; Charette 2001; Kelly 2001). Samples were allowed 14 d for ²²⁶Ra to reach secular equilibrium with its daughter ²¹⁴Pb before analysis of ²²⁶Ra (²¹⁴Pb peak at 351 keV) and ²²⁸Ra (²²⁸Ac peak at 911 keV) with a Canberra pure germanium well-type gamma spectrometer (Model GCW 3023). Salinity samples were analyzed using a Guildline Autosol 8400 salinometer.

3. Results

3.1. Shoreline sites

Radium activity and salinity for shoreline sampling sites are presented in Table 1. Salinity increases with depth at site *A* whereas site *B* has the inverse relationship. Site *A* and *B* both exhibit increasing activity with depth for all four isotopes. ²²⁶Ra activity varied significantly with depth at individual sites as well as between sites (Fig 2). ²²⁶Ra activity ranged from 1.5–6.1 dpm L⁻¹ at site *A* and from 1.1–13.4 dpm L⁻¹ at site *B*. At 10 cm depth, the ²²⁶Ra activity for sites *A* and *B* were observed to be very similar (1.5 and 1.1 dpm L⁻¹), but activity differences between sites increased with depth to 50 cm where activities differed by over a factor of two (6.1 and 13.4 dpm L⁻¹).

3.2. Transect

Transect ²²³Ra and ²²⁴Ra activity and salinity data are found in Table 2. ²²³Ra increased with depth at site *C* and *E*, but did not vary significantly with depth at the other transect points. On the transect overall, ²²³Ra and ²²⁴Ra increased with increasing depth and distance from the northern, landward shoreline (Fig. 3). ²²⁴Ra activity increased with depth at site *E* and did not vary significantly elsewhere on the transect. The depth profiles of sites closest to the northern shoreline, *C* and *E*, exhibited larger ranges of ²²³Ra activity (5.6 dpm L⁻¹ and 12 dpm L⁻¹) in relation to the sites closest to the barrier beach, *F* and *G*. Inadequate pore-water collection prevented radium and salinity analysis at site *D*.

4. Discussion

4.1. Variability in groundwater radium activity

Radium activity did not display an apparent relationship

Table 1. Shoreline sampling site measurements. ²²³Ra and ²²⁴Ra activities reported as average $\pm$ standard deviation of triplicate analyses.

Site	Depth (cm)	²²³ Ra (dpm L ⁻¹)	²²⁴ Ra (dpm L ⁻¹)	²²⁶ Ra (dpm L ⁻¹)	²²⁸ Ra (dpm L ⁻¹)	Salinity (psu)
A	10	7.6 $\pm$ 2.7	30.5 $\pm$ 4.2	1.5 $\pm$ 0.1	11.8 $\pm$ 0.3	28.20
	20	21.8 $\pm$ 8.9	50.3 $\pm$ 5.0	2.3 $\pm$ 0.1	31.0 $\pm$ 0.6	28.31
	30	31.2 $\pm$ 3.5	64.0 $\pm$ 6.2	3.3 $\pm$ 0.2	53.1 $\pm$ 0.8	28.43
	40	32.1 $\pm$ 5.8	84.4 $\pm$ 1.7	4.6 $\pm$ 0.1	56.2 $\pm$ 0.5	28.50
	50	63.7 $\pm$ 3.9	69.5 $\pm$ 11.4	6.1 $\pm$ 0.2	75.5 $\pm$ 1.0	28.61
Average		31.3 $\pm$ 18.5	59.8 $\pm$ 18.3	3.6 $\pm$ 1.8	45.5 $\pm$ 24.6	28.4 $\pm$ 0.16
B	10	2.4 $\pm$ 0.7	14.3 $\pm$ 0.1	1.1 $\pm$ 0.1	6.1 $\pm$ 0.3	27.19
	20	7.2 $\pm$ 1.7	28.7 $\pm$ 2.5	1.2 $\pm$ 0.1	9.1 $\pm$ 0.3	26.25
	30	6.8 $\pm$ 1.3	28.3 $\pm$ 4.4	1.9 $\pm$ 0.1	13.4 $\pm$ 0.4	25.31
	40	11.4 $\pm$ 1.3	30.4 $\pm$ 2.6	3.2 $\pm$ 0.1	23.2 $\pm$ 0.3	24.24
	50	13.3 $\pm$ 1.7	68.0 $\pm$ 6.4	13.4 $\pm$ 0.8	58.9 $\pm$ 2.5	26.90
Average		8.2 $\pm$ 3.8	34.0 $\pm$ 18.0	4.2 $\pm$ 5.2	22.1 $\pm$ 21.5	26.0 $\pm$ 1.21
High		63.7 $\pm$ 3.9	84.4 $\pm$ 1.7	13.4 $\pm$ 0.8	75.5 $\pm$ 1.0	28.61
Low		2.4 $\pm$ 0.7	14.3 $\pm$ 0.1	1.1 $\pm$ 0.1	6.1 $\pm$ 0.3	24.24
Average A-B		19.8 $\pm$ 18.6	46.8 $\pm$ 23.4	3.9 $\pm$ 3.7	33.8 $\pm$ 25.0	27.19 $\pm$ 1.52

Figure 2. Depth versus ^{226}Ra activity at shoreline sites *A* and *B*.

with salinity for ^{223}Ra , ^{224}Ra , ^{226}Ra , or ^{228}Ra (Fig 4). All radium isotopes demonstrated variability with depth and site location. ^{226}Ra varied with depth by a factor of 12 at site *A*, and, though located only 5 m apart, Site *A* and *B* ^{226}Ra activities differed by up to a factor of two at the same depth. ^{224}Ra activity exhibited a forty-fold increase from 10-50 cm depth at site *E* and varied by 30 times between site *E* and *F*.

Differences in ground and pondwater mixing interactions within the subaqueous sediments may result in the observed variability in pore-water radium activities. At sites *A-E*, radium activities increase with depth and relative proximity to the radium enriched aquifer. Sites *F* and *G* display little variation with depth and have activities similar to the pond surface water. At these two sites, groundwater and pondwater may be in equilibrium, or the sediments may not contribute radium to the pond. Also, the interface between the aquifer and pondwater may be deeper than sampling conducted in this study. Also, sediment

Table 2. Transect site measurements. Ra data reported as average $\pm$ standard deviation of triplicate analyses. N/A designates insufficient pore-water volume for analysis.

Site	Depth (cm)	^{223}Ra (dpm L ⁻¹)	^{224}Ra (dpm L ⁻¹)	Salinity (psu)
C	10	N/A	N/A	N/A
	20	10.0 $\pm$ 2.9	87.4 $\pm$ 9.7	N/A
	30	N/A	N/A	N/A
	40	13.5 $\pm$ 5.8	80.1 $\pm$ 7.4	27.17
	50	15.6 $\pm$ 5.6	80.3 $\pm$ 7.0	26.72
Average		13.0 $\pm$ 2.8	82.6 $\pm$ 4.1	26.95 $\pm$ 0.32
E	10	0.6 $\pm$ 0.4	3.7 $\pm$ 0.3	28.02
	20	1.4 $\pm$ 2.2	24.2 $\pm$ 3.8	N/A
	30	7.4 $\pm$ 9.6	34.0 $\pm$ 5.4	27.50
	40	7.6 $\pm$ 3.5	94.8 $\pm$ 19.4	N/A
	50	12.6 $\pm$ 5.2	151.4 $\pm$ 27.1	N/A
Average		5.9 $\pm$ 5.0	61.6 $\pm$ 60.6	27.76 $\pm$ 0.36
F	10	1.9 $\pm$ 1.2	12.2 $\pm$ 2.3	27.46
	20	0.2 $\pm$ 0.1	1.8 $\pm$ 0.5	27.75
	30	1.6 $\pm$ 1.6	3.5 $\pm$ 4.2	N/A
	40	N/A	N/A	N/A
	50	1.9 $\pm$ 1.1	4.8 $\pm$ 1.6	28.00
Average		1.4 $\pm$ 0.8	5.6 $\pm$ 4.6	27.73 $\pm$ 0.29
G	10	1.6 $\pm$ 1.4	6.7 $\pm$ 1.2	N/A
	20	1.8 $\pm$ 0.9	7.8 $\pm$ 0.9	26.72
	30	1.6 $\pm$ 0.7	7.8 $\pm$ 0.3	26.63
	40	1.0 $\pm$ 0.2	10.3 $\pm$ 1.6	27.31
	50	1.3 $\pm$ 0.7	8.1 $\pm$ 1.7	27.54
Average		1.5 $\pm$ 0.3	8.2 $\pm$ 1.3	27.05 $\pm$ 0.45
Average C-G		4.8 $\pm$ 5.2	36.4 $\pm$ 44.8	27.34 $\pm$ 0.49

Figure 3. Depth versus ^{224}Ra activity along the transect sites *C* (far left) through *G* (far right).

Figure 4. ^{224}Ra activity versus salinity for sites A-G.

composition may influence these mixing interactions. On the transect, sites B and C are located in a muddy, shallow lagoon bottom, whereas sites E and F consist of more permeable sandy overwash sediments.

4.2. Calculation of water residence time

Using ^{223}Ra and ^{224}Ra , residence time may be estimated by first determining the excess radium activity relative to the ocean end-member (Block Island Sound for this study) using (Krest et al. 2000),

$$Ra_m = f(Ra_o) \quad (1)$$

where Ra_m is modeled ^{223}Ra or ^{224}Ra activity of pond, f is the fraction of ocean end-member water composing the sample, and Ra_o is the activity of the ocean end-member temporally corresponding to the embayment water sampling. The ocean end-member fraction, f , is determined by

$$f = \frac{S_s}{S_o} \quad (2)$$

where S_s represents the embayment sample salinity and S_o represents the ocean-end member salinity. Excess radium within embayment water sample is defined as (Hougham 2006),

$$\overline{Ra_{ex}} = Ra - Ra_m \quad (3)$$

where Ra is ^{223}Ra or ^{224}Ra embayment water activity, and $\overline{Ra_{ex}}$ is the excess activity of the corresponding isotope. Residence time, t (d), can be calculated using the equation (Hougham 2006),

$$t = \frac{\ln\left[\frac{^{224}\text{Ra}}{^{223}\text{Ra}}\right]_{ex} - \ln\left[\frac{^{224}\text{Ra}}{^{223}\text{Ra}}\right]_{init}}{\lambda_{224} - \lambda_{223}} \quad (3)$$

where $\left[\frac{^{224}\text{Ra}}{^{223}\text{Ra}}\right]_{ex}$ is the surface water excess activity ratio, $\left[\frac{^{224}\text{Ra}}{^{223}\text{Ra}}\right]_{init}$ is the pore water activity ratio, and λ_{223} and λ_{224} represent the respective decay constants for

Table 3. Radium-derived water residence time and groundwater fluxes in Ninigret Pond.

	This Study			Hougham 2006
	Low	High	Average	
Water residence time (d)	<1	11±4	4±3	8±5
Groundwater flux (L m ⁻¹ d ⁻¹)	4±2	45±27	13±14	130±110

^{223}Ra (0.0606 d⁻¹) and ^{224}Ra (0.189 d⁻¹). Use of short-lived radium isotopes for residence time estimation necessitates several assumptions (Moore 2000): that the pore-water activity ratio, $\left[\frac{^{224}\text{Ra}}{^{223}\text{Ra}}\right]_{init}$, is spatially and temporally constant, mixing and decay are the only radium addition or subtraction after introduction into the embayment, and the ocean end-member contains negligible radium.

Pore-water activity ratios on the transect ranged from a high of 17.12 to a low of 2.17 with a mean of 7.22 ± 3.97 . Calculation of water residence time with these values results in a range of <1–11 d, with an average of 4 ± 3 d. This average residence time differs by a factor of two from a previous study that estimated an 8 ± 5 d average residence time in August 2002 (Table 3; Hougham 2006). Because of the more spatially extensive pore-water sampling conducted in the present study, these results may be considered to provide a more representative average pore-water activity and accurate residence time estimate.

4.3. Estimation of submarine groundwater discharge

Groundwater flux estimation using ^{226}Ra or ^{228}Ra mass balance first requires calculation of excess surface water radium activity, $\overline{Ra_{ex}}$ (Eq 3). Integrated flux of ^{226}Ra or ^{228}Ra from groundwater into the embayment surface water, J_{Ra} , can be calculated using,

$$J_{Ra} = \frac{\overline{Ra_{ex}} \times V}{\tau \times A} \quad (5)$$

where $\overline{Ra_{ex}}$ is average excess radium, V is the embayment's exchangeable volume, τ is the residence time, and A is the embayment area. Groundwater flux is estimated using (Hougham 2006),

$$J_{GW} = \frac{J_{Ra}}{\left[\frac{Ra_{pw}}{Ra_{ex}}\right]} \quad (6)$$

where $\left[\frac{Ra_{pw}}{Ra_{ex}}\right]$ is the average ^{226}Ra or ^{228}Ra pore-water activity and J_{GW} is the groundwater flux, or submarine groundwater discharge. This calculation assumes that pore-water ^{226}Ra and ^{228}Ra activities are spatially and temporally constant. Integrated flux values, J_{Ra} , obtained in August 2002 by a previous study of Ninigret Pond were used in ^{226}Ra calculation of groundwater flux for this study (Hougham 2006).

The high, low, and average ^{226}Ra pore-water activities (13.4, 1.1, 3.9 dpm L⁻¹ respectively), from sites A and B were used in calculation of groundwater flux. This produced a 4–45 L m⁻² d⁻¹ range for submarine groundwater discharge, with an average of 13 L m⁻² d⁻¹. Surface and

pore-water ^{226}Ra activity data from a previous Ninigret Pond study resulted in calculation of an average August 2002 groundwater flux of $130 \text{ L m}^{-2} \text{ d}^{-1}$, an order of magnitude higher than in this study (Hougham 2006). While annual variations in aquifer recharge can influence the magnitude of submarine groundwater discharge, the significant groundwater flux estimation disparity between studies suggests that sampling strategy may significantly influence radium-derived groundwater flux estimates.

5. Conclusion

Significant spatial variability in pore-water ^{223}Ra , ^{224}Ra , ^{226}Ra , and ^{228}Ra activities was observed within the sub-aqueous sediments of Ninigret Pond, RI. Radium activities varied both with depth and location within the embayment. This variability substantially influences the radium-derived water residence time and groundwater flux results. Estimates of submarine groundwater discharge differed by 12 times when using two pore-water samples from a single sampling site. Calculation of residence time using ^{223}Ra and ^{224}Ra activity ratios resulted in estimates that varied by over a factor of 11. By comparison, the groundwater flux calculated from a previous study using radium isotopes in Ninigret Pond was an order of magnitude higher than the average value from this study, and the residence time estimate varied by a factor of two. The observed range in groundwater flux and residence time estimates due to coastal groundwater radium variability highlights the importance of determining representative groundwater activity for such calculations.

Acknowledgments. We thank the Department of Defense ASSURE program and the National Science Foundation's REU program for funding. The efforts of many people contributed to this project, and I would like to especially thank Haley Brew for her selfless laboratory instruction and assistance, Graham Lau and Dana Reznik in sample collection and preparation, all of my fellow SURFO participants for their invaluable support, and most of all, Rob Pockalny for his tireless mentorship and unwavering patience.

References

- Abraham, D. M., M. A. Charette, M. C. Allen, A. Rago and K. D. Kroeger, Radiochemical estimates of submarine groundwater discharge to Waquoit Bay, Massachusetts, *Biological Bulletin*, 205, 246-247, 2003.
- Burnett, W. C., M. Taniguchi, and J. Oberdorfer, Measurement and significance of the direct discharge of groundwater into the coastal zone, *J. Sea Res.*, 46, 109-116, 2001.
- Burnett, W. C., J. P. Chanton, J. L. Christoff, E. Kontar, S. L. Krupa, M. Lambert, W. S. Moore, D. O'Rourke, R. J. Paulsen, C. F. Smith, L. Smith and M. Taniguchi, Assessing methodologies for measuring groundwater discharge to the ocean, *Eos Trans. AGU*, 83, 117, 122-123, 2002.
- Charette, M. A., K. O. Buesseler and J. E. Andrews, Utility of radium isotopes for evaluating the input and transport of groundwater-derived nitrogen to a Cape Cod estuary, *Limnology and Oceanography*, 46, 465-470, 2001.
- Charette, M. A., R. Splivallo, C. Herbold, M. S. Bollinger and W. S. Moore, Salt marsh submarine groundwater discharge as traced by radium isotopes, *Marine Chemistry*, 84, 113-121, 2003.
- Dettmann, E. H., Effect of water residence time on annual export and denitrification of nitrogen in estuaries: a model analysis, *Estuaries*, 24, 481-490, 2001.
- Hougham, A. L., Radium isotopes as tracers of water mass age and groundwater flux to shallow coastal salt ponds, M.S. thesis, University of Rhode Island, 2006.
- Johannes, R. E., Ecological Significance of the Submarine Discharge of Groundwater, *Mar. Eco. Prog. Ser.*, 3, 365-373, 1980.
- Kelly, R. P., Radium isotopes as tracers of seasonally variable groundwater input and mixing within the Pettaquamscutt River Estuary, M.S. thesis, University of Rhode Island, 2001.
- Kelly, R. P. and S. B. Moran, Seasonal changes in groundwater input to a well-mixed estuary estimated using radium isotopes and implications for coastal nutrient budgets, *Limnology and Oceanography*, 47, 1796-1807, 2002.
- Krest, J. M., W. S. Moore, L. R. Gardner and J. T. Morris, Marsh nutrient export supplied by groundwater discharge: Evidence from radium measurements, *Global Biogeochemical Cycles*, 14, 167-176, 2000.
- Lee, V., An elusive compromise: Rhode Island coastal ponds and their people, Coastal Resources Management Council, URI Technical Marine Technical Report, 73, 1980.
- Lee, V. and S. Olsen, Eutrophication and management initiatives for the control of nutrient inputs to Rhode Island coastal lagoons, *Estuaries*, 8, 191-202, 1985.
- Moore, W. S. and D. F. Reid, Extraction of radium from natural waters using manganese-impregnated acrylic fibers, *Journal of Geophysical Research*, 78, 8880-8886, 1973.
- Moore, W. S. and R. Arnold, Measurement of ^{223}Ra and ^{224}Ra in coastal waters using a delayed coincidence counter, *Journal of Geophysical Research*, 101, 1321-1329, 1996.
- Moore, W. S., Ages of continental shelf waters determined from ^{223}Ra and ^{224}Ra , *Journal of Geophysical Research*, 105, 22117-22122, 2000.
- Nixon, S. W., J. W. Ammerman, L. P. Atkinson, V. M. Berounsky, G. Billen, W. C. Boicourt, W. R. Boynton, T. M. Church, D. M. Dittoro, R. Elmgren, J. H. Garber, A. E. Giblin, R. A. Jahnke, N. J. P. Owens, M. E. Q. Pilson and S. P. Seitzinger, The fate of nitrogen and phosphorous at the land-sea margin of the North Atlantic Ocean, *Biogeochemistry*, 35, 141-180, 1996.
- Rama and W. S. Moore, Using the radium quartet for evaluating groundwater input and water exchange in salt marshes, *Geochimica et Cosmochimica Acta*, 60, 4645-4652, 1996.
- Rhode Island Geographic Information System, <http://www.edc.uri.edu/rigis>, 2001.
- Scott, M. K., Radium-226 as a tracer of ground water input to the coastal waters of southern Rhode Island, M.S. thesis, University of Rhode Island, 1998.
- Valiela, I., J. Costa, K. Foreman, J. M. Teal, B. Howes, and D. Aubrey, Transport of groundwater-borne nutrients from watersheds and their effects on coastal waters, *Biogeochemistry*, 10, 177-197, 1990.

J. W. Swearman, S. B. Moran, and R. P. Kelly, Graduate School of Oceanography, University of Rhode Island, Narragansett, RI 02882. (jus159@psu.edu, moran@gso.uri.edu, rokelly@gso.uri.edu)

Copyright 2006 by the Graduate School of Oceanography/University of Rhode Island, SURFO program