2018

DEVELOPING CONSEQUENCE THRESHOLDS FOR STORM MODELS: CASE STUDY OF WESTERLY RHODE ISLAND

Robert Witkop
University of Rhode Island, robert_witkop@my.uri.edu

Follow this and additional works at: <https://digitalcommons.uri.edu/theses>

Recommended Citation

Witkop, Robert, "DEVELOPING CONSEQUENCE THRESHOLDS FOR STORM MODELS: CASE STUDY OF WESTERLY RHODE ISLAND" (2018). *Open Access Master's Theses*. Paper 1316.
<https://digitalcommons.uri.edu/theses/1316>

This Thesis is brought to you for free and open access by DigitalCommons@URI. It has been accepted for inclusion in Open Access Master's Theses by an authorized administrator of DigitalCommons@URI. For more information, please contact digitalcommons-group@uri.edu.

DEVELOPING CONSEQUENCE THRESHOLDS FOR STORM MODELS: CASE
STUDY OF WESTERLY RHODE ISLAND

BY

ROBERT WITKOP

A MASTER'S THESIS SUBMITTED IN PARTIAL FULFILLMENT OF THE

REQUIREMENTS FOR THE DEGREE OF

MASTER OF ARTS

IN

MARINE AFFAIRS

UNIVERSITY OF RHODE ISLAND

2018

MASTER OF ARTS THESIS

OF

ROBERT WITKOP

APPROVED:

Thesis Committee:

Major Professor Austin Becker

Robert Thompson

Christopher Baxter

Nasser H. Zawia
DEAN OF THE GRADUATE SCHOOL

UNIVERSITY OF RHODE ISLAND
2018

ABSTRACT

Emergency managers face challenges in understanding and communicating potential hurricane hazards. Preparedness typically emphasizes the last event encountered, the potential implications of future hazards may thus be underestimated. Risk assessment models (e.g., basic HAZUS) that emphasize accumulated damages in economic terms do not provide actionable data regarding specific local concerns, such as access by emergency vehicles and potential communications disruptions. Qualitative methods conventionally used to identify these concerns, however, lack the specificity necessary to incorporate the managers' knowledge into hazard models (e.g., highly exact geographic location of the vulnerability or cascading consequences). This research develops a method to gather rich, actionable, qualitative data from critical facility managers that can be utilized in combination with hydrodynamic, wind, and precipitation models to assess potential hazard impacts. A pilot study was conducted with critical facility managers in Westerly, Rhode Island USA, using semi-structured interviews and participatory mapping. Interview methods were based on existing practices for vulnerability assessments, and further augmented to obtain data based on hurricane modeling requirements. This research identifies challenges and recommendations when gathering critical facility manager's knowledge for incorporation into storm simulations and contributes to the overall participation and knowledge co-generation framework of natural hazard models.

ACKNOWLEDGMENTS

I want to thank my advisor, Austin Becker, for guiding me through a series of independent research projects that defined my graduate school experience. The freedom he gave me and the international coastal resilience projects he exposed me to allowed for the inspiration of this paper and fueled my passion to prepare communities for climate change. Many thanks to Peter Stempel for developing the methods that enabled this research and for pushing me to become a better thinker. His brilliant insights made my work meaningful and fun. Thanks to Robert Thompson for sharing his positive outlook on life with me and revealing how other cultures are preparing for climate change. Thanks to Christopher Baxter for showing me firsthand how coastal engineers conduct storm and sea level rise vulnerability assessments and for including me in his ocean engineering classes. Thanks to Erin Roberts for helping me overcome challenges and keeping me calm as I completed my thesis work. Thanks to Isaac Ginis and Dave Ullman from the Graduate School of Oceanography for developing and sharing their powerful and accurate hurricane models with me. Thanks to Mark Bennett from Rhode Island's Emergency Management Agency for hiring me as an intern with the Rhode Island's Critical Infrastructure Program. Thanks to Westerly's emergency manager Amy Gryzbowski and Police Chief Richard Silva for connecting me to the critical facility managers of Westerly, Rhode Island. Finally, thank you to Westerly's critical facility managers for sharing their storm concerns with me.

TABLE OF CONTENTS

ABSTRACT	ii
ACKNOWLEDGMENTS	iii
TABLE OF CONTENTS.....	iv
LIST OF TABLES	vi
LIST OF FIGURES	vii
CHAPTER 1: INTRODUCTION.....	1
CHAPTER 2: REVIEW OF LITERATURE	4
2.1 Need for a method to develop actionable qualitative data for models used in disaster risk reduction.	4
2.2 Stakeholder participation and the understanding of their concerns is needed in order for planners to be effective in increasing resiliency of social environmental systems to hazards.....	5
2.3 Data required to make qualitative concern data actionable in DRR models.....	6
2.4 Limitations of publically available CTs	7
2.5 Methodologies we adapted to gather CTs	8
CHAPTER 3: METHODOLOGY	11
3.1 Case Study Westerly Rhode Island Site Selection	11
3.2 Sampling approach.....	12
3.3 Interview instrument design	14
3.4 Interview process	15
3.5 Coding method	17
3.6 Preparing CTs to be incorporated into storm impact models.....	18

CHAPTER 4: RESULTS	21
4.1 FMs could not identify modellable increments.....	22
4.2 FMs identified unmodellable location of concerns.....	24
4.3 FM’s impact component	25
4.4 Storm impact model outputs FM’s impacted concerns in chronological order	25
CHAPTER 5: DISCUSSION	28
5.1 How can existing methods for eliciting vulnerability data be adapted to gather FM’s intra-facility level storm concerns for inclusion in storm impact models? ..	28
5.2 What challenges exist when gathering FM’s concerns for incorporation into storm impact models?.....	29
5.2.1 Challenge 1: The modellable increment identification challenge.....	30
5.2.2 Challenge 2: The unknown locations of concerns challenge	31
5.2.3 Challenge 3: Not asking for CT components for all FM concerns during interviews	32
5.3 How are storm impact models improved by gathering FM’s concerns through a participatory process?.....	32
5.4 Limitations of this approach.....	33
5.5 Conclusion	34
APPENDICES	35
BIBLIOGRAPHY	40

LIST OF TABLES

TABLE	PAGE
Table 1. Methodologies adapted to gather consequence thresholds.	10
Table 2. Standardization of FM's increment component responses	20
Table 3. Total number of concerns, description of concern for each modeled hazard and coding classification of corresponding increment component for 13 Westerly FMs of 11 critical facilities.....	24

LIST OF FIGURES

FIGURE	PAGE
Figure 1. Combining storm simulations with stakeholder’s storm concerns creates a storm impact model.....	2
Figure 2. Current publically available location and fictitious CTs for a WWTP in Westerly, RI. Note the publically available location is not impacted by modeled flooding while two CTs have already been marked as damaged.....	8
Figure 3. Westerly critical facilities included in pilot study	4
Figure 4. Image used as a thought prompt during interviews	16
Figure 5. CT interview collection process	16
Figure 6. FM’s used Google maps satellite views to identify and label locations of concern	18
Figure 7. Storm impact model for Westerly’s critical facilities showing wind and inundation CTs triggered by simulated storm Rhody 30 minutes (top) and two hours (bottom) after Rhody’s storm surge makes landfall. The red pin in front is a CT triggered by one foot of flooding and represents a fire chief’s concern that, “When it floods above a foot here, we can’t reach the homes around the lighthouse.” Yellow pins show where inundation blocks roads.....	26

CHAPTER 1: INTRODUCTION

Coastal communities face increasing risk from coastal storms and sea level rise (Romero & Emanuel, 2017). To address these risks coastal managers employ Disaster Risk Reduction (DRR), the systematic practice of evaluating and reducing risks posed by natural hazards such as storm surge associated with hurricanes (Thomalla, Downing, Spanger-Siegfried, Han, & Rockström, 2006). Incorporating stakeholders concerns through processes such as workshops can improve the accuracy and usefulness of DRR assessments (Messner & Meyer, 2006), and is an essential component of hazard management (Eakin & Luers, 2006).

Current DRR assessments typically use single average vulnerability curves representing damage as a function of depth of flooding, an approach that does not account for more detailed qualitative concerns that may be raised by stakeholders (Aerts et al., 2018). Such concerns include, for instance, the loss of a diary or the short-circuiting of a hospital's generator. In many cases, DRR assessments that account for social factors are not at a fine enough geographic scale for practitioners to use in DRR projects (Carr, Abrahams, Arielle, Suarez, & Koelle, 2015).

Storm impact model definition: A form of hazard impact model that allows a storm simulation to interact with stakeholders concerns (Figure 1).

Figure 1. Combining storm simulations with stakeholder's storm concerns creates a storm impact model.

Storm impact models that combine an individual's qualitative concerns with storm simulations (e.g., the ADvanced CIRCulation model (ADCIRC)) at the intra facility scale have been developed (Stempel, Ginis, Ullman, Becker, & Witkop, 2018). Storm impact models can incorporate a wastewater treatment plant operator's concern that an aeration tank will spill during a storm surge and spread disease within the community it serves. However, methods for gathering qualitative concerns for incorporation into storm impact models at the intra-facility have not been elaborated (Hendricks et al., 2018; Messner & Meyer, 2006; Aerts 2018; Palmer, 2014). Gathering qualitative concerns for incorporation into storm impact models is complex. It requires that aspects of the concern, such as the wind speed at which the concern occurs, be defined in quantifiable terms. For example, incorporating a fire chief's concern that a generator will short circuit due to flooding into a storm impact model requires the generator's location along with the water level that would cause the generator to short circuit.

This research thus seeks to establish and test a method to gather rich qualitative concerns (Doody & Noonan, 2013) with adequate definition for incorporation into storm impact models and DRR assessments. Using critical facility managers (FMs) in Westerly Rhode Island as a case study, it asks the following research questions

RQ 1. How can existing methods for eliciting vulnerability data be adapted to gather FMs intra-facility level storm concerns for inclusion in storm impact models?

RQ 2. What challenges exist as researchers gather FM's concerns for incorporation into storm impact models?

RQ 3. How can storm impact models be improved by gathering stakeholders concerns for inclusion in the model?

The basis for the method tested is drawn from and expands current approaches to vulnerability assessment that address aspects of disaster risk and public engagement related to DRR. After establishing the basis for this approach in the background section, the methodology is subsequently evaluated based on interviews with 15 facility managers (FMs) in Westerly Rhode Island. The paper identifies challenges that exist when gathering FM's concerns for incorporation into storm impact models and how storm impact models can be improved by including stakeholders in storm impact models through participatory assessments.

CHAPTER 2: REVIEW OF LITERATURE

2.1 Need for a method to develop actionable qualitative data for models used in disaster risk reduction.

An increasing body of literature explains that planners should understand and include the concerns of stakeholders (defined here as potentially vulnerable individuals) in the assessment and planning processes when preparing for hazards (Becker, 2013; Paul et al., 2018). This is in part because concerns influence how people behave (Moser & Ekstrom, 2010) and the behaviors of individuals, businesses, and government entities before, during and immediately after disasters dramatically affect impact and recovery (Aerts et al., 2018). To illustrate, when behaviors are ignored during DRR assessments, flood risk can be overestimated by 100% (Haer, Botzen, Moel, & Aerts, 2017). A behavior includes specific responses that reduce exposure (e.g. moving out of harm's way or shutting down a facility). These behaviors are kinds of qualitative data that can be gathered and incorporated into storm impact models. Specific concerns and perceptions vary based on social and cultural factors, therefore, vulnerability varies based on social and cultural factors (Nielsen & Reenberg, 2010). Accounting for concerns in hazard assessment and planning is therefore beneficial.

Although concerns can increase DRR assessment accuracy, most DRR assessments ignore stakeholders concerns because they are difficult to quantify and incorporate into models (Aerts, 2018). Concerns regarding high-order losses (Rose, 2004) or hidden costs (Hienz, 2000) like damages to ecosystems and cultural assets are rarely accounted for even though the loss of these intangible objects are normally

what people bemoan the most after a flood (Green, Wierstra, Penning, & van der Veen, 1994). Instead, most flood risk assessments use single average vulnerability curves representing depth of flooding and damage (Aerts et al., 2018) including HAZUS, the most common DRR assessment tool in the USA (Banks, Camp, & Abkowitz, 2014). In addition to the possibility of the storm impact model output being inaccurate (Stempel et al., 2018) or irrelevant (White et al., 2010), the lack of stakeholder input has serious ramifications for the perceived legitimacy and credibility of modeled outcomes (Schroth, Pond, & Sheppard, 2011).

2.2 Stakeholder participation and the understanding of their concerns is needed in order for planners to be effective in increasing resiliency of social environmental systems to hazards

Directly involving stakeholders in model building processes increases the quality of decisions the model is meant to assist (Salter, Robinson, & Wiek, 2010). Active, iterative and inclusive Participatory Integrated Assessment processes that build models increase the credibility, relevance and legitimacy of the model, and therefore enhances the models ability to connect scientific knowledge with environmental policy (White et al., 2010). Guiding a participant through a boundary object in a workshop or including participants' opinions in the model itself allows participants to shed the 'blackbox' perception of the model and the model's assumptions (Salter et al., 2010; Sheppard et al., 2011; White et al., 2010). In other words, incorporating local knowledge into climate models has allowed stakeholders to validate the models, without having to understand the underlying model's mathematics (Salter et al., 2010). As previously discussed, methods exist for combining stakeholder concerns at the

intra-facility scale in storm simulations to create storm impact models that address these concerns (Stempel et al., 2018), providing that the information gathered is defined sufficiently (e.g. spatial location, depth or velocity at which the concern occurs) (Stempel et al., 2018). The challenge thus becomes gathering qualitative data with adequate definition.

2.3 Data required to make qualitative concern data actionable in DRR models

Combining stakeholder concerns with storm simulations requires several points of data in addition to the qualitative data related to the concern (Figure 2). These five required components are explained below and when combined, make up a complete “Consequence Threshold” (CT).

1. ***The concern*** - An asset or operation the FM perceives can be directly impacted by a storm force. For example, a generator that can be impacted by flooding.
2. ***The accurate location of concern*** – The latitude and longitude of the asset or operation the FM believes can be directly impacted by storm forces. For example, a generator’s location at 41.12345 N and -71.12345 W. (Stempel et al., 2018).
3. ***The modeled hazard*** - A storm force that can be quantified such as inundation depth or wind velocity that is modeled as part of a storm simulation (Stempel et al., 2018).
4. ***The increment*** - The storm force threshold that when exceeded at the location of concern triggers an impact. For example, winds above 100 mph or flooding above 1 foot. (Stempel et al., 2018).

5. ***The impact*** – The outcome if the storm force exceeds the increment at the location of concern. For example, the generator would short-circuit.

2.4 Limitations of publically available CTs

These requirements were initially developed as part of work supporting of a Federal Emergency Management Agency (FEMA) Integrated Emergency Management Course (IEMC) to prepare RI's FMs and emergency managers (EMs) for hurricane response. As part of that work, the University of Rhode Island (URI) and the Rhode Island Emergency Management Agency (RIEMA) developed time incremented impact reports based on combinations of storm simulations and qualitative data (Stempel et al., 2018). To gather specific outcomes for the IEMC, we turned to Rhode Island's publically available vulnerability information for critical facilities. We determined when critical facilities would be damaged because including when critical facilities would be damaged into hurricane training simulations may better prepare EMs for storms (Brecht, 2007).

The E-911 database includes the latitude and longitude for RI's schools, fire departments, police stations, hospitals and other critical facilities around Rhode Island. This database of coordinates helps responders reach these buildings during times of emergency. Since databases are developed based on the particular purpose they are supposed to serve (Liu & Palen, 2010) it is unlikely that these points are at the location within the facility where an impact could occur. Therefore, using these points as vulnerabilities may mislead the storm impact model output because ground elevations are extrapolated based on the latitude and longitude of the given point which are in turn used to see if a critical facility is flooded (Stempel et al., 2018). Therefore, a

critical facility may be marked as safe by a storm impact model, but really should have been marked as damaged by flooding because the location of concern is at a lower elevation than the given point (Figure 2). Since this intra-facility level vulnerability information was not publically available, we decided to collect it ourselves.

Figure 2. Current publically available location and fictitious CTs for a WWTP in Westerly, RI. Note the publically available location is not impacted by modeled flooding while two CTs have already been marked as damaged.

2.5 Methodologies we adapted to gather CTs

Methods for gathering CT components for use in DRR models such as storm impact models are not well elaborated. For instance, there is a framework to incorporate citizen scientists into hydrological models, including flood management Buytaert et al. (2014), these models however do not address the diversity of hazards encountered in storms. Other researchers give guidelines for creating realistic climate change visualizations based on citizen and expert input for use in planning processes (Sheppard et al., 2011). This includes guidelines for engaging community leaders to ensure the outputs are of locations, themes, viewpoints, and local conditions the community cares about. Although this guidance is clear and generalizable, it does not

provide methods to elicit the specific forms of data necessary for storm impact modeling including the storm force (increment) that would cause a facility damage.

This research adopts principals from the vulnerability assessment (R J Cox, 2013) and participatory mapping methodologies (Cadag & Gaillard, 2012) to create a method that gathers actionable concerns for storm impact models. Some vulnerability assessments address all necessary aspects for incorporation into storm impact models, but none has reflected the gathered information in a storm impact model (Table 1).

Since no single study has explored all required CT components for incorporation into a storm impact model this research pilots the methodology presented here. Our method draws on principles from the methodologies identified in Table 1, including using open ended questions to determine stakeholder concerns, storm force increments and associated impacts (Willows, Reynard, Meadowcroft, & Connell, 2003) along with participatory mapping techniques (Cadag & Gaillard, 2012).

Table 1. Methodologies adapted to gather consequence thresholds

<i>Study/vulnerability assessment questionnaire</i>	<i>Aspects necessary to include concerns in storm impact models</i>				
	<i>Defines stakeholder's local concern</i>	<i>Defines location of concern</i>	<i>Defines modeled hazard</i>	<i>Defines increment</i>	<i>Defines impact or outcome</i>
(Vladimir Stenek, 2011)	X	X	X	X	X
(Graciela, K., & Cees, 2012)	X		X	X	X
(Yamaguchi et al., 2007)			X	X	X
(Monioudi et al., 2018)	X		X	X	X
(Reeder & Ranger, 2011)	X		X	X	X
(R J Cox)	X		X	X	X
(Douglas, Kirshen, Li, Watson, & Wormser, 2013)	X		X		X
(Cadag & Gaillard, 2012)	X	X	X		X
(FEMA, 2013)	X		X		X
(Hendricks et al., 2018)	X	X			
(Becker, Matson, Fischer, & Mastrandrea, 2015)	X		X		X
(Hapij, 2011)	X				X
(Willows et al., 2003)	X		X	X	X
(ICF, 2017)	X		X	X	X
(DHS, 2013)	X		X		X
(Rhode Island Emergency Management Agency)	X	X	X		X

CHAPTER 3: METHODOLOGY

3.1 Case Study Westerly Rhode Island Site Selection

The early stage of gathering FM's concerns for incorporation into storm impact models to begin to answer nuanced questions made a case study an appropriate method for exploratory work (Becker, 2013). We partnered with RIEMA to give the study credibility and gain access to FMs within the case study that might otherwise be hesitant to participate because of security threat concerns (Rinaldi, 2004). We selected critical facilities in Westerly (RI) to pilot this approach because RIEMA wanted to analyze Westerly's FM's storm concerns and determine the cascading effects of a storm on those concerns. Since modeling can provide insights into critical facilities interdependencies and recovery after extreme events (Rinaldi, 2004) and Westerly has a relatively small number of critical facilities, RIEMA deemed Westerly appropriate for the study. Westerly is a coastal community on Rhode Island's southern coast with a population of about 18,000 as of 2010 (United States Census Bureau, 2018). The Hurricane of 1938, 1954, and the "Floods of 2010" (a series of rain events that impacted Westerly during March of 2010) all impacted the town and it lost many buildings during Hurricane Sandy due to storm surge and winds that reached 86 mph (sustained at 64.4 mph) in the town (Manning, Carnevale, & Rubinoff, 2014).

3.2 Sampling approach

Gaining access to infrastructure vulnerability information is challenging because it is normally proprietary in nature (Rinaldi, 2004). Therefore, RIEMA introduced us to Westerly's local emergency managers (EMs) who, in turn, provided contact information for FMs. By the nature of their work, local EMs are highly informed about how a storm affects their community (Newkirk, 2001) and are well connected to the FMs in their community. We used FEMA's definition of a RI critical facility as a facility that, "if severely damaged, would reduce the availability of essential community services necessary to cope with an emergency" and "a facility associated with utilities that are required to protect the health and safety of a community" according to the local EM (Mitigation Assessment Team, 2012). These critical facilities include fire departments, police stations, hospitals, and waste water treatment plants among others. Since resiliency policy has been promoted when participants are included in the development of realistic climate visualizations (Sheppard et al., 2011) and FMs can make resiliency policy changes, including FMs in the development of storm impact models may promote storm resiliency actions. FMs will also likely participate in future storm-training simulations. Therefore, creating a method that gathers FMs concerns for incorporation FM's perceptions into storm impact models particularly useful.

We thus asked local EMs to select FMs to interview since FMs are highly informed about their facility (Mendonça & Wallace, 2006) and external resources their facilities rely on (Rinaldi, 2004). We sent selected FMs an invitation through email and called them over the phone to schedule a time to meet while simultaneously explaining the overall goal of the research Paul et al. (2018). Additional FMs were interviewed as the

opportunities presented themselves (Patton & Appelbaum, 2003). For Westerly, this resulted in 13 FMs from 11 critical facilities including five fire departments, the police station, the dispatch center, the ambulance corps, the wastewater treatment plant, the water department, one electrical distribution substation and the department of public works (Figure 3). There are about 30 critical facilities in Westerly. We were unable to interview individuals from Westerly's hospital, school system, telephone networks, and natural gas facilities mostly because of the security threat posed by sharing the information.

Figure 3. Westerly critical facilities included in pilot study.

3.3 Interview instrument design

In developing next steps to address the needs of FMs as they incorporate their concerns into storm impact models, ground truthing assumptions can help focus further research efforts (Becker, 2013). As a first step toward this goal, this exploratory survey gathered a wide range of FM's storm concerns for incorporation into storm impact models in order to identify the challenges and opportunities the method presented.

The instrument primarily rested on a section from Becker, 2013's interview prompt since it had already been used to explore the storm concerns of the stakeholders in a Rhode Island port organization. To gather concerns and identify the challenges and opportunities our method posed, we asked open-ended questions that prompted a wide

variety of concerns. Many of these questions were adapted from questions from RIEMA's Critical Infrastructure Program vulnerability assessment, the Department of Homeland Security's Critical Infrastructure vulnerability assessment, the UKCIP's threshold identification methods, the ICF's Climate vulnerability assessment, and results from the Sandy Mitigation Assessment Team for critical facilities. For additional prompts and questions, see Appendix I. RIEMA's Critical Infrastructure Program reviewed the survey instrument along with two members of URI Marine Affairs Department and an ex-FM.

3.4 Interview process

In a few cases, an FM's colleagues joined the interviews, which may have contributed to the FM's comfort and is recommended for risk communication meetings (Chess et al., 1988). To begin interviews, we explained the study was meant to gather FM's storm concerns for incorporation into storm impact models (Chess et al., 1988; Paul et al., 2018). Then we explained the underlying storm models that the storm simulation utilized relied on (as recommended by White et al. (2010)). We next used an illustration of a fictional *CT* for a petroleum facility triggered by storm surge from Hurricane Carol at 4:30 pm on August 5th, 1954 overlaid on a modern day map at the Port of Providence as a thought prompt to show the interviewee how their responses could be used (Figure 4). We told FMs their names would be kept confidential and quotes from their responses would not be identified and attributed to them individually, but might be discovered due to the limited number of critical facilities in Westerly.

Then we asked for the FM's immediate concerns to a storm. FMs were encouraged to consider storm impacts on other parts of the community (e.g. roads) that could affect

their facility. We listened to FM's concerns, which is important for a risk communication spokesman (Chess et al., 1988), and then worked to identify the remaining *CT* components for each concern FMs identified (Figure 5).

Figure 4. Image used to explain potential of storm models during interviews.

Figure 5. CT interview collection process.

When an FM identified a storm concern, we asked the FM to identify the location of concern on a navigable Google Map satellite (15 meters to 15 cm resolution) and/or street view using our laptop (Figure 6). We also asked the FM to identify the concern increment using an open response threshold-identification method similar to the UKCIP and ICF methods (Monioudi et al., 2018; Wilson, 2015). For example, we asked, “What inundation level would cause the impact you mentioned?” Although FMs were encouraged to identify the storm forces that the underlying storm models used (rain, wind, storm surge, standing inundation and wave height) FMs elaborated on other weather concerns they had.

If FMs had trouble coming up with storm concerns, follow-up prompts were used to stimulate the conversation (see appendix I). Not all questions were covered in each interview, and the precise wording and order in which the questions came up were not constrained (Merriam, 1988) since interviews were focused on subjects that matched the interviewee’s knowledge and points that the interviewee brought up (Lewis & Sheppard, 2006). The questions also gathered information on the FM’s career experience and responsibilities at the facility. Interviews lasted between 1 and 2 hours.

3.5 Coding method

We digitally recorded and transcribed the interviews in full with the help of a hired transcription service (200 pages). In order to answer our three research questions we identified and analyzed all *CT* components mentioned by FM and major themes that occurred throughout the interviews using Excel and NVivo. We coded interviews line by line and identified themes in the data through an analytic induction method, a form of grounded theory described by (Ratcliff, 1994) as an iterative process.

Figure 6. FM’s used Google maps satellite views to identify and label locations of concern.

3.6 Preparing CTs to be incorporated into storm impact models

We standardized *CT* components before incorporating them into the storm impact models. As mentioned earlier, *CTs* require five components for incorporation into storm impact models.

1. **The concern** - An asset or operation the FM perceives can be directly impacted by a storm force. For example, a generator that can be impacted by flooding.
2. **The accurate location of concern** – The latitude and longitude of the asset or operation the FM believes can be directly impacted by storm forces. For example, a generator’s location at 41.12345 N and -71.12345 W. (Stempel et al., 2018).
3. **The modeled hazard** - A storm force that can be quantified such as inundation depth or wind velocity that is modeled as part of a storm simulation (Stempel et al., 2018).

4. **The increment** - The storm force threshold that when exceeded at the location of concern triggers an impact. For example, winds above 100 mph or flooding above 1 foot. (Stempel et al., 2018).
5. **The impact** – The outcome if the storm force exceeds the increment at the location of concern. For example, the generator would short-circuit.

To standardize these components for inclusion into storm impact models, we wrote the impact component in similar terms the FM used during the interview. Also, to standardize increment responses, the following actions were taken (Table 2).

Table 2. Standardization of FM's increment component responses.

<i>Language used by FM</i>	<i>Example</i>	<i>Increment chosen</i>	<i>Rationale</i>
Threshold range	"The impact would occur when the water reached 1 to 2 feet here."	1 foot	Choosing the lowest value in range makes the storm impact model output more conservative.
Hurricane category	"The impact would occur when winds reached category 1."	74 mph	This is the sustained wind speed required to be considered a category 1.

CHAPTER 4: RESULTS

The results below are themes identified while analyzing the interviews and the gathered *CT* components. These themes are referenced in the discussion to answer our three research questions.

RQ 1: How can existing methods for eliciting vulnerability data be adapted to gather FM's intra-facility level storm concerns for inclusion in storm impact models?

Our *CT*-gathering method identified 197 concerns from 13 FMs representing 11 critical facilities. We identified every *CT* by showing FMs potential uses of their responses through an illustration of a *CT* (Figure 4), asking for the FM's concerns using prompts (see appendix I) and then identifying remaining *CT* components on the FM's own terms (Figure 5). We restated the FM's concern and specifically asked for each *CT* component for almost every *CT*.

After asking for FMs concerns to storms at the beginning of the interview, FM's most often referenced the FM's previous experiences with storms. Once the FM exhausted these initial concerns, asking the FM about unprecedented storms enabled the collection of more *CTs*. For example, questions like, "What concerns do you have if flooding reached one foot where we are standing now?" or "What concerns do you have if a storm with 150 mph winds passed over this facility?" both prompted additional *CTs*.

FMs guided us to almost every location of concern using the navigable Google Maps satellite view during the interview. In some cases, FMs located and marked the location of concern themselves on the Google Map. The Google Map's Street View allowed FMs to identify locations of concern that were hard to identify on the satellite view.

RQ 2: What challenges exist as researchers gather FM's concerns for incorporation into storm impact models?

4.1 FMs could not identify modellable increments

74 of 197 CTs could not be incorporated into storm impact models because the increment was unknown, not explicitly asked for, or was not given in units the underlying storm model currently uses (Table 3). All but nine increments were coded as uncertain. This means the FM was willing to estimate the increment, but said they unsure of its accuracy. 40 of the consequence thresholds were coded as "unknown". Increments were uncertain or unknown with regards to wind speed and inundation level because the FM knew a precise increment existed for the concern, but did not know it. One FM illustrated this dilemma when he said, "for an antenna to break, each one has a rated wind speed velocity-- and you have to look up each and every antenna because there's multiple types of antennas, different manufacturers." Also, FMs had to consider if the equipment had been properly installed and mounted properly.

Only one increment was modellable for rainfall and wave height and no increment was modellable for storm surge because FM's do not know rainfall rates in inches per hour or storm surge velocities in any modellable increment (Table 3). One FM illustrated this when he said, "When it rains, it rains hard! That's all I know."

Similarly, for storm surge, another FM explained that he would not drive his fire truck through water, “If you could see a decent current with any type of like a ripple to it.”

Many concerns and associated impacts were based on the FM’s experiences with the Floods of 2010 and Hurricane Sandy. When asked for the increment that would cause the impact, FM’s would ask the researcher for wind speed/storm surge levels of Hurricane Sandy and the rainfall amounts of Floods of 2010. FMs also tried to look up these increments online during the interview. One FM illustrated a commonly given unmodellable increment with the quote, “Whatever the 2010 floods were, how much rain we got [caused the impact].”

Table 3. Total number of concerns, description of concern for each modeled hazard and coding classification of corresponding increment component for 13 Westerly FMs of 11 critical facilities.

Modeled hazard	Concern most commonly impacted by modeled hazard	Increment classification			
		Increment was modellable	Increment was unknown	Increment was given in unmodellable unit	Increment was not explicitly asked for
Inundation (78)	cars, roads, generators, electrical panels, facility specific equipment (wells, clarifiers)	56	5	9	9
Wind (70)	cars, power/telephone lines, roofs, personnel	44	19	2	5
Rain (18)	power/telephone lines, generators, electrical panels	1	14	2	1
Wave height (4)	boats, roads	1	1	0	2
Storm surge (5)	home gas, water and electrical systems, bridges	0	1	3	1

4.2 FMs identified unmodellable location of concerns

FMs said that 40 of the 197 concerns could occur at many locations in Westerly and did not specify those locations. For example, one FM was concerned that a storm would flood fire hydrants and prevent his crew from reaching them. However, the FM did not know the locations of the fire hydrants that were at risk to flooding and therefore they could not be incorporated into the storm impact model. FMs gave the following concerns that had many locations and did not identify those locations so without further research could not be incorporated into storm impact models.

1. *Roads*
2. *Telephone lines*
3. *Power lines*
4. *Sewage/rain man hole covers*
5. *Residential oil tanks*
6. *Residential propane tanks*
7. *Residential basements*
8. *Fire hydrants*

9. *Personnel*

10. *Vehicles*

RQ 3: How can storm impact models be improved by gathering stakeholders concerns for inclusion in the model?

4.3 FM's impact component

This method gathered a wide range of FM's storm impacts. 26 of the impact components included an FM's immediate response to the impact and 34 included an FM's long-term response to the impact. Some impacts had both immediate and long-term responses. For example, the water department's wells need to be shut down immediately if water reaches them and then require a long-term chemical treatment process once the floods recede.

4.4 Storm impact model outputs FM's impacted concerns in chronological order

After incorporating the gathered *CTs* into a storm impact model that used a hypothetical storm, called Hurricane Rhody as the underlying storm simulation (Ginis, 2017) we found that 23 wind and 21 inundation *CTs* were triggered. The following illustrates and describes the 44 *CTs* triggered by Rhody in chronological order.

Figure 7 . Storm impact model for Westerly’s critical facilities showing wind and inundation CTs triggered by simulated storm Rhody 30 minutes (top) and two hours (bottom) after Rhody’s storm surge makes landfall. The red pin in front is a CT triggered by one foot of flooding and represents a fire chief’s concern that, “When it floods above a foot here, we can’t reach the homes around the lighthouse.” Yellow pins show where inundation blocks roads.

Hurricane Rhody's winds knock out Westerly's power and no emergency responder has communications, aside from cell phones and hand held radios. 24 to 48 hours later, Rhody's storm surge makes landfall. Within 30 minutes of landfall, the storm surge blocks a fire department from reaching sections of homes (Figure 7). Within the next 30 minutes, Westerly's water distribution pipes may be broken and the water supply of the town may be contaminated. Between hour 1.5 and 2, the storm pushes water further inland and impacts the WWTP, which requires the plant to operate as a primary facility for 10 to 21 days and receive essential materials from another WWTP. Between hour 2 and 2.5 Westerly's main power station is impacted, and requires a mobile substation. Also, the water department requires two wells to shut down and chemically treated for 72 hours.

CHAPTER 5: DISCUSSION

This research gathered FM's intra-facility level concerns for incorporation into storm impact models and identified challenges and opportunities the process posed. Identifying the challenges presented while gathering FM's intra-facility level concerns for incorporation into storm impact models contributes to answering Moser 2010's call for "applied research that links geographic information to practitioners concerns" and Messner and Meyer 2006's call for the development of "multi-criteria tools in order to include non-monetary intangible damage into the assessment framework of flood damage analysis". The following section will discuss this work's three guiding research questions and the following three associated contributions this research makes to the literature.

1. The development and analysis of a method to gather FM's concerns for incorporation into storm impact models.
2. The identification of challenges of gathering FM's knowledge for incorporation into storm impact models.
3. The identification of improvements to storm impact models made by developing the models with FMs using a participatory approach.

5.1 How can existing methods for eliciting vulnerability data be adapted to gather FM's intra-facility level storm concerns for inclusion in storm impact models?

Participatory mapping using Google Maps and a set of exploratory open-ended questions was an effective way to gather FM's storm concerns for incorporation into storm impact models. Beginning this process by asking for the FM's storm concerns led to a list of concerns the FMs had already experienced. Many of the concerns

mentioned at the beginning of interviews had been impacted by the Floods of 2010 and Hurricane Sandy. Once all *CT* components were gathered for these historical concerns, then the researcher could bring up concerns the FM had yet to experience to determine more *CTs*. This process may have gathered many *CTs* because it allowed the FM to guide the conversation and made the FM feel like the researcher was considering their concerns (Chess, Hance, & Sandman, 1988). Also, beginning interviews with storm impacts that have already occurred may have made the research more relevant and less abstract to FMs, which likely made it easier for FMs to identify *CT* components.

FMs easily identified location of concerns on the navigable Google Map satellite view during the interview. When the satellite view was limited, the Google Map's Street View also helped identify the location of concern. Identifying the location of concern on a Google map made it easier to record FM's concerns and identify remaining *CT* components. For example, identifying locations of concern helped identify increments because we could explain to the FM that increments should be for *the location the FM identified on the map*. This was useful because FMs tended to identify inundation increments in feet above sea level instead of feet above ground level at the location of the concern.

5.2 What challenges exist when gathering FM's concerns for incorporation into storm impact models?

The most common challenges when gathering FM's concerns for incorporation into storm impact models are uncertainty of the increment, uncertainty of the location of concern and recording all *CT* components during the interview.

5.2.1 Challenge 1: The modellable increment identification challenge

Researchers conducting climate change vulnerability assessments have found that determining the quantified weather force that would cause a particular impact on an Indonesian community was, “considerably more challenging than [determining] qualitative descriptors like hotter, drier and rainier” (Gustafson, Cadena, & Hartman, 2018). Also, Shackley and Deanwood 2003 found stakeholders were reluctant to quantify climate forces and associated impacts because quantification “precisely defines the model scenario and is less likely to be correct than less accurate qualitative statements.” This research found that stakeholder’s uncertainty in identifying increments also extends to storms.

To help future researchers gather FM’s concerns for incorporation into storm impact models we recommend researchers collect increments with FMs by asking a set of standardized closed questions with consistent anchors after an FM mentions a concern. For example, the researcher should ask, “Would the concern be impacted when water reached between 0 and 1 foot (anchor 1), 1 to 2 feet (anchor 2), or above 2 feet (anchor 3) at the location of concern?” Since many FMs referenced previous storms that impacted their facility to identify the increment, we recommend researchers use the increments of the biggest and most recent storms to affect the interviewee’s area as the anchors since the interviewee have already experienced those events. Another way to standardize the increment identification process could be by showing a set of photographs or realistic visualizations of the storm forces. For example, a researcher could show photographs of 60, 100, and 140 mph winds in another area or realistic visualizations for the FM’s facility under various inundation

levels. Finally, if interviewees are not comfortable giving an increment, or even a range of values, researchers should ask for the concern's make and model so the researcher can look up the increment after the interview. In order to promote effective policy through model building, iterative processes like this are key (White et al., 2010).

5.2.2 Challenge 2: The unknown locations of concerns challenge

20% of FM's concerns could be impacted at many locations. For example, FMs were concerned about power lines, roads and fire hydrants. Without identifying the exact latitude and longitudes of these concerns, it is not possible to incorporate them into storm impact models. To incorporate *CTs* with multiple, currently unknown locations into storm impact models we recommend the creation of datasets with these locations. Determining the locations of concern for sewage manhole covers, fire hydrants, telephone/power lines and the remaining concerns with many unknown locations was outside of the scope of this work. However, we found an existing data set for the locations of roads in Westerly, which allowed us to conduct a roadway low point analysis for Westerly to account for FM's road inundation concerns (Figure 8). When water reached above 8" at the low point on the road, the road was flagged as impassable since that is the depth some Westerly FMs are blocked. Similar analyses can be done for remaining *CTs* that have vague locations of concern once locations of concerns are gathered for those *CTs*.

5.2.3 Challenge 3: Not asking for CT components for all FM concerns during interviews

Although the method presented here gathered 197 concerns, researchers did not hear 34 concerns mentioned by the FMs during the interview and therefore did not ask for the remaining, required *CT* components.

To prevent researchers from missing concerns identified by FMs, we recommend marking each location of concern on the Google Map as the interviewee identifies the location and then filling out remaining components later in the interview. We recommend using a satellite map with more advanced labeling functions than Google Maps (e.g. Google Earth). This will make it easier for the interviewer to label all *CT* components directly on the map as the FM explains their concerns during the interview.

5.3 How are storm impact models improved by gathering FM's concerns through a participatory process?

Gathering FMs concerns for incorporation into storm impact models through a participatory approach improves storm impact models by increasing their accuracy and relevance to participants. Traditional DRR assessment outputs like HAZUS struggle to provide actionable data regarding relevant, specific local concerns for communities to use to prepare for disasters (Paul et al., 2018). Caution needs to be used when analyzing HAZUS hurricane damage outputs for particular facilities because results are based on average damages to similar facilities under similar circumstances (Vickery et al., 2006). Traditional DRR outputs like HAZUS also do not take into account intangible consequences of storms like losses of cultural assets

(Messner & Meyer, 2006) even though these losses are what people normally bemoan the most after a flood (Green, Wierstra, Penning, & van der Veen, 1994). Therefore, including FMs concerns using a participatory process allows storm impact models to output more specific local concerns than relying on generalized damage curves and likely makes the models more credible, actionable and relevant to participating FMs. As storm simulations increase in accuracy (Aerts et al., 2018), on the ground vulnerability information will need to be gathered with increasing precision using a participatory method to most effectively use these models. Gathering this information in a standardized way may eventually allow FMs to use storm impact models to predict and prepare for real storms in the days and hours leading up to landfall (Brecht, 2007; Ginis, 2017).

5.4 Limitations of this approach

Most increments identified by FM's were uncertain. However, the storm impact model this research created did not account for this uncertainty because we did not gather that information from FM's during interviews. When an FM said they were unsure of the increment, we asked the FM to identify a particular value. If the FM identified a range of values, we chose the lowest for incorporation into the storm impact model and ignored the rest of the range. Precisely quantifying the storm force at which an impact occurs makes the output appear more certain than it is (Shackley & Deanwood, 2003). When experts identify a point which a certain piece of infrastructure will fail, it is likely that the point has a good deal of uncertainty, which is not easily shown by the point (Cooke & Goossens, 2004). Future research that gauges the uncertainty of stakeholders increments will enable storm impact models to

show uncertainty when developing visualizations of the data (Liu & Palen, 2010) and will make the models more useful to decision makers (Couclelis, 2003). Future research should be conducted to validate increments identified in this research before using them to justify DRR activities.

5.5 Conclusion

This paper presents an exploration of a methodology that gathers FM's rich concerns at the intra- facility level for incorporation into storm impact models. More than 100 concerns were gathered for incorporation into storm impact models using principals from participatory mapping and vulnerability assessment literature. After incorporating these concerns into storm impact models, we found the chronological order a hypothetical storm would impact those concerns. Gathering FM's concerns for inclusion into the storm impact models likely increases the relevance and credibility of the model's outputs to participating FMs. This research also identified challenges of gathering FM's concerns for incorporation into storm impact models and presents recommendations to overcome those challenges. This includes FM's uncertainty of specific storm force increments that would cause impacts. This research thus calls for an exploration as to why FM's are uncertain about increments and a way to identify increments using a closed-response method that accounts for FM's uncertainty. As storm simulations increase in accuracy and applicability, researchers will need to develop standardized methods to gather on-the-ground vulnerability information in a participatory manner to increase the relevance and credibility of storm impact models. This research acts as a guiding step in the creation of such a method.

APPENDICES

Appendix I

FM in person interview: Consequence threshold identification

Interview Instrument Goal:

1. Attains data that can answer the following questions:
 - a. In what ways do Facility Managers (FMs) perceive their assets/facilities/operations as being vulnerable to quantifiable storm-related forces?
 - b. How can researchers elicit quantifiable, local, consequence thresholds from FMs for incorporation into storm models?

MATERIALS PROVIDED AT INTERVIEW:

1. Printed questionnaire (below)
2. Navigable Google map of FM's facility area (on laptop)
3. Consent form

INTERVIEW PROCESS:

Respondent Name: _____ Date: _____
Interviewer: _____ Organization: _____
Position: _____

1. Briefly describe URI's storm models including the resolution, the required units, the associated visualizations, potential uses and consequence thresholds. Explain how this interview enhances storm models and may benefit the FM.

We are creating a method to elicit quantifiable local, information from facility managers (FMs) for incorporation into storm models in order to enhance disaster planning and preparedness because URI's storm models are now precise enough to incorporate storm impacts on individual facilities. URI and Rhode Island Emergency Management Agency (RIEMA) will use your responses to improve storm impact identification methods and better prepare Rhode Island's facilities for storms including your own.

To include aspects of facilities or communities into URI's storm models, we need four pieces of information:

1. **CONCERN:** What is the specific place or item that is of concern (e.g., a generator, storage tank(s)) and where is it located (identify on Google map)?
2. **HAZARD:** What storm related forces including storm surge (depth, velocity and direction), wind (velocity, direction), riverine and ocean inundation (depth), rainfall (inches per hour), significant wave height (feet), time after the event, or combination of hazards causes the damage or interruption?

3. *IMPACT: What impacts are you concerned with? (e.g., generator gets flooded and stops operating, residents evacuate, road becomes impassable). This is the result of the event on the concern. We are especially interested in examining different thresholds of impact, e.g., two feet of water disrupts operations, two meters of water damages electrical systems. This depends on the fourth aspect, increment.*

4. *INCREMENT: The level(s) at which various impacts occur, this is a specific measurement (e.g, wind speed, water level), or combination of measurements, and can be a range or a minimum/maximum the impact could occur.*

Example

CONCERN: Electrical generator at x location

HAZARD: Inundation

INCREMENT 1: One foot inundation at x location,

IMPACT 1: Generator falters

INCREMENT 2: Two foot inundation at x location

IMPACT 2: Generator short circuits and facility turns off

1.1 INFO: *There are 23 questions, but I won't be asking you all of them since some depend on your response to others.*

1.3 IMPORTANT: Interview purpose, storm models, consequence threshold, explanation of units storm models can incorporate.

2. SCENARIO

I would like you to imagine that you have prepared your facility and community for a storm heading this direction. As you answer these questions, please consider the potential impacts this storm could have on your facility and community. The storm can be of any magnitude and the associated impacts are the ones that are most important to you and the operation of this facility.

Every time you identify a concern, I need you to locate the concern on a Google Map and then I will need you to identify the increment and the impact.

2.1 CONFIDENTIALITY:

The detailed geographic points, facility names, and specific vulnerabilities gathered today will be shared with RIEMA, your community's emergency manager, you, my lab at URI and its trusted partners (e.g., DHS Office of Cyber and Infrastructure Security, collaborating researchers affiliated with other Universities). This data will be used by URI and its trusted partners to:

- 1. Develop CT collection methods.*
- 2. Develop hazard impact modeling tools, such as hurricane damage forecasting tools that can be run as a storm approaches.*
- 3. Develop damage estimation tools that will be used to make more general damage predictions and not include any facility specific identifiers.*
- 4. Develop 3-dimensional visualizations of hurricane impacts for your and other critical facilities. These visualizations will be available to RIEMA, you, used*

for presentations at conferences, used in educational settings and may be published in scientific journals. Although no facility identifiers or detailed point data will be included (e.g., highly specific location or vulnerability data), locations may be recognizable to people who are familiar with the context depicted

3. CONSEQUENCE THRESHOLD COLLECTION

This section enables the interviewee to identify consequence threshold components. However, in many cases the questions will require the interviewer to develop remaining components of consequence thresholds by furthering the interviewee's ideas (CONCERN, HAZARD, IMPACTS, and/or INCREMENTS).

Experience driven questions

1. Have you had experience with storms at your facility?
 - a. If answer→ identify consequence threshold
 - b. If unknown→ ask next question
 - i. **(repeat questions a and b for every question)**
2. Do you have a way to prepare/account for/plan for these kinds of events?
3. Consider this storm hits your facility...
 - a. What would your immediate concerns be?
 - b. What impacts would be difficult to address in the aftermath?
4. In what storm conditions has your facility been damaged or otherwise effected in the past?

Asset driven questions

5. Does your facility have any significant assets or areas that could be impacted by storms? A significant asset or area is something critical to operation/function of the facility.
6. How could a significant asset of your facility be impacted by storms?
7. Does your facility have redundancies (a generator, a secondary access road) that are meant to be used in response to storms?
8. Can you identify consequence threshold components for any external resources (electric power, natural gas, water, wastewater, communications, transportation, or cyber (mainframes, cloud provider's, server farms) your facility depends on?

Storm hazard driven questions

9. In what storm conditions is your facility unable to operate?
10. What storm conditions is your facility designed to withstand?
11. At what point would your facility be impacted by storm surge?
12. At what point would your facility be impacted by wind?
13. At what point would your facility be impacted by inundation?
14. At what point would your facility be impacted by rainfall?
15. At what point would your facility be impacted by a wave?
16. Imagine a storm that is unprecedented for Westerly is approaching...(repeat 9 through 15)

Document driven questions

17. Does your facility have a written physical security plan/business continuity plan/that:
 - a. identifies risks to a storm?
 - b. evaluates the potential damage or loss to the facility due to a storm?
 - c. identifies strategies to limit or control potential consequences of an incident caused by a storm?
 - d. identifies storm response and recovery procedures for life safety, human resources, core operations, information technology, and other necessary organizational functions?
18. Does your facility have operational manuals that specify storm conditions for when your facility is unable to operate?
19. Do industry guidelines (federal guidelines/design specifications) specify storm conditions that your facility can withstand?
20. Has your facility conducted post storm assessments that identified consequence threshold components?

Miscellaneous

21. How have storms impacted facilities similar to yours?
22. Do you think facilities of your type have similar impact ranges?
23. If you could change or add one thing about your facility to prepare it for a storm what would it be?
24. Do you know the FMs of the facilities that your facility relies on and would be willing to answer the previous questions?
 - a. If yes, can you connect me with them?
25. Did you prepare for these questions after our first telephone discussion?
26. Of the impacts we have determined today, which ones are most important to you?
27. Is there anything else you would like to add?

Interviewee background

28. To help me analyze my research, I would like to know about your work as a facility manager.
29. How many years of experience do you have preparing the facility you currently work at for storms?
30. Do you create, execute or contribute to plans to keep your facility functioning after disruptive events such as a storm? If yes, please explain what this work entails.
31. Do you create, execute or contribute to resiliency related activities? These activities include conducting impact analyses or risk assessments that take into account your facilities significant assets (assets essential to the function of the facility), functions (e.g., IT systems), personnel, and supply chains. If yes, please explain what this work entails.

3.1 IMPORTANT: Develop consequence thresholds while referencing google map and input data into consequence thresholds collection table during interview.

Thank you for meeting with me and have a great day!

BIBLIOGRAPHY

- Aerts, J., Botzen, W., Clarke, K., Cutter, S., Hall, J., Merz, B., . . . Kunreuther, H. (2018). Integrating human behaviour dynamics into flood disaster risk assessment. *Nature Climate Change*, 1.
- Banks, J. C., Camp, J. V., & Abkowitz, M. D. (2014). Scale and resolution considerations in the application of HAZUS-MH 2.1 to flood risk assessments. *Natural Hazards Review*, 16(3), 04014025.
- Becker, A. H. (2013). *Building seaport resilience for climate change adaptation: Stakeholder Perceptions of the problems, impacts, and strategies*. Stanford University.
- Becker, A. H., Matson, P., Fischer, M., & Mastrandrea, M. D. (2015). Towards seaport resilience for climate change adaptation: Stakeholder perceptions of hurricane impacts in Gulfport (MS) and Providence (RI). *Progress in Planning*, 99, 1-49.
- Brecht, H. (2007). Geo-technologies in hurricane research. *Cartography and Geographic Information Science*, 34(2), 153-154.
- Buytaert, W., Zulkafli, Z., Grainger, S., Acosta, L., Alemie, T. C., Bastiaensen, J., . . . Dewulf, A. (2014). Citizen science in hydrology and water resources: opportunities for knowledge generation, ecosystem service management, and sustainable development. *Frontiers in Earth Science*, 2, 26.
- Cadag, J. R. D., & Gaillard, J. (2012). Integrating knowledge and actions in disaster risk reduction: the contribution of participatory mapping. *Area*, 44(1), 100-109.

- Carr, E. R., Abrahams, D., Arielle, T., Suarez, P., & Koelle, B. (2015). Vulnerability assessments, identity and spatial scale challenges in disaster-risk reduction. *Jàmbá: Journal of Disaster Risk Studies*, 7(1), 1-17.
- Chess, C., Hance, B. J., & Sandman, P. M. (1988). *Improving dialogue with communities: a short guide for government risk communication*: Division of Science and Research, New Jersey Department of Environmental Protection.
- Cooke, R. M., & Goossens, L. H. J. (2004). Expert judgement elicitation for risk assessments of critical infrastructures. *Journal of Risk Research*, 7(6), 643-656. doi:10.1080/1366987042000192237
- Couclelis, H. (2003). The Certainty of Uncertainty: GIS and the Limits of Geographic Knowledge. *Transactions in GIS*, 7(2), 165-175. doi:doi:10.1111/1467-9671.00138
- DHS. (2013). *Threat and Hazard Identification and Risk Assessment Guide Comprehensive Preparedness Guide 201, Second Edition*.
- Doody, O., & Noonan, M. (2013). Preparing and conducting interviews to collect data.
- Douglas, E., Kirshen, P., Li, V., Watson, C., & Wormser, J. (2013). Preparing for the rising tide.
- Eakin, H., & Luers, A. L. (2006). Assessing the vulnerability of social-environmental systems. *Annu. Rev. Environ. Resour.*, 31, 365-394.
- FEMA. (2013). *Hurricane Sandy in New Jersey and New York-Building Performance Observations, Recommendations, and Technical Guidance*.
- Ginis, I., Kincaid, C., Hara, T., Rothstein, L., Ullman, D. S., Huang, Chawla, A., Valle, D., Bender, M. Massey, . Cox, D. W., Hashemi, M. (2017). Modeling

the combined coastal and inland hazards from high-impact hypothetical hurricanes. *Annual project performance report prepared for the DHS Coastal Resilience Center. Retrieved from the principal investigator.*

- Graciela, P. G., K., M. M., & Cees, v. W. (2012). Coping strategies and risk manageability: using participatory geographical information systems to represent local knowledge. *Disasters*, 36(1), 1-27. doi:doi:10.1111/j.1467-7717.2011.01247.x
- Green, C., Wierstra, E., Penning, P., & van der Veen, A. (1994). Vulnerability refined: analysing full flood impacts *Floods Across Europe*: Middelsex University Press.
- Gustafson, S., Cadena, A. J., & Hartman, P. (2018). Adaptation planning in the Lower Mekong Basin: Merging scientific data with local perspective to improve community resilience to climate change. *Climate and Development*, 10(2), 152-166.
- Haer, T., Botzen, W., Moel, H., & Aerts, J. C. (2017). Integrating Household Risk Mitigation Behavior in Flood Risk Analysis: An Agent-Based Model Approach. *Risk Analysis*, 37(10), 1977-1992.
- Hapij, A. W. (2011). *Multidisciplinary assessment of critical facility response to natural disasters: the case of Hurricane Katrina*: American Society of Civil Engineers (ASCE).
- Hendricks, M. D., Meyer, M. A., Gharaibeh, N. G., Van Zandt, S., Masterson, J., Cooper, J. T., . . . Berke, P. (2018). The Development of a Participatory

- Assessment Technique for Infrastructure: Neighborhood-level Monitoring towards Sustainable Infrastructure Systems. *Sustainable Cities and Society*.
- Heinz, J. (2000). *The hidden costs of coastal hazards: Implications for risk assessment and mitigation*: Island Press.
- ICF. (2017). *Climate Risk and Vulnerability Assessment Framework for Caribbean Coastal Transport Infrastructure*. Retrieved from Geneva, Switzerland:
- Lewis, J. L., & Sheppard, S. R. J. (2006). Culture and communication: Can landscape visualization improve forest management consultation with indigenous communities? *Landscape and Urban Planning*, 77(3), 291-313.
doi:10.1016/j.landurbplan.2005.04.004
- Liu, S. B., & Palen, L. (2010). The New Cartographers: Crisis Map Mashups and the Emergence of Neogeographic Practice. *Cartography and Geographic Information Science*, 37(1), 69-90. doi:10.1559/152304010790588098
- Manning, H., Carnevale, M., & Rubinoff, P. (2014). *Rhode Island Coastal Property Guide*. University of Rhode Island's Coastal Resources Center and Rhode Island Sea Grant.
- Mendonça, D., & Wallace, W. A. (2006). Impacts of the 2001 world trade center attack on new york city critical infrastructures. *Journal of Infrastructure Systems*, 12(4), 260-270.
- Merriam, S. B. (1988). *Case study research in education: A qualitative approach*: Jossey-Bass.

- Messner, F., & Meyer, V. (2006). Flood damage, vulnerability and risk perception—challenges for flood damage research *Flood risk management: hazards, vulnerability and mitigation measures* (pp. 149-167): Springer.
- Mitigation Assessment Team. (2012). *Definitions of Critical Facilities and Risk Categories*.
- Monioudi, I. N., Asariotis, R., Becker, A., Bhat, C., Gooden, D. D., Esteban, M., . . . Witkop, R. (2018). Climate change impacts on critical international transportation assets of Caribbean Small Island Developing States (SIDS): The case of Jamaica and Saint Lucia. *Regional Environmental Change* (Special Issue 1.5 °C and Small Island Developing States.).
- Moser, S. C., & Ekstrom, J. A. (2010). A framework to diagnose barriers to climate change adaptation. *Proceedings of the national academy of sciences*, 107(51), 22026-22031.
- Newkirk, R. T. (2001). The increasing cost of disasters in developed countries: A challenge to local planning and government. *Journal of Contingencies and Crisis Management*, 9(3), 159-170.
- Nielsen, J. Ø., & Reenberg, A. (2010). Cultural barriers to climate change adaptation: A case study from Northern Burkina Faso. *Global environmental change*, 20(1), 142-152.
- Patton, E., & Appelbaum, S. H. (2003). The case for case studies in management research. *Management Research News*, 26(5), 60-71.

- Paul, J. D., Buytaert, W., Allen, S., Ballesteros-Cánovas, J. A., Bhusal, J., Cieslik, K., . . . Stoffel, M. (2018). Citizen science for hydrological risk reduction and resilience building. *Wiley Interdisciplinary Reviews: Water*, 5(1).
- R J Cox, K. P. a. R. M. C. (2013). *Climate Risk Assessment for Avatiu Port and Connected Infrastructure*. Retrieved from New South Wales, Australia:
- Ratcliff, D. E. (1994). Analytic induction as a qualitative research method of analysis. *University of Georgia*. Retrieved on March, 1, 2010.
- Reeder, T., & Ranger, N. (2011). How do you adapt in an uncertain world?: lessons from the Thames Estuary 2100 project.
- Rhode Island Emergency Management Agency. *Rhode Island Assessment Tool Handbook*.
- Rinaldi, S. M. (2004). *Modeling and simulating critical infrastructures and their interdependencies*. Paper presented at the System sciences, 2004. Proceedings of the 37th annual Hawaii international conference on System Sciences.
- Romero, R., & Emanuel, K. (2017). Climate change and Hurricane-like extratropical cyclones: Projections for North Atlantic polar lows and medicanes based on CMIP5 models. *Journal of Climate*, 30(1), 279-299.
- Rose, A. (2004). Economic principles, issues, and research priorities in hazard loss estimation *Modeling spatial and economic impacts of disasters* (pp. 13-36): Springer.
- Salter, J., Robinson, J., & Wiek, A. (2010). Participatory methods of integrated assessment—a review. *Wiley Interdisciplinary Reviews: Climate Change*, 1(5), 697-717.

- Shackley, S., & Deanwood, R. (2003). Constructing social futures for climate-change impacts and response studies: building qualitative and quantitative scenarios with the participation of stakeholders. *Climate Research*, 24(1), 71-90.
- Sheppard, S. R., Shaw, A., Flanders, D., Burch, S., Wiek, A., Carmichael, J., . . . Cohen, S. (2011). Future visioning of local climate change: a framework for community engagement and planning with scenarios and visualisation. *Futures*, 43(4), 400-412.
- Stempel, P., Ginis, I., Ullman, D. S., Becker, A., & Witkop, R. (2018). Real-Time Chronological Hazard Impact Modeling.
- Thomalla, F., Downing, T., Spanger-Siegfried, E., Han, G., & Rockström, J. (2006). Reducing hazard vulnerability: towards a common approach between disaster risk reduction and climate adaptation. *Disasters*, 30(1), 39-48.
- United States Census Bureau. (2010). QuickFacts Westerly CDP, Rhode Island.
- Vickery, P. J., Skerlj, P. F., Lin, J., Twisdale Jr, L. A., Young, M. A., & Lavelle, F. M. (2006). HAZUS-MH hurricane model methodology. II: Damage and loss estimation. *Natural Hazards Review*, 7(2), 94-103.
- Vladimir, S., C., Connell, O., Palin, S., Wright, B., Pope, J., Hunter, J., McGregor, W., Morgan Ben Stanley, R., Washington D., Liverman, H., Sherwin, P., Kapelus, C., Andrade, J., Pabón (2011). *Climate Risks and Business Port Terminal Marítimo Muelles el Bosque Cartagena, Colombia*.
- White, D. D., Wutich, A., Larson, K. L., Gober, P., Lant, T., & Senneville, C. (2010). Credibility, salience, and legitimacy of boundary objects: water managers'

assessment of a simulation model in an immersive decision theater. *Science and Public Policy*, 37(3), 219-232. doi:10.3152/030234210x497726

Willows, R., Reynard, N., Meadowcroft, I., & Connell, R. (2003). *Climate adaptation: Risk, uncertainty and decision-making. UKCIP Technical Report: UK Climate Impacts Programme.*

Wilson, G. (2015). *Climate Change Adaption Report for the Felixstowe Dock and Railway Company.*

Yamaguchi, S., Ikeda, T., Iwamura, K., Naono, K., Ninomiya, A., Tanaka, K., & Takahashi, H. (2007). *Development of GIS-based flood-simulation software and application to flood-risk assessment.* Paper presented at the 2nd IMA International Conference on Flood Risk Assessment.